STUDENT HIX SOFTWARE SYSTEM (SMSS) REHOST(U) AIR COMMAND AND STAFF COLL MAXWELL AFB AL A G DECELLES ET AL APR 88 ACSC-88-0700 MD-H192 422 1/2 UNCLASSIFIED F/G 12/5 NL




OTIC TILE CUEY

CONTROL CONTRO



AD-A192 422





REPORT NUMBER 88-0700
TITLE STUDENT MIX SOFTWARE SYSTEM (SMSS) REHOST

AUTHOR(S) MAJOR ARTHUR G. DECELLES, USAF MAJOR RICHARD M. JENSEN, USAF

FACULTY ADVISOR MAJOR JOHN P. BUCKNER, ACSC/DO

SPONSOR MAJOR JOHN P. BUCKNER, ACSC/DO

Submitted to the faculty in partial fulfillment of requirements for graduation.

AIR COMMAND AND STAFF COLLEGE AIR UNIVERSITY MAXWELL AFB, AL 36112-5542

AI	92	422
<i>y</i>	· 2	7 7 7 7 -

		REPORT D	OCUMENTATIO	N PAGE	Form Approved OMB No. 0704-0188						
1a. REPORT SE UNCLASSI		IFICATION		16. RESTRICTIVE MARKINGS							
2a. SECURITY	CLASSIFICATIO	N AUTHORITY		3. DISTRIBUTION SYATEMENT OF REPORT							
2b. DECLASSIF	ICATION/DOV	NGRADING SCHEDU	J.E	Approved for public release; Distribution is unlimited.							
4. PERFORMIN	G ORGANIZAT	ION REPORT NUMBE	R(S)	5. MONITORING	ORGANIZATION RE	PORT NU	IMBER(S)				
88-0700				 							
6a. NAME OF ACSC/EDC		ORGANIZATION	6b. OFFICE SYMBOL (if applicable)	7a. NAME OF MO	ONITORING ORGAN	IZATION					
6c. ADDRESS (City, State, an	d ZIP Code)		7b. ADDRESS (Cit	ty, State, and ZIP C	ode)					
Maxwell	AFB AL 3	6112-5542									
8a. NAME OF ORGANIZA		DNSORING	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMEN	T INSTRUMENT IDE	NTIFICAT	ION NUMBER				
8c. ADDRESS (City, State, and	I ZIP Code)		10. SOURCE OF I	UNDING NUMBERS						
				PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO	WORK UNIT ACCESSION NO.				
11. TITLE (Incl	ude Security C	lassification)		<u> </u>							
-	-	•	(U)				•				
12. PERSONAL	***				******						
Decelles		G., Major, USA 113b. TIME CO	AF; Jensen, Ric		RT (Year, Month, E	Day) 15	. PAGE COUNT				
		FROM	то	1988 Apri		,,,	129				
16. SUPPLEME	NTARY NOTA	rion									
17.	COSATI	CODES	18. SUBJECT TERMS (Continue on revers	e if necessary and	identify	by block number)				
FIELD	GROUP	SUB-GROUP									
							·				
(ACSC). seminars expertis Mix Soft conjunct document computer the data and the balancin successf assignme	The concis desige, and faware Systion with sthe reh code and handling programmig capabilul that ints for A	ept of mixing ned to increase cilitate selfem (SMSS) is a prioritized mixed and use of and user into a capabilitie ity, and the control of th	se the exposure improvement fee used at the school in the school in the second strains as a second strain of the second strain of the second strain of the second strain operation; it is a second strain operation; it is second strain operation.	etudent chara of each student student from model to maintain students cenith 158 per second the Sec	leteristics a lent to differ multiple instant in student of s to seminars ersonal compu- vas designed SMART integral ed SMSS drama em. The relation generate the CURITY CLASSIFICA INCLASSIFIED	erent of tructor lata and terms. The terms of the terms o	ckgrounds within experiences and rs. The Student nd, in is report and includes the ke advantage of oftware package, ly increases SMSS is so rd mix student				
ACSC/EDC	F RESPONSIBLE Maxwe 1		12-5542	(205) 293	Include Area Code) 3–2867	22c Of	FFICE SYMBOL				
	HOAWEL	1 11 D UL 2011	L JJ76	(203) 29.	, 2001						

DD Form 1473, JUN 86

Previous editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE

This report documents the rehost and use of the Student Mix Software System (SMSS) for the Zenith 158 personal computer. SMSS is used at the Air Force Air Command and Staff College (ACSC) to maintain characteristic and background data on students and, in conjuction with prioritized mixing rules, assigns students to seminars. The rehosted SMSS dramatically improves balancing capability, and the over-all utility of the system. The rehosted SMSS is so successful that it is already in operation; it was used to generate the third mix student assignments for ACSC class of 1988.

The authors wish to publicly acknowledge the assistance and support of many people who supported the completion of this project. Special thanks and recognition is given to Major John Buckner, USAF, who patiently answered the many questions necessary to finalize the rehost products. We also thank Captain Ronald Ford, USAF, who assisted in the acquisition of the GW-BASIC compiler used in this project.

This project includes over 3,000 lines of computer source code which is listed in the SMSS User Manual (Appendix A) and is maintained on three 5 1/4" computer diskettes (Appendix B of original report only). The computer code for this project may be obtained by contacting the ACSC Mix Master, ACSC/DO, Maxwell AFB, AL 36112-5564. Requestor must supply three MS-DOS formatted, double sided, double density, 5 1/4" diskettes.

This research project is submitted to simplify and optimize a process that is key to the education of all students at ACSC, that of the seminar mix. We sincerely hope that future classes capitalize on the benefits and opportunities that a balanced seminar provides, a balance achieved as a result of the rehosted SMSS.



Accesi	on For	,				
DTIC	ounced					
By Distribution /						
A	vailability	Codes				
Dist	Avail and Specia					
A-1						

-ABOUT THE AUTHOR-

Major Arthur G. Decelles is from Storrs, Connecticut. He graduated from the University of Connecticut in 1972 with a Bachelor of Arts degree in Mathematics and a minor in Computer Science. In 1983 he completed his Masters degree in Business Administration with an emphasis on computer based systems management from the University of Wyoming. Major Decelles received his Air Force commission in 1975 (Officer Training School) and has held positions at Headquarters Military Airlift Command (MAC); the 90th Strategic Missile Wing, Strategic Air Command; and Headquarters Electronic Systems Division (ESD), Air Force Systems Command. He has four years experience as a computer programmer/analyst satisfying MAC's Command and Control software and Computer Simulation modeling needs. At ESD, he managed the only Air Force program dedicated to reducing the exploding costs associated with the acquisition of Mission Critical Computer Resources. Major Decelles' technical experience includes an extensive knowledge of varied computer hardware systems, and the ability to program in seven different computer languages. He is a 1983 graduate of the Air Force Squadron Officer School. Major Decelles is married to the former Rita Desautels of Willimantic, Connecticut and they have two sons, Timothy and Andrew.

Major Richard M. Jensen is from Brea, California. He attended the United States Military Academy and graduated from California State University, Fullerton with a Bachelor of Arts degree in Mathematics and a Bachelor of Science degree in Computer Science in 1973. Later, he completed a Master of Arts degree in Computer Sciences from the University of Texas at Austin. Major Jensen was commissioned in the United States Air Force in 1975 and has held positions at Headquarters, Air Training Command; Headquarters Air Force; the National Emergency Airborne Command Post (Organization of the Joint Chiefs of Staff); and the Air Force Military Personnel Center. He is a graduate of the Air Force Squadron Officer School and Air Command and Staff College. Major Jensen and his wife, Laurel, have two children, Mark and Amanda.

-TABLE OF CONTENTS-

Preface		 					111
About the Authors		 					iv
List of Illustrations		 •	•	 •	 •	•	٧i
CHAPTER ONE - INTRODUCTION TO STUDENT	MIXING	 					1
History of Automated Mixing		 					2
Purpose of this Paper		 		 •	 •	•	3
CHAPTER TWO - THE NEED TO REHOST SMSS		 					5
SMSS Defects and Deficiencies		 					6
Benefits of Rehosting SMSS		 •		 •	 •	•	8
CHAPTER THREE - CONCLUSION		 					11
Third Mix Comparisions		 •				•	11
Recommended Changes		 •		 •	 •	•	14
BIBLIOGRAPHY		 •				•	17
APPENDICES:							
Appendix A - SMSS User's Manual		 					19
Annuality D - CMCC Committee Software							

-LIST OF ILLUSTRATIONS-

FIGURES

FIGURE	1	 Rehosted	SMSS	Third	Mix	Results								12
FIGURE	2	 Original	SMSS	Third	Mix	Results						_		13

Chapter One

INTRODUCTION TO STUDENT MIXING

Student mixing is integral to the operation of the Air Force Air Command and Staff College (ACSC) at Maxwell AFB, Alabama. In fact, the mixing of ACSC students is directly linked to the mission of the school. The ACSC mission ". . . to enhance the professional knowledge, skills, and perspectives of mid-career officers for increased leadership roles in command and staff positions" (3:1) led to the establishment of several goals. Of particular importance to this paper are the school's goals to provide a forum for each student's professional contribution, and an environment for the personal and professional growth of each student. (3:1) The concept of mixing and balancing student characteristics and backgrounds within seminars is designed to achieve these goals by increasing the exposure of each student to different experiences and expertise, and facilitating self-improvement feedback from multiple Faculty Instructors (FIs). (3:3) The student mixing concept is such an integral part of the school's mission that the Director of Operations appoints a mix master for the entire school and each squadron commander assigns an FI as the focal point for student mixing requirements.

In addition to the extensive people resources assigned to the student mixing effort, the school is actually structured to facilitate the mixing concept. The school is currently made up of four squadrons, each consisting of up to eleven seminars of approximately thirteen students each. The school and squadron mixers balance the seminars by evenly assigning officers of like characteristics and backgrounds across seminars. For example, each seminar has at least one International Officer (IO) assigned, as well as one Army officer. Other types of officers, like females and minorities, are spread across seminars as evenly as possible. This balancing process occurs three times during the ACSC school year. With the exception of IOs and SOS faculty, ACSC students must be assigned to new seminars (different FIs) each mix. addition, the number of seminar classmates with whom a student was previously assigned is minimized. To accompdate for the graduation of all the IOs at the end of the second mix, one seminar in each squadron is closed down for the third mix.

Assigning approximately 570 ACSC students into 44 seminars may seem like a trivial task, but when you add some thirty different rules and constraints to a process that occurs three times each school year the task quickly becomes complex and time-consuming. The basic idea behind the

mixing rules is to provide the widest range of experience possible to expose each student to new and different ideas, career fields, and service and country backgrounds. It is also important that each seminar contain representative experience and expertise as each major area of the ACSC curriculum is studied. Topics such as tactical, strategic and space operations and acquisition, logistics and budgeting functions are more quickly grasped and understood when first-hand knowledge is available within the seminar. Expertise within each seminar is especially desirable since the students present and lead the majority of the seminar lessons themselves. A well balanced student mix requires the constant and repetitive consideration of numerous factors, a task particularly well suited for a computer.

HISTORY OF AUTOMATED MIXING

Student mixing was first automated as the "Seminar Automated Mixer" (SAM) which ran on the mainframe Honeywell computer at Gunter AFS. The system was extremely slow requiring seven to ten days to receive the output reports. In addition, the SAM system violated most of the mixing rules and required extensive manual manipulation by the school and squadron mixers. (8:—) It took approximately two months prior to the start of the ACSC school year to input and process the student data, and produce just the initial reports. (4:2) Although a breakthrough from the totally manual method of mixing, the SAM system was terribly unresponsive and quite inefficient by today's standards. It was subsequently replaced with the current automated system, the "Student Mix Software System" (SMSS).

SMSS was designed to run on the Zenith 120 computer using the ZBASIC programming language and the CONDOR III Relational Data Base Management System (DBMS), systems which were readily available at ACSC. (4:3) This configuration brought the automated mixing capability directly into the mix master's office, and provided real-time, hands-on access. incorporated all the mixing rules, heuristics and factors needed by the school at the time, and it sharply reduced the amount of manpower required to produce a final mix from about 200 hours (4:31) to about 40 hours. (5:--) The system was severly constrained, however, by the limited memory capacity of the Z-120 (256K Bytes RAM) and the limited report formatting capability of CONDOR III and ZBASIC. SMSS was also unnecessarily constrained by a three tiered priority scheme for implementing the mixing rules; a constraint which severely handicapped the mix masters ability to properly balance student characteristics and skills automatically. (5:--) In the final analysis, SMSS was a giant step forward because it brought a much needed capability directly into the user's office. By providing initial reports within an hour of initiation SMSS was much more responsive than the old SAM system; so responsive that the mix master could repeatedly refine and rerun the mix several times a day. Unfortunately, as will be seen in the next chapter, this capability would become the most redeeming feature of a system which was plagued with problems.

PURPOSE OF THIS PAPER

The heart and soul of this project is the computer software and User's Manual attached to this paper (appendix A and B). The software provides the actual data manipulation, mixing, and report producing capabilities, while the User's Manual provides the ability to easily use and maintain the system. By far the majority of the effort went into the development of these products. The purpose of this paper is to establish the absolute need for these products, and consequently, justify the effort spent.

This chapter introduced the ACSC student mixing concept and provided some background into the development of SMSS. Chapter two assesses the need for rehosting the SMSS system by identifying the many shortcomings of SMSS and exploring the many benefits realized in rehosting the system. Lastly, chapter three provides some conclusions about the SMSS rehost effort, how well the new SMSS operates in comparison to the old system, and what improvements could be made to make it even better.

Chapter Two

THE NEED TO REHOST SMSS

SMSS was a tremendous step forward for ACSC student mixing but it definitely had its problems and limitations. By providing real-time, hands-on access and rapid turnaround, SMSS provided a responsiveness that was previously only dreamed of. But some SMSS functions just didn't work correctly and several others left a lot to be desired. These defects and deficiencies were important ingredients which fed into the decision to rehost SMSS, but the predominant reason for rehosting the SMSS system was its inherent lack of flexibility.

Like the earlier SAM system, SMSS was unable to accommodate even minor changes to the mixing process. Since the development of SMSS, two student characteristics ceased to be factors in the mixing process: that of "Communication Skills" and "Air Research Institute" students. (5:--) wasn't difficult for SMSS to ignor these traits, but it was definitely a problem to incorporate new mixing rules into SMSS. The student characteristic of "Space Operations Experience" became a major mixing factor in 1987. The only way the mix master could make SMSS handle this new mixing requirement was to use the existing "Communication Skills" field to identify students with "Space Operations Experience." This was a brute force method to make SMSS handle the new requirement, but the SMSS reports still reflected the "Communications" label. However. SMSS could not handle any other additional characteristics, even the brute force way. The ACSC mix master needed the capability to handle additional student mixing characteristics, especially considering the overwhelming emphasis being placed on "Joint Service Experience" in upcoming ACSC classes. This is a capability that SMSS currently lacks.

Another major change since the development of SMSS was an ACSC decision to standardize the school's computer hardware and software. In late 1986 the school made an investment of about \$225,000.00 in purchasing 65 Zenith 158 (IBM-compatible) personal computers, and acquiring the SMART integrated software package for each machine. (6:--) The Z-158 has more than twice the internal memory (640K Bytes RAM) of the Z-120 and, consequently, isn't as constrained in the number and type of computer application programs that can be used. In addition, the SMART software package provided a capability which integrated four vital computer applications within one system: wordprocessing, data base management, telecommunications, and spreadsheet. In essence, the school decided to standardize, for the foreseeable future, on the capabilities and user

interfaces inherent in these systems. To maximize the return on the school's investment in standard computer resources, the ACSC Director of Operations set an objective to get ". . . the faculty proficient and using the SMART software system." (2:1) However, as the ACSC mix master soon discovered, SMSS would not run on the \mathbb{Z} -158s, and it was not compatible with the SMART data base manager. (5:—) This was an SMSS limitation that needed to be rectified.

SMSS clearly lacked the flexibility necessary to accommodate even the most minor mixing changes. This chapter will further assess the need to rehost SMSS by first identifying SMSS defects and deficiencies, and then by exploring the many benefits to be gained in rehosting the SMSS system.

SMSS DEFECTS AND DEFICIENCIES

SMSS has been used since 1986 to maintain student data, perform the student mixing, and generate the required reports. During that time, several difficulties were encountered in using SMSS. (5:—) The ACSC mix master was repeatedly interviewed to identify the problems and limitations of the current SMSS system, and to determine the existing student mixing requirements and practices. This information was further supplemented by reviewing related Air University and ACSC regulations dealing with seminar organization, rank, and procedures, and by inspecting the actual SMSS computer code and documentation. The result was the identification of several SMSS defects and deficiencies. A defect refers to a capability that doesn't work correctly, while a deficiency refers to a capability that is difficult to use or incorporate. Both defects and deficiencies have hidden costs associated with them.

The first defect of SMSS is that the mixing module incorrectly assigns Seminar Leaders (SLs) and Assistant Seminar Leaders (ASLs). The school has a very strict procedure for assigning SLs and ASLs, and the assignment rules change depending on the mix being processed. (1:1) The SMSS mixing module assigned students that were either not eligible for the position, or didn't assign students who were. The result was several hours of manual checking by the mix master to insure the SLs and ASLs were correctly assigned. (5:—) This was such a cumbersome task that, eventually, the mix master started pre-assigning students to seminars and to SL/ASL positions manually within the SMSS data base module. This one SMSS defect cost several hours of mix master time each mix, and considerably reduced the randomness and flexibility of the mixing process.

Another defect of the SMSS mixing module is the inaccurate statistical report summaries that it produced. (5:--) This defect had an indirect, yet more significant, cost associated with it. The mix master could get the correct mix statistics by generating SMSS data base reports using CONDOR III capabilities. This requires minimal effort by the mix master, but, the balancing capabilities of the SMSS mixing module strongly depends upon the student statistics in maintains. (4:58-97) Consequently, the

inaccurate statistics gave the mixing module a false indication of seminar bulance, and directly affected student assignments. The result is the inability of SMSS to properly balance seminars, the prime SMSS function. Ineffective seminar balancing cost several hours of manual changes each mix by the school and squadron mixers to achieve an acceptable balance, a job that SMSS was created to do and which it should have done night by itself.

The last SMSS defect is that the mixing module periodically caused the computer to "hang-up". (8:--) This defect is an innitant to the mix master because the only way to get out of this condition is to re-start the computer and re-run the mix. (5:--) Fortunately, this condition occurs infrequently and cost very little in time and effort, however, it demonstrates the immaturity of the SMSS system. The SMSS mixing module contains recursive computer code (code that calls itself) and unstructured computer code. (4:58-97) Such programming practices lead to conditions that cause computers to "hang-up" and make it nearly impossible to maintain the system. All three of these SMSS defects need fixing, but the mix master could often tollerate them more than he could the other SMSS deficiencies.

The most significant deficiency of SMSS is the inadequate control it provides to the mix master over mixing rule priorities. SMSS was developed using a three tiered priority scheme which enabled the mix mester to designate each mixing rule as being either "Always Important", "Sometimes Important", or "Not Important". (4:21) With the requirement to mix students on eighteen different characteristics, this priority scheme didn't provide the capability needed to define the relative importance of each rule during a given mix. As a result, the mix master had to adjust and re-run the mix several times to even come close to the desired results. (5:--) This deficiency caused several hours of mix master time in re-running the mix, and in manual adjustments to seminar assignments afterwards. The developers of SMSS recognized the balancing inefficiencies of the system and suggested an additional computer program be written to adjust the seminar assignments made by the mixing module. (4:32) It is absolutely ridiculous to write a computer program to do the job that the original computer program is suppose to do. The three tiered priority scheme incorporated within SMSS unnecessarilly constrained the mix master, it caused the SMSS mixing module to work harder and longer than was really required, and in the end it caused poor mix balances. The seminar imbalances produced by SMSS are the direct result of an inadequate mixing rule priority scheme.

Another deficiency of SMSS is its poor report generation capability. As noted by the original developers, SMSS "..., does not automatically produce the final report in the correct format." (4:32) This deficiency is attributable to the limitations of the CONDOR III DBMS which provides all the information necessary for the Student Statistical Report, but which cannot handle the required report format. SMSS also lacks the capability to provide real-time, ad hoc reports. (5:--) The ACSC mix

master is constantly called upon to provide special purpose, one-time reports, especially between mixes. Although this is a major requirement of the mix master, SMSS is deficient in the support it provides in this area.

Three of SMSS's capabilities don't work correctly and two others are deficient in providing all the capability the mix master's needs. These defects and deficiencies, along with the general inability of SMSS to handle changing conditions, led to the decision to rehost SMSS.

BENEFITS OF REHOSTING SMSS

Solving all the problems of the original SMSS system required much more than quick patches, it involved a complete rehosting and redesign of the system. SMSS needed the ability to run on the ACSC standard Z-158 computer using the SMART data handling and user interface capabilities. The SMSS mixing module needed to be rewritten to correct the current defects and to "optimize" the mix balancing capability. Last but not least, a comprehensive User's Manual needed to be developed. This was the scope of the SMSS rehost effort, an effort which would provide the mix master with enormously increased capabilities and the ability to produce the mixing products in a fraction of the time. The remainder of this section explores the benefits possible in four areas of SMSS: defects, deficiencies, flexibility, and maintainability.

Just fixing the three SMSS defects identified earlier would be strong justification for the rehost effort. Correcting the Seminar Leader and Assistant Seminar Leader assignment defect would save the time required to manually recheck or pre-assign students each mix. Likewise, fixing the SMSS mixing module statistics defect would save time by reducing the number of manual reassignments necessary to achieve an acceptable mix balance. Correcting the SMSS computer "hang-up" defect would save the time needed to re-run the mix and would help restore user confidence in the SMSS system. Fixing the three SMSS defects would save an estimated 20 hours each mix in the time and effort required by the school and squadron mixers to produce the necessary mixing products.

Correcting the SMSS deficiencies would not only save user time, but would provide capabilities comparable to the "responsiveness" provided by the original SMSS system. Replacing the three tiered priority scheme of SMSS with a ten level priority scheme would provide the mix master with a control over student mixing never thought possible. It would save the time required to re-run the mix over and over, and would "optimize" the student mixes. Providing the capability to generate correctly formatted reports directly with the SMSS data base module would save the time required for the mix master to reformat reports with a word-processor and would support the mix master in the real-time generation of adhoc reports. Fixing the SMSS deficiencies would provide the mix master with tremendous new capabilities; the capability to "optimize" the mixing process, and the

capability to produce reports as needed. These new SMSS capabilities alone would justify the SMSS rehost effort, but even greater benefits are possible.

Correcting the SMSS defects and deficiencies were major determinants in rehosting the SMSS system, but the predominant reason for rehosting SMSS to the Z-158 was to make the SMSS system more flexible, useable, and maintainable. The original SMSS is unable to handle additional student characteristics and mixing rules. One of the benefits of the rehost would be the addition of five unlabeled mixing identification fields which are ready for immediate use. SMSS would also be designed to allow even more fields to be added. Further flexibility would be attained by rehosting SMSS to IBM-compatible computer hardware (Z-158), and by providing three different user definable SMSS configurations: dual floppy disks, hard disk and floppy disk, and RAM disk with either hard or floppy disk. These features would increase the flexibility and useability of SMSS by expanding the number of computers SMSS could potentially run on.

Rehosting the SMSS to the Z-158 under the SMART integrated software package would make SMSS more useable and maintainable. The SMART data base manager would provide SMSS with a standard ACSC user interface capability, and would provide the SMSS user with an automated "help" feature for each SMSS menu option. The SMSS "help" feature would inform the user of each menu option available and would provide textual rational for choosing an option. A critical product for the useablity of the SMSS system is adequate user documentation. The SMSS rehost effort would produce a comprehensive User's Manual (Appendix A) which would thoroughly explain the design of the rehosted SMSS, and would guide the user through each step of the SMSS mixing process. The User's Manual would also be invaluable for modifying the SMSS computer code and for maintaining the system in the future. In addition, all SMSS computer code would be structured and documented to further enhance the maintainability of the system.

The rehost of SMSS corrected defective and deficient capabilities, and provided powerful, new capabilities for using and maintaining the system. The next chapter will compare the performance of the rehosted SMSS to the original system, and suggest improvements which could make it even better.

Chapter Three

CONCLUSION

Although the SMSS rehost effort required a complete redesign of the system and rewrite of the computer code, the original SMSS name was not changed. SMSS is an automated mixing concept, a concept which really didn't change with the rehost. The rehost fixed SMSS defects and deficiencies and provided additional capabilities, but the mixing concept stayed the same. In addition, the original SMSS was developed as a prototype system (4:3), a prototype which never reached full maturity. Consequently, the original name was retained.

The success of the SMSS rehost effort can be judged in its performance against the performance of the original system. The rehosted SMSS was used to generate the third mix student assignments for ACSC class 1988. The original SMSS was also run for purposes of comparison. The rest of this chapter compares the performance of the two systems and recommends improvements which can make the rehosted SMSS even better.

THIRD MIX COMPARISONS

Figures 1 and 2 show comparative results from the rehosted SMSS and the original SMSS for the third mix of ACSC class 1988. The results for only the 3821st Student Squadron are shown, but are representative of the entire school. The figures show the number of students SMSS assigned to each seminar which possess the characteristic listed on the left. Those student characterstics which are not completely balanced are underlined for clarity purposes. Prior to running this mix, the mix master assigned the highest rule priority of "9" to the following characteristics: Army; Reserves, ANG, Civilians, USMC, or Navy; Minorities; Females; and Medical, Legal, or Chaplains. The lowest rule priority of "0" represents characteristics which the mix master is not concerned with balancing. Priority "O" was assigned to the following characteristics: Line AD AF; No Degree; HO Experience: Academy Graduate: Captains: and Bomber or Missile Experience. Comparable priorities were assigned by the mix master using the "Always", "Sometimes", and "Not Important" scheme of the original SMSS system. Figures 1 and 2 reflect the actual student assignments of the two SMSS systems, and do not contain any manual adjustments.

In every instance, the rehosted SMSS outperformed the original SMSS in balancing the third mix student characteristics. The only non-zero

FIGURE 1. Rehosted SMSS Third Mix Results.

FIGURE 2. Original SMSS Third Mix Results.

priority characteristics that the rehosted SMSS failed to perfectly balance were "Unaccommpanied" and "Pilots" which were assigned the lowest two non-zero priorities for this mix. Even the "Unaccompanied" category was only off from a perfect balance by two students, and the "Pilot" category was off by one student. On the other hand, the original SMSS failed to balance six characteristics of concern, including one with the highest priority (Medical,Legal,Chaplain/88XX,89XX,9XXX). The other unbalanced characteristics of interest are: Strat Ops; Acq/Log Exp; Pilots; Navigators; Space Exp; and Unaccompanied. In addition, the original SMSS was often off in its balance by a factor of four. Clearly, the rehosted SMSS outperformed the original system. In fact, it actually "optimized" the third mix.

In addition to optimizing the third mix, the rehosted SMSS proved many of its other capabilities. The portability of the system was demonstrated by running the system on the Z-120 computer with a Gemini Board. This hardware configuration allows the Z-120 to emulate an IBM-compatible computer. The rehosted SMSS ran at about half the speed as on the Z-158, but otherwise operated without difficulty. The user-friendly, menu-driven interface of the rehosted SMSS was demonstrated by the ability of a novice user, the 3824 STUS mixer, to operate the system with minimal assistance. The system's flexibility was demonstrated by successfully using an unlabeled characteristic field during the mixing process. The student information transferred from the original SMSS data base for "Strategic Operations Experience" was flawed. The flexibility of the additional characteristic fields enabled the mix master to quickly recover from this condition without having to manually edit each student record. Last, but not least, the new mixing module correctly assigned all the Seminar Leaders and Assistant Seminar Leaders. The rehosted SMSS clearly met all the performance objectives and exceeded the expectations of all concerned.

RECOMMENDED CHANGES

One limitation of the rehosted SMSS system became apparent during processing of the third mix. The SMSS mixing module is designed to assign the SLs and ASLs before making any other assignments, just as the original SMSS did. This gives the assignment of SLs/ASLs an unintended, artificial priority above all other mixing rules. (7:—) It also severely limits the school and squadron mixers ability to manually reassign students assigned to these positions, and requires that the student dates of rank be rechecked if any manual reassignments are made. If the assignment of SLs and ASLs were moved from the SMSS mixing module to the SMSS data base module, all students could be manually reassigned by the mix master without regard to the final determination of the SLs and ASLs. Besides providing additional capability, this change would provide even more flexibility and randomness to the mixing process.

The rehosted SMSS has dramatically reduced the workload of the school and squadron mixers. It provides much better products, with greater

flexibility, in about the same amount of time as the original system. But, regardless how good the rehosted SMSS, no automated mixing system will ever totally remove all manual adjustments. There are always person unique mixing factors, such as personality, which cannot be automated, but which will always play an important role. The rehosted SMSS "optimizes" the mixing process and, as a tool, provides a tremendous capability to the mix master; a capability which is highly flexible, useable, and maintainable, and which will continue to satisfy the school's future student mixing needs.

-BIBLIOGRAPHY-

A. REFERENCES CITED

Official Documents

- 1. Air University. Seminar Organization and Responsibilities, ACSCR 35-2, Maxwell AFB, AL. 1 September 1987.
- 2. Air University. ACSC SMART Survey, ACSC/DO, Air Command and Staff College, Maxwell AFB, AL. 26 January 1988.

Unpublished Materials

- Air University. Operations Handbook, Academic Year 1988, Air Command and Staff College, Maxwell AFB, AL. 1988.
- 4. Ritchhart, Kenneth M., Major USAF and Simmons, Robert L., Major USAF. ACSC Project 86-2120, The Student Mix Software System (SMSS). Research Study prepared at the Air Command and Staff College, Air University, Maxwell AFB, AL. April 1986.

Other Sources

- 5. Buckner, John P., Major, USAF. ACSC Mix Master, Air Command and Staff College, Maxwell AFB, AL. Multiple Interviews: Oct-Dec 87.
- 6. Ford, Ronald D., Captain, USAF. Chief ACSC Information Systems, Air Command and Staff College, Maxwell AFB, AL. Interview: Oct 87.
- 7. Hansen, Steven L., Major, USAF. 3824 STUS Mixer, Air Command and Staff College, Maxwell AFB, AL. Multiple Interviews: Feb 88.
- 8. Romer, Irving, F., Major, USAF. Former ACSC Mix Master, Air Command and Staff College, Maxwell AFB, AL. Interview: Jan 88.

B. RELATED SOURCES

Official Documents

9. United States Air Force. Rank, Procedures, and Command, AFR 35-54, Maxwell AFB, AL. 15 September 1981.

CONTINUED

Other Sources

- 10. Innovative Software's SMARTWARE. The SMART Data Base Manager. PO Box 15998, Lenexa, KS. 66215-9990, 1986.
- 11. Innovative Software's SMARTWARE. The SMART System Manual. PO Box 15998, Lenexa, KS. 66215-9990, 1986.

Constitution of the second of the second second of the sec

COCCOSC RECOCCOS PROBLEM RECOCCOS RECOCCOS PROBLEM PROCESSOR PROBLEM P

- 12. Zenith Data Systems. Microsoft GW-BASIC Compiler User's Guide, Version 3.2. Manual: 595-3900-01, St. Joseph, Michigan, 49085, 1982.
- Zenith Data Systems. Microsoft GW-BASIC Compiler User's Reference, Version 3.2. Manual: 595-3865-01, St. Joseph, Michigan, 49085, 1982.
- 14. Zenith Data Systems. Microsoft GW-BASIC Interpreter, Version 2. Manual: 595-3161-04, St. Joseph, Michigan, 49085, 1982.
- 15. Zenith Data Systems. Microsoft MS-DOS, Version 3. Volume I III, 595-3705-01/02/03, St. Joseph, Michigan, 49085, 1884.

----APPENDICES-

Appendix A

THE PROPERTY OF THE PROPERTY O

STUDENT MIX SOFTWARE SYSTEM (SMSS)

USER'S MANUAL



TABLE OF CONTENTS

List of Illustrationsiii
CHAPTER ONE SMSS OVERVIEW
CHAPTER TWO INSTALLING AND STARTING SMSS. 3 2.1 The SMSS Release Disks. 3 2.2 Runtime Disk Configurations. 3 2.3 Setup Steps. 4 2.4 Running SMSS. 6 2.4.1 Disk Option Screen. 6 2.4.2 SMSS Main Menu. 7 2.4.3 Menu Selection Rules. 7 2.4.4 Help Screens. 8
CHAPTER THREE FILE MAINTENANCE. 11 3.1 Build Student Records From Another Disk. 11 3.2 Add Student Records Manually. 13 3.3 Edit Existing Student Record. 14 3.4 Delete Student Record. 15 3.5 Designate Student Numbers. 15 3.6 Edit Environment Record. 15 3.7 Delete International Officers. 20 3.8 Post Mixer Tentative Assignments. 20
CHAPTER FOUR PERFORM MIXING
CHAPTER FIVE PRODUCE REPORTS
CHAPTER SIX MIXMASTER'S CHECKLIST
AFPENDICES: Appendix One Student File

Appendix	Two SMART Project Files - Program Listings	43
Appendix	Three SMSS Mixer Program - Program Listing	77
Appendix	Four SMSS.BAT - Program Listing	01

LIST OF ILLUSTRATIONS

FIGURES

Figure	2.1		SMART Configure Screen 5
Figure	2.2		Disk Option Screen Display 7
Figure	2.3		SMSS Main Menu 8
Figure	2.4		Example Help Display 9
			File Maintenance Menu11
Figure	3.2		Build Student File Menu12
Figure	3.3		Student Record Data Entry Form
Figure	3.4		Record Selection Menu14
Figure	3.5		Environment Record Page 1
Figure	3.6		Environment Record Page 218
Figure	3.7	- -	Environment Record Page 319
Figure	3.8		Environment Record Page 420
Figure	4.1		Mixing Option Menu23
Figure	5.1		Report Mix Selection Menu
Figure	5.2		Reports Selection Menu28
Figure	5.3		Report Output Selection Menu29
Figure	5.4		School Mixing Summary30
Figure	5.5		Squadron Mixing Summary31
Figure	5.6		Seminar Mixing Report32
Figure	5 7		Student Alpha Roster

Chapter One

SMSS Overview

1.1 What is SMSS?

The Student Mix Software System (SMSS) is a set of computer programs used to distribute (or mix) Air Command and Staff College (ACSC) students into ten to thirteen-person seminars to which they will be assigned for parts of the school year. The school philosophy is to distribute students evenly among seminars based on characteristics and skills of each student so that each seminar has a uniformly homogeneous "mix" of students. Students are generally reassigned three times each academic year. The following features of SMSS aid the ACSC staff in assigning students:

- Student data base.
- Menu driven program that "walks" the user through the mixing process.
- Predefined reports

SMSS is designed to run on the Zenith 158 (Z158) computer system, which is commonly used at ACSC. Additionally, it will run on any IBM-compatible personal computer with a configuration similar to the ACSC standard Z158.

1.2 SMSS Structure.

There are two main software elements to SMSS: (1) the user interface and (2) the mixing program. The user interface runs under the SMART integrated software package which is a commercial software system owned by ACSC. SMART contains a word processor, spreadsheet, data base manager, and a telecommunications package. SMSS uses the data manager to maintain its student data base, detailed in Appendix 1. Also, there is programming language within SMART, called the SMART Project Processing feature. The SMSS user interface is written in this language and runs as a SMART project file. Appendix 2 is a source listing of all the SMSS project files. See the SMART user's manuals located in the ACSC Computer Room (room 236) for more information on the SMART data manager and project processor. However, because SMSS guides the user through a menu driven process, it should not be necessary for him/her to be an expert on the SMART data manager.

SMART does not provide the detailed programming capability needed to do student mixing, so the SMSS mixing program is written in the

GW-BASIC programming language. A complete source listing of the mixer is at appendix 3. Again, a knowledge of BASIC is not needed to run SMSS.

1.3 Using This Manual.

This user's manual is organized in the same sequence as the steps involved in the student mixing process. Chapter 2 describes how to load SMSS, how to configure it for your computer, and how to get it started. Next, Chapter 3 shows you how to build and maintain the SMSS data base. Chapter 4 deals with student mixing, and Chapter 5 discusses the reports that show the results of mixing. Finally, Chapter 6 lists the sequence of steps that the ACSC "mixmaster" (the staff officer responsible for student mixing) should go through, using SMSS. Therefore, the first-time user should start at the beginning and march through sequentially as the manual will describe the mixing process as well as how to use SMSS in its support.

There are several examples throughout the manual that show sequences of commands to type into the computer. Actual keyboard inputs will be shown **boldfaced** and **underlined**.

Chapter Two

Installing and Starting SMSS

This chapter gives step by step instructions for installing SMSS on your computer and shows how to get the system started. If SMSS is already installed, skip to paragraph 2.4 for running instructions.

2.1 The SMSS Release Disks.

SMSS comes to you on three, 5 1/4 inch floppy diskettes. Disk i (SMSSPROG) contains the SMSS source and object programs, and all the auxiliary files needed to run and maintain SMSS. Because the whole system will not fit on one diskette, the large student data base is on disk 2 (SMSSSTUS). Together, disk i and disk 2 contain all of SMSS. A third disk (SMSSRUN) is similar to disk i but contains only the object, or run-time versions of the mixer and user interface programs. Disk 3 is useful if space is limited and you don't want to load up the program source code or if you want to release the system to someone else and don't wish to make the source code available. Make a backup copy of all three diskettes using the MS-DOS, "DISKCOPY" command.

2.2 Runtime Disk Configurations.

Some actions you will take to prepare your computer for SMSS depend on how you plan to run the system. SMSS can be run from either of three disk configurations using (1) floppy disk, (2) hard disk, or (3) a combination of floppy disk and virtual (in-memory) disk, sometimes called ramdisk. Each configuration has certain benefits and constraints in terms of speed and transportability as follows:

FLOPPY DISK ONLY -- If you don't have room on your hard disk to permanently install SMSS, or you want to be able to transport the system between computers, this is the way to go. You must have a computer with two floppy disk drives -- drive A will be used for the SMSSPROG or SMSSRUN disk and drive B will be used for the SMSSSTUS disk. This is the slowest-running option.

HARD DISK -- If you've got a hard disk with at least 750k bytes available, this is the fastest and preferable way to run SMSS. Transportation between computers can be tedious.

FLOPPY AND VIRTUAL DISK -- Virtual disk (VDISK) is an MS-DOS feature that allows you to set aside an area of memory that is treated as if it were a disk device. In this option, SMSS programs run from floppy drive A, but the student data base is copied into VDISK at the beginning of your session and copied back to floppy disk at the end. This method is a compromise between the other two options both in terms of speed and transportability.

If you're not constrained to a particular mode of operation, or haven't decided how you will configure SMSS, go ahead with all the following setup steps to allow all modes of operation.

2.3 Setup Steps

Load the SMSSPROG disk into drive A (the upper floppy disk drive) and SMSSSTUS into drive B (the lower one). Type cd a: to switch to drive A. Perform any of the following steps that are applicable to your configuration.

SETUP HARD DISK -- If you will run SMSS from hard disk, you must create a directory and copy all of SMSS to it. There is a routine on the SMSSPROG disk to do this. Type <u>hardset</u> to run this routine. HARDSET creates a subdirectory called SMSS and copies the SMSSPROG and SMSSSTUS disks to it.

SETUP SYSTEM PATH COMMAND -- SMSS is designed so that it can run from any subdirectory or disk. Therefore, SMART must be accessible from wherever SMSS is working. Type in the system command, path. The response will be a list of subdirectories which MS-DOS searches to find program names entered as commands. The directory, \smart, must be among this list. If it is not, change the system autoexec.bat file so that it includes \smart in its path command. See your MS-DOS manual for details on the path command and the autoexec.bat file.

SETUP VIRTUAL DISK -- If you are going to run SMSS with the virtual disk option described above, you must define an area of main memory to set aside for virtual disk. This is done in the system config.sys file. See the MS-DOS manual for a detailed discussion of virtual disk and the config.sys file. There is a routine on the SMSSPROG disk to create a proper config.sys. Type vdiskset to run this routine. To activate the newly defined virtual disk after vdiskset runs, you must re-boot the system by striking the "Ctrl", "Alt", & "Del" keys simultaneously (remove the floppy disks from their drives first). As long as this config.sys file is active, 180Kb of main memory will always be set aside for virtual disk. SMSS will run on the standard ACSC Z158 computer with this memory reserved, but some other very large applications may not.

SETUP CONFIG.SYS -- Whether or not you use virtual disk, your config.sys file must contain a "FILES=20" command and a "BUFFERS=20" command. Vdiskset inserts these commands for you. But, if you do not run vdiskset because you don't want to configure virtual disk, you must manually edit config.sys to insert both these commands.

```
Configuration
     Parity: Even Odd None
     Stop bits: 1 2
 Plotter pen speed (1-10): 10
  ----- Graphics Display Screens -
 1 IBM Color Display Adapter
                                 6 Apricot-xi
 2 AT&T 6300
                               102 IBM EGA - RGB
 3 IBM 3270 PC
                               103 IBM EGA - enhanced/monochrome
 4 Hercules
                               110 Tandy 2000
 5 STB Graphics Plus II(color) 201 IBM Monochrome
 Graphics display screen number: 1
 Paging file path: c:\smartdat
 Application data paths
     Spreadsheet/Graphics: c:\smartdat
     Word Processor: c:\smartword
 Data Manager:
F1 Help
          F2 Edit text
                         F3 Blank text
                                          F10 Finished
configure
CONFIGURE - change configuration settings
```

Figure 2.1 SMART Configure Screen

SETUP SMART DATA PATH -- SMSS is designed to operate from whichever directory it is called from. For example, if you are running from floppy disk, you would first enter cd a: to make drive A the active directory before calling SMSS. Similarly, if you wanted to run from hard disk, you would first enter cd \smss to activate the SMSS subdirectory. But, on most ACSC Z158 computers, SMART is set up to look to the floppy drive A only for database data. Therefore, you must first use the SMART "configure" command to set up SMART

correctly. Call SMART and blank out the Data Manager application data path by keying the following commands:

smart (Enter) Calls SMART main menu Chooses command line 3 Selects the "Configure" command Ç Repeat the down arrow until you ŧ. see a screen display like fig 2.1 (Space) (Enter) Hit the space bar to blank out the "Data Manager" field F10 F10 function key to exit "Configure" F10 F10 function key to exit main menu Select "Quit" command to exit SMART

Blanking the Data Manager application data path tells SMART to get data base data from whichever subdirectory is current when SMART is called. See the SMART system manual for details of the "configure" command.

2.4 Running SMSS.

To run SMSS, you must be "in" the directory where the SMSS programs reside. In other words, if you previously loaded the system to a hard disk subdirectory called SMSS, you must first use the MS-DOS "chdir", or "cd" (for change directory) command to make SMSS the current directory. Once there, simply type the command, smss. Here's an example:

If you're running SMSS from the floppy disk, first load the SMSSPROG diskette in drive A, then type:

a: (Enter) Changes to the floppy drive smss (Enter) Calls SMSS

2.4.1 Disk Option Screen

In either case, control will pass to the SMSS project file in SMART and the screen shown in figure 2.2 will appear. This screen is typical of the menu screens that appear throughout SMSS. In this one, you are asked to tell SMSS what disk option you are using: floppy, hard, or floppy with virtual disk. To select an option, move the arrow to your choice with the "q" (up arrow) or "¢" (down arrow) keys, then press the "Enter" key. You can also press the "Esc" key to choose the default (hard disk) option and continue to the next screen. To get helpful information about this menu displayed on the screen, you can press the (upper or lower case) "H" key for help. Help screens are described in detail in paragraph 2.4.3 below.

menu level O

WELCOME TO SMSS

CHOOSE DISK OPTION

- => 1. FLOPPY DISK ONLY a:(programs),b:(student file)
 - 2. HARD DISK c: programs & student file
 - 3. FLOPPY AND VDISK a:(programs),d:(student file)

*** DEFAULT (Esc) IS OPTION 2 ***

Enter h for HELP, Esc to exit to next menu

Figure 2.2 Disk Option Screen Display

2.4.2 SMSS Main Menu.

After indicating your disk configuration, You'll see some student data records flash on the screen as SMSS loads the student and other files. Note that in the lower right hand corner of the display you see messages such as, "LOADING STUDENT FILE". These are simply information messages to let you know that SMSS is performing some action and is not waiting for keyboard input. The next menu to appear is the main menu as shown in figure 2.3. Its three options: "File Maintenance", "Perform Mixing", and "Produce Reports" are major subsections of SMSS. Each is described in subsequent chapters. Every menu in SMSS looks essentially like this one and is subject to the following general menu option selection rules.

2.4.3 Menu Selection Rules.

When selecting options from an SMSS menu, the only valid keyboard inputs are the up-arrow (†), down-arrow (†), "Enter", "H" (upper or lower case), and "Esc" keys. All other keys will cause an audible warning beep. Here are the meanings of the valid keys:

UP OR DOWN ARROW -- Use these keys to move the display pointer up or down to the option you want to select. The pointer will wrap around if moved below the last option or above the first option.

ENTER -- Striking the "Enter" key selects whichever option the display pointer is pointing to.

ESC -- This key causes SMSS to "pop back" to the last menu displayed. "Escaping" from the main menu (figure 2.3) is the way to exit from SMSS. Exit is to the SMART data manager. From there, an "F10" and "Q" (for "quit") will exit back to MS-DOS. The one exception to the "pop back" rule is the disk option menu (figure 2.2). Escaping from that menu pops forward to the main menu.

H -- The "H" (or "h") key calls for a help screen. Each menu in SMSS has an associated help screen that explains the option selections. The next paragraph describes how to manipulate the help screens.




Figure 2.3 SMSS Main Menu

2.4.4 Help Screens.

SMSS is somewhat self-documenting since you can call up information explaining each menu option by pressing the "H" key. Figure 2.4 is an example of a help display for the main menu. If there is more than one page to the help display, move back and forth between pages with the "Pg Dn" and "Pg Up" keys. You can print the screen by holding down the "Shift" key and pressing "Prt Sc". Return to the menu with the "Esc" key. These instructions are printed at the bottom of the boxed area on each help display. Help displays are implemented in SMSS as screens of a dummy data

base called HELP. When you press the "H" key, SMSS performs a SMART "update" command on this data base. Since there is no data in HELP, the update, and hence, the SMART function key operations (F2,F3,...,F10) displayed at the bottom (below the double line) of screen are meaningless. Use only the commands defined above.

```
= Window 1 =
                         CHOOSE DISK OPTION HELP SCREEN
                                                             page 1 of 2 HELPO
 GENERAL: SMSS can be run from either of 3 different disk configurations using
floppy disk, hard disk and/or virtual (in-memory) disk, sometimes called ram-
disk. Each configuration has certain benefits and constrains in speed and
 transportability. The options are described as follows:
   1. FLOPPY DISK ONLY: The SMSS system is too big to fit on one 360kB floppy
             In this option, the SMSSPROG diskette should be loaded in drive
  a: (the upper floppy drive) and the SMSSSTUS diskette, containing the
   student data base should be in drive b: (the lower floppy drive).
   have called SMSS from drive a:. This is the slowest option but it is very
   transportable from one machine to another.
   HARD DISK: This is the fastest and preferable way to run SMSS.
                                                                     You must
   have previously created a directory on drive c: (hard or Bernouli) and
   copied the SMSSPROG & SMSSSTUS diskettes to it. Also, you must have been
Pg Dn for next page; Esc to return; Shift/Prt Sc to print
 Insert ON
            F3 - Prev fld
                            F5 - Prev rec
                                             F7 - Fld delete
                                                               F9
                                                                   - Repeat fld
                            F6 - Next rec
                                                               F10 - Finished
F2 - Date
            F4 - Next fld
                                             F8 - Fld reform
File: help
            Window: 1
                                                Page: 1 Rec: EOF (1)
```

Figure 2.4 Example Help Display

ACON PROCESSOR - SECURIAR REPORTED AND SOCIOSA DISTRIBUTE AL SECURIOR DE COSSOCIA DE COSSOCIA DISTRIBUTE DE COSSOCIA DE COSSOC

Chapter Three

File Maintenance

This chapter describes the functions that are performed in the file maintenance section of SMSS. File maintenance functions are those used to build and maintain the student and environment files. When you select FILE MAINTENANCE from the main menu, figure 3.1 will appear on the screen. The eight functions shown are described in the subsequent paragraphs. Exit the file maintenance section by pressing the "Esc" key at the file maintenance menu. Control will pass back to the main menu.



menu level 11

OPTIONS

- ---->
- 1. BUILD STUDENT RECORDS FROM ANOTHER DISK
- 2. ADD STUDENT RECORDS MANUALLY
- 3. EDIT EXISTING STUDENT RECORD
- 4. DELETE STUDENT RECORD
- 5. DESIGNATE STUDENT NUMBERS
- 6. EDIT ENVIRONMENT RECORD (MIXING RULES)
- 7. DELETE IO'S (FOR MIX 3)
- 8. POST MIXER TENTATIVE ASSIGNMENTS

Enter h for HELP, Esc to exit to last menu

Figure 3.1 File Maintenance Menu

3.1 Build Student Records from Another Disk

This operation builds much of the student file and is generally the first SMSS function to be performed prior to the start of each academic year. The personnel office at Headquarters, Air

University (AU) can provide data on each active duty Air Force student projected into ACSC. Contact AU/DPXM at extension 6272 to request this data. They have direct access into the central Air Force personnel computer at the Air Force Military Personnel Center, but you should give them a week or two lead time. SMSS expects this data on a single file on a floppy diskette in the ASCII data format discussed in the SMART Data Base Manager Reference Guide, page Read-1. Note that only fields 1 through 27 (see Appendix One) of the student file are read in from floppy disk. All other fields are computed by the system or entered manually.

SMSS - BUILD STUDENT FILE

menu level 111

This option allows you to build the student file by reading student records from an ASCII floppy disk file See the SMSS users manual for the correct format of this file. You can build the student file from scratch or you can add new records to the end of the existing file.

****WARNING****

If you build from scratch, any records in the current student file will be lost.

OPTIONS

- => 1. BUILD STUDENT FILE FROM SCRATCH
 - 2. ADD RECORDS TO STUDENT FILE

Enter h for HELP, Esc to exit to last menu

Figure 3.2 Build Student File Menu

After you select the BUILD STUDENT RECORDS option from the SMSS file maintenance menu, you will see figure 3.2. This menu gives you the option of either totally starting from scratch or adding new student records from the floppy disk to the student file. If you choose the first (start from scratch) option, all existing records will be erased. Note -- you can use the "copystu" command described in paragraph 6.1 to save the previous data base if necessary. Next, SMSS will ask you for the name of the file on the floppy diskette. If you don't know, back out of SMSS and use the MS-DOS "dir a:" command to display the diskette directory. After one more warning message to make sure you understand what you're doing, SMSS will ask you to load your diskette into drive

A, read the diskette and build new records into the student file. If you are running SMSS from floppy disk, there will be some disk switching ordered -- just follow the directions on the screen. This operation takes several minutes and is completed when the file maintenance menu reappears.

3.2 Add Student Records Manually

Unfortunately, the whole student file cannot be built with the option of paragraph 3.1. AU/DPXM can only give us automated data on active duty Air Force students. Information on international officers, other service officers, civilians, guardsmen, and reservists must be entered manually from the keyboard. Choose this option to type in one or more student records. A data entry form like the one in figure 3.3 will appear and the cursor will move to the first field on the form. You simply type the correct information into each field. See Appendix One for the meaning and data ranges of each field. You cannot enter anything into the last column, "COMPUTED FIELDS", since these values are computed by the system based on other information in the record.

PERSONAL DATA		ACSC	STUDENT RECORI	D = SCHOOL	SKILLS	COMPUTEI FIELDS
NAME			BACKGROUND	DATA		
RANK					= PPBS _	10
SEX			ED.LVL	SQUADRON	ACLOG _	USAF
RACE			DAFSC	MIX1	_ SPACE	NOMAST
MAR.STAT			PAFSC	MIX2 _	_ TRD1 _	SORG
SSAN			2AFSC	_	_ TøD2	PILOT
DOB			3AFSC	MIXX _	_ TBD3 _	NAV
			PME1		_ TBD4	SINGLE
MILITARY DATA	FLYING DATA		PME2	SOS	_ TBD5	USAFA
	····	==	PME3	ARI	_	ARMY
COMP			MAJCOM	cc	_	OTHER
	AERO		ORG.LVL	SRO	_	MIN
	RTFD	_		SL	_	FEMALE
	MOF _			ASL	_	CAPT
AC1.HRS.DT _				SLX	_	NONLIN
AC2.HRS.DT _				ASLX		STRAT
AC3.HRS.DT _		_		····	COULDBSL _	TACSK
Insert ON F3	- Prev fld	F5 -	Not used F7	- Fld delet	e F9 - F	Repeat flo
F2 Date F4	- Next fld	F6 -	Next rec F8	- Fld refor	m F10 - F	inished

Figure 3.3 Student Record Data Entry Form

SMSS uses the SMART "enter" command to implement this option. See the SMART Base Manager Reference Guide, page Enter-3 for the meaning of the many helpful movement and editing keys, some of which are listed at the bottom of the screen. When you are done entering records, press the "F10" function key to return to the file maintenance menu.

3.3 Edit Existing Student Record

Select this option to change any of the fields in an existing student record. You will see the menu shown in figure 3.4, which will ask you to identify a particular student record to edit. You can select a record by name, social security number (SSAN), or student number (we'll assign student numbers later). Choose one and a box will appear in which to enter the search value. need not enter a complete name, but the SSAN or student number must be complete. SMSS will find the record and display it in a form like that of figure 3.3. If the record is not found, you'll see an error message and control will return to the file maintenance menu. If found, the SMART "update" command is used to edit the record. Use the editing keys described in the SMART Data Base Manager Reference Guide, page Enter-3. When finished, press the "F10" function key to save the changes and return to the file maintenance menu. Note that you cannot edit the NAME, SS'N, or STU.NO fields since these are data base key fields. If you must change these fields, use SMART to load the STUDENTS file with screen, STUDENT2; then "update" to edit fields and update keys.

> STUDENT RECORD SELECTION

menu level 113

Choose which record to process by one of the following fields.

NOTE: SSAN & STUDENT NUMBER options are much faster.

OPTIONS

- => 1. NAME (or partial name)
 - 2. SSAN
 - 3. STUDENT NUMBER

Enter h for HELP, Esc to exit to last menu

Figure 3.4 Record Selection Menu

3.4 Delete Student Record

Use this option to delete a record if a student disenrolls or you enter an erroneous record. You'll see the menu shown in figure 3.4 which will ask you to identify a particular student to delete. Recommend you use SSAN or student number to be precise. If that record is not found you'll see an error message and control will pass to the file maintenance menu. If found, the record is deleted using the SMART "delete" command. Note that deleted records are not actually physically dropped from the student file. You can recover a deleted record by manually using the SMART "delete" command.

3.5 Designate Student Numbers

ACSC uses student numbers internally to identify students. Once you've created the entire student file, use this option to assign student numbers. The file is ordered alphabetically and sequential multiples of five (0005, 0010, 0015,...) are generated into the STU.NO field. If you add students after performing this operation, run it again to regenerate numbers. Once numbers are issued to students, however, you should not run this again, since everyone's assigned number will change. Note that you cannot do any mixing before student numbers are assigned because the mixing program identifies students by student number. You'll get a warning message to make sure you really want to perform this operation; then, when completed, the file maintenance menu will appear.

3.6 Edit Environment Record

SMSS maintains an environment record (in the ENVIRON file) used to pass control information to the mixing program. With this record you tell the mixer:

- Which mix (1,2 or 3) to process
- Relative priorities of mixing rules
- Organizational structure of the school

You must have edited the environment record before mixing. There are four pages to the environment record data entry form shown in figures 3.5, 3.6, 3.7, and 3.8. When you choose this option, SMSS uses the SMART "update" command and displays page one on the screen. Enter or change the following fields depending on the mix environment you desire:

MIX NUMBER -- The mixer uses different algorithms depending on which of the three annual mixes it is working on. Enter a value of 1, 2, or 3 here.

MAX NUMBER OF PREVIOUS SEMINAR MATES -- The mixer avoids assigning together students who have previously been assigned together in

past seminars. Enter here, the number of previously-assigned-together students you want to allow in each seminar. The number must be from 2 through 9. If the mixer is force to violate this rule, it will issue a warning message

SYSTEM MIXING RULES AND PRIORITIES -- Students are mixed according to a set of adjustable mixing rules. The rules shown on page 1 of the environment record (figure 3.5) are system-wide rules as follows:

ARI -- Airpower Research Institute students should not change seminars. Enter 9 to honor this rule. Any other value (from 0 to 8) will be treated as a student mixing rule (see below), and ARI students will be mixed like any other student attribute.

SOS -- Squadron Officer School instructors should not change seminars. (9 to honor, any other to mix SOS instructors)

10 -- International Officers should not change seminars. (9
to honor, any other to mix IO's)

BUDDIES -- How important is it (which priority) that the number of students in the MAX-NUMBER-OF-PREVIOUS-MATES field not be assigned together? This feature is currently not implemented, and is treated as a 9 (highest) priority regardless of what you enter here.

SEMCHANGE -- All other students (not ARI, SOS, IO) must change seminars. (9 to honor, any other to ignore). This feature is not currently implemented. All other students will always change seminars.

STUDENT MIXING RULES AND PRIORITIES -- The mixing program's primary task is to distribute students equitably among seminars according to attributes and skills each student possesses. are 23 such attributes shown in figures 3.6 and 3.7. priorities you assign to each attribute define how the mixer will operate. It first "spreads-out" all the students with priority nine attributes, then the eights, and so on down through priority ones. Thus it is more likely that students with high priority attributes will be distributed evenly among seminars. with low priority attributes are more likely to "bunch up" together. For example, if the school determines that it is very important that pilots are spread out among seminars, give the PILOT attribute rule a relatively high priority number. Similarly, if it is less important that students with PPBS experience are uniformly distributed, give the PPBS attribute a relatively low priority number. The actual values from 9 down to 1 are unimportant -- only the relative values among the priorities are important. A priority of O (zero) means, "do not consider this

attribute at all in mixing". By experimenting with different priority relationships, you can adjust the mixer output.

The five "TBD" (To Be Determined) fields in figure 3.7 allow the system to respond to changing school mixing requirements. For example, assume that in the future, the school determines that it is important to spread out students with joint organization experience. After you identify these students, you can use the EDIT STUDENT RECORD option to mark these records with a "Y" in the TBD1 field. Then, edit the environment record to assign that attribute a mixing priority and enter "Joint Experience" in the TBD1 description field to indicate what TBD1 is being used to represent. As long as the TBD fields are not being used, their priorities should be zero.




Figure 3.5 Environment Record Page 1

SEMINAR STRUCTURE -- The fourth page (figure 3.8) of the environment record is used to define the organization of the

school. Enter here the first (lowest numbered) and last (highest numbered) seminar numbers in each squadron. If any seminars are missing from that range, (as they might in mix 3 after the international officers depart), you can designate up to three missing seminar numbers.

Finally, after the environment record is set like you want it. press the "F10" function key to save the changes and return to the file maintenance menu.

		MIX ENVIRONMENT RECORD Page 2 of 4
RULE	PRIORITY	DESCRIPTION
==		
USAF	0_	Line AD Air Force
NOMAST	2_	No advanced Degree
SORG	4_	HQ (>=Majcom) Experience_
PILOT	6_	Any Pilot
NAV	6_	Any Navigator
SINGLE	5_	Anyhow Unaccompanied
USAFA	5_ 2_ 9_ 8_ 5_	USAFA (academy) grad
ARMY	9_	Army
OTHERCOMP	8	Res, ANG, Civ, USMC, or Navy
MINORITY	5	Black or other
FEMALE	-	Female
CAPTAIN		Current captains
NONLINE	7	Medical, legal, chaplain
(More on	next pageHit	Pg Dn)
Insert ON	F3 - Prev fld	F5 - Prev rec F7 - Fld delete F9 - Repeat fld
F2 - Date	F4 - Next fld	F6 - Next rec F8 - Fld reform F10 - Finished
ile: enviro	on Window: 1	Page: 2 Rec: EOF (1) Act:

Figure 3.6 Environment Record Page 2

```
= Window 1 ==
                        MIX ENVIRONMENT RECORD Page 3 of 4
RULE
           PRIORITY
                         DESCRIPTION
                         Bomber or missile exp___
STRATOPS
TACOPS
              9_
                         Fighter pilot or WSO_____
             9_
PPBS
                         PPBS experience_____
ACQLOG
              9_
                         Acq/Log experience___
                         Space experience____
SPACE
            6
*************Following Can Be Defined Later if needed********
             0__
TBD1
                         unassigned____
             0_
TBD2
                         unassigned____
TBD3
              0
                         unassigned
TBD4
              0_
                         unassigned_____
TBD5
                         unassigned
Next Page is for designating school structure...hit Pg Dn
Insert ON
           F3 - Prev fld
                         F5 - Prev rec
                                       F7 - Fld delete
                                                       F9 - Repeat fld
F2 - Date
         F4 - Next fld F6 - Next rec
                                       F8 - Fld reform F10 - Finished
File: environ Window: 1
                                          Page: 3 Rec: EOF (1) Act: Y
```

Figure 3.7 Environment Record Page 3




Figure 3.8 Environment Record Page 4

3.7 Delete International Officers

CONTRACTOR OF THE PROPERTY OF

International officers (IO's) graduate before the end of the academic year. Choose this option to delete IO records after they graduate. After a warning message to double check that you really want to do this, the operation is completed when you see the file maintenance menu reappear.

3.8 Post Mixer Tentative Assignments

The mixing program only makes tentative seminar assignments. Thus, after a mix, you can examine the mixing results and rerun it or make manual adjustments, if necessary. MIXX is the tentative seminar assignment field in the student file. When the mix is acceptable, use this option to move MIXX values into MIX1, MIX2, or MIX3, thereby making the mix assignment permanent. Also, the mixer sets fields SLX and ASLX to a value of "Y" if the student would be a seminar leader or assistant seminar leader, respectively, in the new mix. This option updates fields SL and

ASL based on SLX and ASLX, as well. After selecting the option, you're asked to enter a value of 1, 2, or 3 to indicate which mix to post.

Chapter Four

Perform Mixing

When the student file has been built and the environment record reflects the proper mixing arguments, you are ready to mix the students into their seminar assignments. Mixing is accomplished by selecting option 2, the PERFORM MIXING option, from the main menu of figure 2.3.

4.1 The SMART/Mixer Interface

As mentioned in Chapter One, SMART is not capable of performing the complex operations of student mixing. Therefore, SMSS contains a mixing program (the mixer) written in GW-BASIC which operates directly under MS-DOS. The mixer cannot read the student file or environment record directly since these are in a special SMART data base manager format. Therefore, we use the SMART "write" command to create two files, STU.ASC and ENV.ASC, which contain selected student and environment information in a form that is readable by the mixer. When you select the PERFORM MIXING option,

SMSS MIXING OPTION

menu level 12

If there have been no changes to the student file since the last mixing run, you can skip the ASCII file update. If there have been changes, or you don't know, be safe by running the ASCII file update.

OPTIONS

- => 1. SKIP ASCII FILE UPDATE
 - 2. RUN ASCII FILE UPDATE

Enter h for HELP, Esc to exit to last menu

Figure 4.1 Mixing Option Menu

SMSS creates these files and passes control to the mixer, outside of SMART. The mixer then produces a results file called STUOUT.ASC and passes control again to SMART, which updates the student file with the mix results in STUOUT.ASC.

4.2 SMSS Mixing Menu

Select the PERFORM MIXING option from the main menu and you will see the two-option mixing menu shown in figure 4.1. SMSS asks you here if you want to skip the creation of the STU.ASC file. If you have mixed before and have since made no changes to the student file, you can save a little time by not writing STU.ASC since it will not have changed since the last time you mixed. In this case, select option 1, SKIP ASCII FILE UPDATE. Otherwise, select option 2, RUN ASCII FILE UPDATE.

4.3 Mixing Sequence of Operations

From this point on, mixing is essentially a "hands-off" operation that requires no user input. You can track the following operations by watching the explanatory messages at the bottom of the display screen.

- 1. SMART sorts the student file by rank and date of rank.
- 2. SMART writes ENV. ASC, the environment record interface file for the mixer.
- 3. If you requested it, SMART writes the student interface file, STU.ASC.
- 4. SMART relinquishes control and the mixer is called.
- 5. The mixer asks whether or not to turn off trace output. Trace output "on" will cause a trace of mixing events to be displayed on the screen. Mixing performed.
- 6. If there is an abort exit from the mixer, the whole process stops in MS-DOS.
- 7. If successful exit, control passes to SMART. SMART reads the output interface file (STUOUT.ASC) into a data manager file called NEWMIX.
- 8. Student file fields, MIXX, SLX, and ASLX are updated from NEWMIX using the SMART "transaction" command.
- 9. Control passes to the main menu.

This whole process will take several minutes, so be patient. When complete, the MIXX field of each student record will contain the tentative seminar number of assignment. SLX will contain "Y" if

the student is designated a Seminar Leader in the new mix. ASLX will be "Y" if he/she is designated as Assistant Seminar Leader. These tentative assignments are not made permanent until you perform the POST MIXER TENTATIVE ASSIGNMENTS option of paragraph 3.8.

Chapter 5

Produce Reports

SMSS produces two types of reports:

- (1) Mixing summary reports that show the results of a mix.
- (2) Alphabetically sorted student rosters.

The mixing summary reports are usually produced after y u have mixed the students. These summaries show whether you have produced a "balanced" distribution. If not, you can make manual changes to the tentative seminar assignments, or you can re-mix after adjusting mix rule priorities as in paragraph 3.6. The alpha rosters can be run at any time to support school operations.




Figure 5.1 Report Mix Selection Menu

5.1 Report Selection Menus

CONTRACT BESSERVE OFFICE CONTRACT OF STANDARD CONTRACT OF

When you select the PRODUCE REPORTS option from the main menu, figure 5.1 will appear. Here, you simply tell SMSS which mix you will be reporting on. Remember that MIXX is the tentative seminar

assignment field. Generally, you will choose MIXX when you want the results of the last mixing run. After choosing a mix, you will see the reports selection menu of figure 5.2. Choose which report you want from this menu. The rest of the paragraphs in this chapter deal with each of these report options.

menu level 131

SMSS REPORTS OPTION

OPTIONS

- -> 1. SCHOOL MIXING SUMMARY
 - 2. SQUADRON MIXING SUMMARY
 - 3. SEMINAR MIXING REPORT
 - 4. COMPLETE MIXING REPORT (all the above)
 - 5. SCHOOL ALPHA ROSTER
 - 6. SQUADRON ALPHA ROSTER
 - 7. SEMINAR ALPHA ROSTER

Enter h for HELP, Esc to exit to last menu

Figure 5.2 Reports Selection Menu

The mixing summaries (options 1 and 2) each produce one page of output and are always directed to the printer. For all other reports, you will see the Report Output Selection Menu shown in figure 5.3. Choose whether you want the output sent to the printer, a disk file, or the display screen. If you choose "DISK", you will be prompted to enter a file name. Enter a single file name or complete path name, but do not include a file extension since SMART appends the extension, ".PRT", to the name you enter. This option is implemented using the SMART "report Print" command. See the SMART Data Base Manager Reference Guide, page Report-25, for details. With the ""DISK" option, you can later print the file you produce with the MS-DOS "print" command. Before you print, however, enter compress to put the printer in compressed text mode. COMPRES.EXE is a program supplied on the SMSSPROG disk.

menu level 1311

REPORT OUTPUT SELECTION

Choose Where you want report output sent

OPTIONS

- => 1. PRINTER
 - 2. DISK
 - 3. SCREEN

Default (Esc) is PRINTER

Enter h for HELP, Esc to exit to next menu

Figure 5.3 Report Output Selection Menu

5.2 School Mixing Summary

This is a one-page report (figure 5.4) that totals the 23 student attributes by squadron. Each line represents a student attribute defined in the environment record. Use this report when developing mix one to determine if each squadron has a reasonable distribution of students. This report only goes to the printer.

5.3 Squadron Mixing Summary

This report (figure 5.5) is similar to the School Mixing Summary, but it displays a column for each seminar in a particular squadron. After selection, SMSS will ask for a squadron number -- Enter $\underline{1}$, $\underline{2}$, $\underline{3}$, or $\underline{4}$. Use this report to evaluate the distribution of students into seminars across a squadron. This report only goes to the printer.

5.4 Seminar Mixing Report

The Seminar Mixing Report for a single seminar is shown in figure 5.6. There is one line for each student in the seminar and each column represents one of the student mixing attributes, printed at the top of each page. A value of "1" in any column indicates that the student possesses that attribute. Students are listed in seminar leader selection order. That is, the first student who has not previously been a seminar leader (indicated by a "Y" in the SL field) would be the seminar leader in this mix. When you choose this option. SMSS asks you for the seminar(s) to report on. Your answer can be one of three options. Enter,

ALL -- to list all seminars in the school.

 \underline{SQn} (where n= $\underline{1},\ \underline{2},\ \underline{3},$ or $\underline{4}) --$ to list all the seminars in a particular squadron.

Seminar number (e.g., 33) -- to list a single seminar.

	SC	CHOOL		STAT STATE	. –	ICS	06 Feb 88
	ATTRIBUTE	SQ1	SQ2	s Q 3	SQ4	TOTAL	
1.	Line AD Air Force	102	101	104	103	410	
2.	No advanced Degree	49	46	37	41	173	
З.	HQ (>=Majcom) Experience	80	78	83	76	317	
4.	Any Pilot	48	52	51	50	201	
5.	Any Navigator	17	17	18	14	66	
6.	Anyhow Unaccompanied	29	23	34	18	104	
7.	USAFA (academy) grad	25	18	22	16	81	
8.	Army	11	11	11	11	44	
9.	Res, ANG, Civ, USMC, or Navy	11	11	9	10	41	
10.	Black or other	5	5	5	6	21	
11.	Fema!e	7	7	7	8	29	
12.	Current captains	6	7	7	3	23	
13.	Medical, legal, chaplain	7	5	5	5	22	
14.	Bomber or missile exp	5	6	4	7	22	
15.	Fighter pilot or WSO	5	8	9	8	30	
16.	PPBS experience	26	34	28	22	110	
17.	Acq Log experience	31	32	15	34	112	
18.	Space experience	0	0	0	0	0	
19.	unassigned	0	0	0	0	0	
20.	unassigned	0	0	0	0	0	
21.	unassigned	0	0	0	0	0	
22.	unassigned	0	0	0	0	0	
	unassigned	0	0	0	0	0	

Figure 5.4 School Mixing Summary

	SQUADRON 3 MIX STATISTICS												
	MIX 1 06-F										06-Feb-88		
	ATTRIBUTE	23	24	25	26	27	28	29	30	31	32	33	TOTAL
1.	Line AD Air Force	10	9	10	8	11	10	10	9	9	9	9	104
2.	No advanced Degree	4	3	3	3	4	2	3	6	4	2	3	37
3.	HQ (>=Majcom) Experience	8	8	9	9	10	7	6	7	7		6	83
4.	Any Pilot	4		4		5	5	4	4	3		5	51
5.	Any Navigator	2	2	2		1	1	2	2	2	1	2	
6.	Anyhow Unaccompanied	2	2			4	2		0	2	3	5	34
7.	USAFA (academy) grad	2	3	3	1	5	2	1	1	0	3	1	22
8.	Army	1	1		1	1	1	1	1	1	1	1	11
9.	Res, ANG, Civ, USMC, or Navy	1	1		2	0	0	1	1	1		1	9
10.	Black or other	0	0	1	0	1	1	0	0	0	1	1	5
11.	Female	1	1	0	1	1	1	1	0	1	0	0	7
	Current captains	0	1	2	1	0	0	0	1	0	1	1	7
13.	Medical, legal, chaplain	0	0	0	1	1	0	1		1	1	0	5
	Bomber or missile exp	1	1			0	0		0	0	0	1	4
	Fighter pilot or WSO	1	1	1	1	2	0	1	1	1	0	0	9
	PPBS experience	4	3	0		5	3	1	2	5	0	0	28
	Acq/Log experience	2	3	1	2	2	1	1	1	1	1	0	15
	Space experience	0	0	0	0	0	0	0	0	0	0	0	0
	unassigned	0	0	0	0	0	0	0	0	0	0	0	0
	unassigned	0	0	0	0	0	0	0	0	0	0	0	0
	unassigned	0	0	0	0	0	0	0	0	0	0	0	0
	unassigned	0	0	0	0	0	0	0	0	0	0	0	0
23.	unassigned	0	0	0	0	0	0	0	0	0	0	0	0

Figure 5.5 Squadron Mixing Summary

5.5 Complete Mixing Report

This option is an "all-the-above" report. It runs the School Summary, Squadron Summary for all squadrons, and Seminar Mixing Report for all seminars. It is convenient (although time-consuming) to run this after mixing to get a complete mixing picture. Note that if you choose "DISK" output, the two summary reports will be printed while the Seminar Mixing Report will go to disk.

5.6 Alpha Rosters

The final three report options all produce alphabetically sorted resters similar to that shown in figure 5.7. You can create a school, squadron, seminar, or set of seminars roster. Note that these rosters contain students' name and social security number.

so they should be protected according to the privacy act. Social security numbers have been deleted from the example.

NAME 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 M1 M2 M3 NF BOR SL ASL S BOWMAN STEVE 1 1 1 1 1 3 30 33 04 850301 Y 7 6 BALRYMPLE XI 1 1 1 1 1 1 1 2 29 33 04 850501 Y 7 6 DOUGLAS JAME 1 1 1 1 1 1 1 1 1 1 24 33 04 860501 LEWIS OLIS 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
NAMES I 2 I 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 M1 M2 M3 NF BOR SLASL S BOWMAN STEVE I 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1: Captain 3: Epace 3/il	113
######################################		SL ASL
STEWART JAME 1 1 1 1 1 1 1 29 33 04 850501 7 6 PALRYMPLE 1 1 1 1 1 1 29 33 04 850501 7 6 DOUGLAS JAME 1 1 1 1 1 1 24 33 04 860501 3 LEWIS OLIB 1 1 1 1 1 1 24 33 04 860501 3 TUEGLE JAMES 1 1 1 1 1 30 33 04 860501 3 JENSEN FICHA 1 1 3 3 3 3 3 3 3 3	57701 Y	
PALRYMPLE RI 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		i j
DOUGLAS JAME : : : : : : : : : : : : : : : : : : :		1
LEWIS BLIS L 1 1 1 1 1 1 1 1 1 26 33 04 860501 1 1 1 1 1 1 1 1 26 33 04 860501 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		0 (
TUBGLE JAMES 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		. j
TENSEN FICHA 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	_	6 9
PREPER CHAR 1 1 1 1 1 1 23 33 04 869701 00 869		ê ê
VILLIAMS FAU 1 1 1 1 24 33 04 861901 0 'IMS EDDIE R 1 1 1 1 1 32 33 04 870101 0 WHNLAF DAVID 1 1 1 1 1 1 26 33 13 870606 0		i i
'IMS EDDIE R 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		0
HUNLAR DAVID 1 1 1 1 1 1 1 1 26 33 13 870606 1		0 6
	⁷ 0506	
ANGA TEMBOR 1 1 27 27 04 0		
AL-SHEDADIS 1 1 1 37.77 04.6		

Figure 5.6 Seminar Mixing Report

BEMINAR DI ALPHA POSTER

STUDENT NUMBER	NAME	SBAN	RANK	DOR	COMMAND	PAFSC	COMPONENT	AERO RATING	MIXI	MIX2	MIXI
NO.	ASAMS TIMOTER M	\ /	34	951202	NGS	9015	AN6	NO RATING	71	27	
7 17E	ARMED	\ /	05	0			SOMAL	PILOT	31	31	
370	BREAULT SIMEON D	$\setminus \setminus$	⊕4	95:201	ELM	2825	USAF	NO RATING	3:	25	
ુદુવદુ	DOOLEY JON 3	\	74	850801	ATC	0950	USAF	SR NAV	31	24	
1945	BUPDAT MARTIN E		04	350101	HAF	7916	USAF	NO RATING	J1	29	
6810	SUTILLY MARTIN D	V	94	870101	ATC	2295D	USAF	SR NAV	31	26	
1245	HOIDAHL ROBERT I I	Λ)4	860401			USA		31	27	
1785	JANIES GORDON R	Λ	04	870301	PAF	5511	USAF	NO RATING	31	28	
1790	JENSEN RICHARD M	$/ \setminus$	-)4	860301	MPC	4915	USAF	NO RATING	31	33	
2245	ROGERS ELITABETY H	/ \	94	950701	TAC	61716	USAF	NO RATING	31	24	
1.29%	FYSSELL MICHAEL 3	1	94	8 60101	SAC	1435Y	USAF	SR PILOT	71	72	
Z74(WEST GARY C	1	94	8 70301	TAC	K1115H	USAF	PILOT	31	27	

Figure 5.7 Student Alpha Roster

Chapter 6

Mixmaster's Checklist

The preceding chapters described how to use SMSS. This chapter lists the mixing tasks required of the ACSC staff officer responsible for student mixing. Numbers in parentheses are paragraph numbers of the SMSS operation to perform each task.

ACTIONS

- 6.1 After graduation in June -- Save the old student file for historical purposes. In the SMSS directory, enter <u>copystu</u>. This will copy all student information to floppy disk.
- 6.2 Prior to start of new class -- Get the Air Force student disk from AU/DPXM and load it. (3.1)
- 6.3 Obtain hardcopy information on non Air Force students from the ACSC Director of Operations. Manually load these students. Don't forget SOS instructors and ARI fellows. (3.2 and appendix 1)
- **6.4** When all students have been loaded -- Assign student numbers. Note that you must assign student numbers <u>before</u> doing any mixing. (3.5)
- 6.5 The following student attributes/skills must be entered by hand. (3.3)
 - MAR.STAT "U" for married, unaccompanied SOS "Y" for SOS phase II instructors ARI "Y" for Airpower Research Inst. fellows PPBS, ACQLOG, SPACE . "Y" for possesses that skill
- 6.6 Enter "Y" in the CC field of the class commander. (3.3)
- 6.7 Enter "Y" in SRO field of the four squadron senior ranking officers. (3.3)
- 6.8 If there are any new mixing criteria, choose TBD fields to represent them. Identify students with the attribute/skill and update appropriate TBD field with "Y".(3.3)
- **6.9** Edit all the fields in the environment record for mix 1. (3.6)

- **6.10** If you want to pre-assign any student to a particular seminar, update his/her MIX1 field with that seminar number. (3.3)
- **6.11** Perform mixing for mix 1. (4.2)
- 6.12 Run the complete mixing report on MIXX and analyze it for acceptability. (5.5)
- **6.13** If the mix is somehow "uneven", adjust the rule attribute/skill priorities and mix again until it comes out right. (3.6, 4.2)
- **6.14** To make any manual mix adjustments, edit the MIXX field. Note that if you make any manual changes, you must manually compare dates-of-rank and manually make any necessary changes to the SLX and ASLX fields. (3.3)
- 6.15 When the mix is satisfactory -- post tentative mix assignments to MIX1. (3.8)
- 6.16 Run the Alpha Rosters. (5.6)
- 6.17 Make a backup copy of the student file to protect against loss of the working copy. On a hard disk system, run "copystu" (6.1). On a floppy system, copy the SMSSSTUS disk using the MS-DOS "diskcopy" command.
- **6.18** As necessary throughout the school year -- delete any disensolled students (3.4), and make any personnel data changes for promotions, change in marital status, etc. (3.3)
- 6.19 Prior to mix 2 -- do steps 6.8 through 6.16 for mix 2.
- 6.20 Prior to mix 3 -- Delete International Officers (3.7), then do steps 6.8 through 6.16 for mix 3.

APPENDICES	The state of the s	Character structure and the Control State an	tallinearinearinearinearinearinearinearinear
	X.		
	X		
	a		
	₹		
	<i>X</i>		
	A.		
	<i>Ž</i> ,		
	e _s		
	<u> </u>	ADDENDICEC	
	Ø	APPENDICES_	
	화		
	lg'		
	Q •		
	X .		
	X.		
	Ø.		
	98		
	\mathbb{Q}		
	X_i		
	SQ .		
	K.		
	J.s.		
37			
37	र्वी के का है		
37	ki		
37	ñ		
37			
37	<u> </u>		
37	N .		
÷ •	(&		
37	₿		
37			
37	5		
37	§ ·		
37	S		
37	₹		
37			
37	sr. •		
37			
37	&		
37	<u>%</u>		
37	X		
37	8		
37			
37	%		
	35		
	8 2		
	8 6	37	
	18 2		
	Mac ▲		
	To		
	\$		
	tigge. Mangangganggangganggangganggangganggangg	ምርብ የመስከር መስከር መስከር መስከር መስከር የመስከር መስከር መስከር መስከር መስከር መስከር መስከር መስከር	MANARA BARARA MANARA BARARA

Appendix One

Student File

NO.	NAME	LENGTH	TYPE	DESCRIPTION	RANGE
	elds 1 thru ilable from			n the Air Force Person	nnel Data System,
1	NAME	27	A	Student's Name	any (e.g.) SMITH JOHN R
2	RANK	2	A	Rank/Pay Grade	01-15 (that's,zero-one)
3	SEX	1	A	Gender	M or F
4	RACE	3	A	Ethnicity	BLK, CAU or OTH
5	MAR.ST	1	A	Marital Status	D, M, S, U
6	SSAN	9	A	Social Security No.	000000000 - 999999999
7	DOB	6	N	Date of Birth	yymmdd (e.g.) 510922
8	COMP	5	A	Service Component	AFRES, ANG, CIV, USA, USAF, USMC, USG, USN or country indicator(e.g.) PAKIS
9	DOR	6	N	Date of Rank	yymmdd (e.g.) 860801
10	PLSD	6	N	Pay List Service Date (Total Service)	yymmdd (e.g.) 750815
1 1	COMM	7	Α	Commissioning Source	ACAD MI, AF ACAD, DIRECT, DP CIV, DP MIL, OCS, OTHER, OTS, OTS DMG, ROTC, ROTC DG, ROTCDMG, UNKNOWN, USMA, USNA
12	AERO	9	A	Aeronautical Rating	MAST NAV, NAV, NAVIGATOR, NFO, NO RATING, NONE, PILOT, SR NAV, SR PILOT, (blank)
13	RTFD	4	N	Return to Fly Date	blank or yymm(e.g.) 9008

AND STANDARD CONTROL OF THE ST

NO.	NAME	LENGTH	TYPE	DESCRIPTION	RANGE
14	MOF	3	A	Months of Flying	blank or nnn (e.g.) (
15	AC1.HRS.DT	15	A	Most recent acft, hours, last flying date	aaaaaaahhhhyymm (e.g. F-5E/F 02168701
16	AC2.HRS.DT	15	A	Next most recent aircraft, hours, date	Same as field 15
17	AC3.HRS.DT	15	A	Third most recent aircraft, hours, date	Same as field 15
8	ED.LEVEL	4	A	Education Level	BAC, BAC+, DOC, MAS, MAS+, PHD, RN, 1PDG
9	DAFSC	6	A	Duty Air Force Specialty Code	(e.g.) K1115H, or 491
20	PAFSC	6	A	Primary AFSC	н н н
21	AFSC2	6	A	Secondary AFSC	H H H
22	AFSC3	6	A	Tertiary AFSC	H H H
23	PME1	5	A	Junior Service School Grad	(blank), ARMY, SOS, SOS
24	PME2	5	A	Intermediate Service School Grad	(blank), ACSC, ACSCC, ACSCS, CSC, MCCSC
25	PME3	5	A	Senior Service School Grad	(blank), MCCSC, OTHER
26	MAJCOM	3	A	Command, Special Operating Agency, or	(blank), AAC, AAG, ACD, AAFW, ATC, AUN, CBT, CMC, I ELC, ELM, ESC, EUR, HAF, I INT, ISC, LCT, LOG, MAC, MGS, OSI, PAF, RPC, SAC, S SYS, TAC, TAP, TEC
27	ORG.LVL	3	A	Highest Organizat- ional Level	(blank), ADV, DOD, HAMAJ, NAF, SOA, SQD, SQN, WNG
(Fi	elds 28 thr	u 49 are	e ente	ered by the mixing pro	ogram or manually)
28	SQUADRON	1	A	ACSC Squadron	1, 2, 3, or 4
				40	

NO.	NAME	LENGTH	TYPE	DESCRIPTION	RANG	<u>E</u>
29	MIX1	2	A	Seminar Assignment for 1st Mix	01 -	44
30	MIX2	2	Α	2nd Mix Seminar	**	#
31	ехім	2	A	3rd Mix Seminar	Ħ	#
32	MIXX	2	A	Tentative Mix Assigned by mixer	#	Ħ
33	STU.NO	4	A	Student Number	0005	-99 9 5
34	SOS	1	Α	SOS Instructor	Y or	blank
35	ARI	1	A	Air Power Research Institute Fellow	Y or	blank
36	CC	1	A	Indicates Class Com- mander	Y or	blank
37	SRO	1	A	Indicates Senior Ranking Officer in Squadron	Y or	blank
38	SL	1	A	Has held Seminar Leader position	Y or	blank
39	ASL	1	A	Has held Asst. Sem- inar leader posn.	Y or	blank
40	SLX	1	A	Seminar Leader in tentative mix	Y or	blank
41	ASLX	1	A	Asst. Seminar Leader in tentative mix	Y or	blank
42	PPBSK	1	Α	Has PPBS skill	Y or	blank
43	ACQLOGSK	1	A	Has Acquisition/Log skill	Y or	blank
44	SPACESK	1	A	Has Space Ops skill	Y or	blank
45	TBD1	1	A	Unassigned attribute	Y or	blank
46	TBD2	1	A	Unassigned attribute	Y or	blank
47	TBD3	1	A	Unassigned attribute	Y or	blank

NO.	NAME	LENGTH	TYPE	DESCRIPTION	Ä	RA	NGE	<u> </u>
48	TBD4	1	A	Unassigned	attribute	Y	or	blank
49	TBD5	1	Α	Unassigned	attribute	Y	or	blank

Fields 50 thru 66 are calculated fields. That is, their values (Y or blank) are calculated by the system according to formulas defined in the data base. See SMART Data Base Manager Reference Guide, page Create-9 for details. Each field has a value of blank or "Y". The "Y" condition is shown.

NO.	NAME	DESCRIPTION	"Y" CONDITION
50	10	International Officer	COMP = anything but US components. (i.e.) not AFRES, ANG, CIV, USA, USAF, USMC, USN, USG
51	USAF	Active Air Force	COMP= "USAF" (not ANG or AFRES)
52	NOMAST	No Master's Degree	ED.LEVEL shows no Master or higher
53	SORG	Sr. Orgn Experience	ORG.LVL shows MAJCOM or higher
54	PILOT	Pilot	AERO shows pilot
55	NAVIGATOR	Navigator	AERO shows nav
56	SINGLE	No spouse	Single, divorced or unaccompanied
57	USAFA	AF Academy grad	COMM = "AF ACAD"
58	ARMY	Army Officer	COMP = "USA"
59	OTHERCOMP	Not Army or USAF	COMP = AFRES, ANG. USMC. Navy. Coast Guard or Civilian
60	MINORITY	Ethnic Minority	RACE is non-caucasian
61	FEMALE	Female	SEX = "F"
62	CAPTAIN	Rank is Captain	RANK = "03"
63	NONLINE	Not a line officer	Civilian or PAFSC is Medical; Legal or Chaplain
64	STRATOPSK	Strategic Ops skills	Missiles or Bomber background
65	TACOPSK	Tactical Ops skills	PAFSC shows Fighter background
66	COULDBSL	Qualified to be Seminar Leader	Any US officer

Appendix Two

SMART Project Files Program Listings

The following programs are written in the SMART project file programming language. See the SMART System Manual, Project Processing Guide for details.

Project File	
Name Page	Description
SMSS 44	Entry and Main Routine. Displays most menus and calls other project file routines.
ENVWRITE 65	Writes environment record for mixer.
GOMIX 66	Returns to MS-DOS when mixer Requested.
IODEL 67	Deletes IO records from student file.
LOADEM 68	Loads student and help screen files.
NEWMIX 69	Called upon return from mixer. Updates student file with tentative mix results.
RAMLOAD 71	Loads student file into Virtual disk.
RAMSAVE 72	Dumps student file from virtual disk to floppy.
STUNUMB 73	Assigns student numbers.
STUREAD 74	Reads student file data from ASCII floppy disk.
STUWRITE 76	Writes student file in ASCII format for mixer.

```
COMMENT ********************************
COMMENT ENTRY POINT FOR MAIN SMSS PROGRAM
COMMENT WRITTEN BY MAJ RICHARD M. JENSEN
COMMENT VARIABLE & PARAMETER CONVENTIONS:
COMMENT
         STANDARD PROJECT VARIABLES (TEXT1, TEXT2, VALUE1, VALUE2) HAVE ONLY A
COMMENT
         TEMPORARY SCOPE. ALL OTHER VARIABLE NAMES ($name) HAVE SPECIFIC
COMMENT USES AND ARE NOT USED FOR MORE THAN ONE PURPOSE.
COMMENT
        PARAMETERS %1-%8 HAVE TEMPORARY SCOPE. %9 AND %0 HAVE SPECIFIC USES
COMMENT
         (%9 INDICATES CHOSEN MIX # IN REPORTS SECTION, %0 INDICATES MEDIA
COMMENT
         SELECTION THROUGHOUT)
COMMENT *********
COMMENT HOUSEKEEPING AND ONE TIME SETUP
QUIET On
singlestep off
COMMENT DELETE ENV. ASC IF IT HAPPENS TO EXIST
COMMENT IN CASE WE EXIT ABNORMALLY, DON'T WANT SMSS.BAT TO THINK WE'RE MIXING
if file("env.asc")=1.0 then file erase env.asc
COMMENT OPEN THE ENVIRONMENT FILE
load environ screen environ1
COMMENT ENTRY TO SMSS FROM SMSS.BAT COULD BE FROM ONE OF 2 PLACES:
COMMENT
             INITIAL ENTRY (PRE-MIXING) OR
          1.
COMMENT
             AFTER MIXING
          2.
COMMENT EXISTENCE OF MIXER OUTPUT FILE, STUDUT. ASC IS INDICATOR OF WHICH.
COMMENT NOTE, MIXER CREATES STUDUT.ASC. TEST FOR STUDUT.ASC
COMMENT IF IT EXISTS GO COPY THE TENTATIVE MIXING INFO INTO THE DATA BASE
COMMENT IF NOT ASK USER WHICH MEDIA HE'S OPERATINE FROM
if file ("stuout.asc")=1.0
        execute newmix in-memory
   else
        call getmedia
COMMENT GETMEDIA AND NEWMIX RETURN $MEDIA AND %O TO INDICATE USER'S CHOICE
COMMENT OF MEDIA. DON'T USE %O FOR ANYTHING ELSE
endif
COMMENT main menu (level 1) loop
label main
COMMENT DISPLAY WELCOME TITLE
call maintitl
let $lvi=1
menu print 8 36 15 4 OPTIONS
menu print 10 24 15 4 1. FILE MAINTENANCE
menu print 12 24 15 4 2. PERFORM MIXING
menu print 14 24 15 4 3. PRODUCE REPORTS
COMMENT GET MENU SELECTION
$firstline=10
```

```
$lastline=14
$linediff=2
$colm=23
label inloop1
call selopt
COMMENT DEBUG SINGLESTEP ON
COMMENT TEST INPUT
if $option = 1
   call preprocess
    jump main
elseif $option= 2
   call mixem
    jump main
elseif $option= 3
   call reports
    jump main
COMMENT TEST FOR H
elseif $key= 104 or $key=72
   call help
    jump main
COMMENT TEST FOR ESCAPE MEANING EXIT
elseif $key= 27
COMMENT EXISTENCE OF FILE ENV.ASC, THE ASCII ENVIRONMENT FILE, IS THE KEY
COMMENT WHETHER EXIT BACK TO DOS IS FROM HERE OR FROM A MIXING REQUEST.
COMMENT ERASE ENV. ASC TO SHOW WE'RE EXITING NORMALLY
   menu clear 15 1
   if file("env.asc")=1.0 then file erase env.asc
   unload all
COMMENT IF WE'VE BEEN WORKING ON VDISK, IT NEEDS TO BE SAVED TO FLOPPY
   if $media=3 then execute ramsave in-memory
   end
else beep on
    beep 3 illegal entry--try again
     jump inloop1
endif
COMMENT **********************************
COMMENT ASK USER WHERE DATA IS COMING FROM--FLOPPY, HARD, OR VDISK
COMMENT OUTPUT: $MEDIA=1,2,OR 3. %O=PATH FOR STUDENTS DATABASE FILES
COMMENT NOTE ENTIRE SYSTEM IS TOO BIG FOR ONE FLOPPY DRIVE SO IF CHOICE
COMMENT IS FLOPPY, STUDENTS.* & NEWMIX GO TO B:, EVERYTHING ELSE TO A:
COMMENT ON OUTPUT, %0="B:\", "", OR "D:\"
COMMENT ****
procedure getmedia
$1 v I = 0
```

```
label inloop0
COMMENT PUT OUT WELCOME HEADER
call maintitl
menu print 8 30 15 4 CHOOSE DISK OPTION
menu print 10 24 15 4 1. FLOPPY DISK ONLY--a: (programs), b: (student file)
menu print 11 24 15 4 2. HARD DISK
                                          --c: programs & student file
menu print 12 24 15 4 3. FLOPPY AND VDISK--a: (programs), d: (student file)
menu print 14 22 15 4 *** DEFAULT (Esc) IS OPTION 2 ***
$firstline=10
$lastline=12
$linediff=1
$colm=23
COMMENT GET USER INPUT
call selopt
COMMENT SET DEFAULTS (IN CASE OF ESC OR 2.) TO HARD
$media=2
%0=null
COMMENT TEST FOR ESCAPE INPUT-ASSUME HARD AND EXIT
if $key=27 then jump gmend
COMMENT TEST FOR HELP REQUEST-PRINT SCREEN AND TRY AGAIN
if $key=104 or $key=72
     call help
     jump inloop0
endif
COMMENT MUST BE AN OPTION SELECTION
$media=$option
COMMENT IF HARD DISK, ALL FILES ON SMART DATAMANAGER DEFAULT CATALOG
if $option=2
   %0=null
   jump gmend
endif
COMMENT IF FLOPPY OR VDISK, NEED TO GET STUDENTS DISK IN B:
message Load STUDENTS disk into drive B:-any key when ready
COMMENT IF VDISK, GO LOAD VDISK FROM FLOPPY
if $option=3
   %0≈"d:\"
   execute ramioad in-memory
COMMENT RAMLOAD RETURNS TEXT1=N IF USER BAILS OUT
   if text1 == "n" then jump inloop0
else
COMMENT MUST BE FLOPPY, RETURN POINTING TO B:
   $media=1
   %0="b:\"
endif
label gmend
COMMENT NEED TO SAVE MEDIA IN ENVIRONMENT FILE, ELSE IT WILL GO AWAY WHEN
COMMENT WE GO OFF TO MIXER AND RETURN (i.e variable aren't saved)
goto file environ screen environt
```

goto record rec-number 1

!et [media]=\$media COMMENT OPEN STUDENT FILE execute loadem in-memory return COMMENT ******************* COMMENT DISPLAY A STANDARD HEADER USED IN LEVELS 1 & 0 COMMENT *************** procedure maintitl COMMENT PAINT SCREEN RED menu clear 15 4 menu draw box 2 35 6 44 15 4 menu print 3 36 15 4 WELCOME menu print 4 39 15 4 TO menu print 5 38 15 4 SMSS return COMMENT*****LEVPRINT**** COMMENT DISPLAYS THE CURRENT LEVEL NUMBER AT TOP RIGHT SCREEN COMMENT \$1v1 CONTAINS LEVEL COMMENT********** procedure levprint %1=\$lvl menu print 2 64 15 4 menu level %1 return COMMENT****FOOTER**** COMMENT DISPLAYS THE STANDARD HELP ESCAPE LINE AT BOTTOM SCREEN COMMENT********** procedure footer if \$1v1=0 or \$1v1=1311 %1="next" else %1="last" menu print 20 5 15 4 Enter h for HELP, Esc to exit to %1 menu return COMMENT ******SELOPT**** COMMENT GIVEN A MENU. RETURNS NUMBER OF OPTION SELECTED COMMENT ********** COMMENT INPUT \$FIRSTLINE=LINE NUMBER OF FIRST OPTION \$LASTLINE=LINE NUMBER OF LAST OPTION COMMENT \$COLM=COLUMN NUMBER TO PRINT > OF ==> POINTER COMMENT \$LINEDIFF=LINE SPACING BETWEEN OPTIONS COMMENT COMMENT OUTPUT \$0PTION= NUMBER OF OPTION CHOSEN IF \$OPTION=0, \$KEY=27 FOR ESCAPE OR "H" FOR HELP COMMENT

```
COMMENT ************
procedure selopt
$key=0
call levprint
call footer
%1=$firstline
%2=$colm-4
COMMENT POINTER SYMBOL ==>
%3=chr(205)|chr(205)|chr(16)
COMMENT DISPLAY ARROW AT 1ST OPTION
menu print %1 %2 15 4 %3
COMMENT UNTIL INPUT IS ESC. ENTER. OR h or H FOR HELP
while (key <> 27 and key <> 13 and key <> 104 and key <> 72)
COMMENT SAVE CURRENT ROW TO BLANK OUT LAST POINTER POSN
$lastrow=%1
COMMENT MOVE UP OR DOWN THE MENU OR BEEP ON BAD KEY
COMMENT CHECK FOR UPARROW (18432)
if $kev=18432
   %1=%1-$linediff
COMMENT CHECK FOR DOWNARROW (20480)
elseif key = 20480
   %1=%1+$LINEDIFF
else
   beep
endif
COMMENT WRAP POINTER IF NECESSARY
if %1 < $firstline
   %1=$lastline
endif
if %1>$!astline
   %1=$firstline
COMMENT BLANK OUT LAST SPOT OF POINTER
%4=$lastrow
menu print %4 %2 4 4 "
COMMENT PRINT POINTER AT NEW POSITION
menu print %1 %2 15 4 %3
COMMENT WAIT FOR KEY TO BE STRUCK
$key=inchar
endwhile
if $key=13
     $option=((%1-$firstline)/$linediff)+1
else
     $option=0
COMMENT DEBUG Iprint $option; $key
return
```

```
COMMENT****HELP*****
COMMENT DISPLAYS HELP SCREEN FOR LEVEL INDICATED IN $1v1
COMMENT**********
procedure help
COMMENT CALL UP THE APPROPRIATE HELP SCREEN
%1=$ | v |
load help screen help%1
paint graphics foreground 11
COMMENT THIS UPDATE IS JUST A DUMMY OPERATION TO GET THE HELP SCREENS UNDER
COMMENT USER CONTROL. NOT REALLY UPDATING ANYTHING
update
unload screen help%1
paint graphics foreground 15
goto file %Ostudents screen student1
return
COMMENT ****PREPROCESS****
COMMENT LEVEL 11 MENU DISPLAY
COMMENT *************
procedure preprocess
COMMENT CLEAR KEY UPDATE INDICATOR
#keyup=0
label main11
$ | v | = 11
COMMENT SET UP SCREEN AS USUAL
menu clear 15 4
menu draw box 2 32 5 46 15 4
meno print 3 38 15 4 FILE
menu print 4 34 15 4 MAINTENANCE
menu print 7 36 15 4 OPTIONS
menu print 9 24 15 4 1. BUILD STUDENT RECORDS FROM ANOTHER DISK
menu print 10 24 15 4 2. ADD STUDENT RECORDS MANUALLY
menu print 11 24 15 4 3. EDIT EXISTING STUDENT RECORD
menu print 12 24 15 4 4. DELETE STUDENT RECORD
menu print 13 24 15 4 5. DESIGNATE STUDENT NUMBERS
menu print 14 24 15 4 6. EDIT ENVIRONMENT RECORD (MIXING RULES)
menu print 15 24 15 4 7. DELETE 10'S (FOR MIX 3)
menu print 16 24 15 4 8. POST MIXER TENTATIVE ASSIGNMENTS
$firstline=9
$lastline=16
$linediff=1
$colm=23
label inloop11
 call selopt
if $cption=1
   call sturead
```

```
elseif $option=2
COMMENT LOAD SCREEN THAT ALLOWS ALL FIELD ENTRIES
   goto file %Ostudents screen student2
   enter
   $keyup=1
COMMENT BACK TO NORMAL SCREEN
   goto file %Ostudents screen student1
elseif $option=3
   call recfind
COMMENT TEST FOR HELP, ESCAPE OR RECORD NOT FOUND AND UPDATE IF OK
   if $option <> 0 then update
elseif $option=4
   call recfind
COMMENT TEST FOR HELP, ESCAPE, NOT FOUND, OR ALREADY DELETED AND DELETE IF OK
   if $option <> 0 and deleted=0.0 then delete
elseif $option=5
   execute stunumb in-memory
elseif $option=6
   goto file environ screen environ1
   update
   goto file %Ostudents screen studenti
elseif $option=7
   execute iodel in-memory
elseif $option=8
   menu print 15 61 15 4 Mix? (1,2 or,3)
   label ask8
   beep
   menu input 16 61 4 15 1 text1
   if texti=null then jump maini1
   if text1<>"1" and text1<>"2" and text1<>"3" then jump ask8
   %1=text1
   menu print 20 35 4 15 Posting permanent mix %1
   query predefined postmix%i neither
elseif $key=104 or $key=72
   call help
elseif $key=27
COMMENT ESCAPE-UPDATE KEYS IF ADD HAS BEEN DONE
       if $keyup<>0
       menu print 20 59 4 15 Updating key fields
       key update
```

endif return endif jump mainii COMMENT ********************* COMMENT LEVEL 111 PROCEDURE - READ IN STUDENT RECORDS COMMENT ***************** procedure sturead label mainili \$1v1=111 COMMENT SET UP SCREEN AS USUAL menu clear 15 4 menu draw box 2 25 4 52 15 4 menu print 3 26 15 4 SMSS - BUILD STUDENT FILE menu print 5 15 15 4 This option allows you to build the student file by menu print 6 15 15 4 reading student records from an ASCII floppy disk file. menu print 7 15 15 4 See the SMSS users manual for the correct format of menu print 8 15 15 4 this file. You can build the student file from menu print 9 15 15 4 scratch or you can add new records to the end of the menu print 10 15 15 4 existing file. menu print 11 31 4 15 *****WARNING***** menu print 12 15 15 4 If you build from scratch, anv records in the current menu print 13 15 15 4 student file will be lost. menu print 15 36 15 4 OPTIONS menu print 16 24 15 4 1. BUILD STUDENT FILE FROM SCRATCH menu print 17 24 15 4 2. ADD RECORDS TO STUDENT FILE \$firstline=16 \$lastline=17 \$linediff=1 \$colm=23 call selopt if \$option=0 and \$key=27 then return if \$option=0 and (\$key=104 or \$key=72) call help jump main111 endif execute sturead in-memory return COMMENT *******RECFIND****** COMMENT LEVEL 113/4 PROCEDURE- FIND A PARTICULAR RECORD COMMENT BASED ON NAME, SSAN OR STU.NO. GIVE USER THE OPTION WHICH COMMENT ************* procedure recfind label main113

```
$1v!=113
COMMENT SET UP SCREEN OF OPTIONS
call rfscreen
$firstline=11
$lastline=13
$linediff=1
call selopt
COMMENT CHECK FOR ESCAPE OR HELP AS USUAL
if $option=0 and $key=27 then return
if $option=0 and ($key=104 or $key=72)
   call help
   jump main113
endif
COMMENT INPUT A NAME. SSAN OR STU. NO ON THE OPTION LINE
COMMENT %1=SELECTED OPTION LINE NO. %2=LENGTH OF NEXT INPUT
COMMENT %3=VALUE OF INPUT, %4=KEY TO SEARCH ON, %5=FIND MODE,%6=FIND OPTION
%1=$firstline+$option-1
COMMENT ASSUME "EQUAL" AND "GLOBAL" FIND MODE AND OPTIONS
%5="equal"
%6=""
if $option=1
   %2=27
   %4="[name]"
COMMENT ON NAME SEARCH, DO (SLOWER) PART WORD AND CASE-LESS OPTIONS
   %5="partial"
   %6="iw"
   order key [name]
elseif $option=2
   %2=9
   %4="[ssan]"
   order key (ssan)
elseif $option=3
   %2=4
   %4="[stu.no]"
   order key [stu.no]
endif
COMMENT NEED TO REFRESH SCREEN SINCE ABOVE "ORDERS" DISTURBED IT
call rfscreen
menu print 10 50 15 4 ENTER SEARCH VALUE
beep
menu input %1 50 4 15 %2 text1
COMMENT GIVE ANOTHER CHANCE TO BAIL OUT
if text1 = null
   $option=0
   return
endif
menu clear 15 4
menu print 20 58 4 15 Searching for Record
```

```
%3=text1
COMMENT ALL THE ABOVE WAS SET UP TO ALLOW A BINARY (FAST) SEARCH ON SSAN OR
COMMENT STUDENT NUMBER. IT SHOULD WORK WITH "find %4 %5 %3 options g%6" BUT,
COMMENT IT DOESN'T. FOR SOME REASON I ALWAYS GET CERROR OF 3002 EVEN WHEN
COMMENT BINARY SEARCH FINDS THE RIGHT RECORD. THE FOLLOWING GETS AROUND
COMMENT THE PROBLEM BY CHECKING FOR THE ACTUAL VALUE WE'RE LOOKING FOR EVEN
COMMENT IF THE 3002 RETURN COMES BACK
find %4 %5 "%3" options g%6
COMMENT DELETED RECORDS ARE LIKE THEY'RE NOT THERE
if deleted=1.0 then jump rf2
COMMENT CERROR RETURNS 3002 IF RECORD NOT FOUND
if $option=1 and cerror(>3002 then jump rf1
text2=%4
COMMENT ON BINARY SEARCH, CHECK FOR A RETURNED VALUE THAT WE'RE LOOKING FOR
if $option<>1 and text2=text1 then jump rf1
COMMENT ELSE RECORD NOT FOUND
label rf2
   call rfscreen
COMMENT ECHO MESSAGE AND ORIGINAL VALUE
   menu print %1 6 4 15 ***NOT FOUND***
   menu print %1 50 4 15 %3
COMMENT SET SOPTION TO SHOW NO UPDATE ON RETURN
   $option=0
label rf1
return
COMMENT *********RFSCREEN********
COMMENT DISPLAY THE OPTION SCREEN FOR RECFIND - LEVEL 113 MENU
COMMENT ****************
procedure rfscreen
menu clear 15 4
menu print 3 35 15 4 STUDENT
menu print 4 36 15 4 RECORD
menu print 5 34 15 4 SELECTION
menu draw box 2 33 6 44 15 4
menu print 7 10 15 4 Choose which record to process by one of the following
fields
menu print 8 10 15 4 NOTE: SSAN & STUDENT NUMBER options are much faster
menu print 10 36 15 4 OPTIONS
menu print 11 24 15 4 1. NAME (or partial name)
menu print 12 24 15 4 2. SSAN
menu print 13 24 15 4 3. STUDENT NUMBER
return
COMMENT *********************
COMMENT LEVEL 12 PROCEDURE- CALL MIXING PROGRAM
COMMENT ******************
```

```
procedure mixem
label main12
$1v1=12
COMMENT SET UP SCREEN AS USUAL
menu clear 15 4
menu draw box 2 29 4 48 15 4
menu print 3 30 15 4 SMSS MIXING OPTION
menu print 5 11 15 4 If there have been no changes to the student data base
menu print 6 11 15 4 since the last mixing run, you can skip the ASCII file
menu print 7 11 15 4 update. If there have been changes, or you don't know,
menu print 8 11 15 4 be safe by running the ASCII file update.
menu print 10 36 15 4 OPTIONS
menu print 12 24 15 4 1. SKIP ASCII FILE UPDATE
menu print 13 24 15 4 2. RUN ASCII FILE UPDATE
$firstline=12
$lastline=13
$linediff=1
$co!m=23
call selopt
if $option = 0 and $key=27 then return
if $option =0 and ($key=104 or $key=72)
   call help
   jump main12
endif
COMMENT WRITE ASCII ENVIRONMENT RECORD
execute envwrite in-memory
COMMENT IF SELECTED, UPDATE ASCII STUDENT FILE
if $option=2 then execute stuwrite in-memory
COMMENT GO OFF TO MIXER UNDER DOS AND DON'T RETURN HERE
transfer gomix
COMMENT ********** REPORTS **********
COMMENT LEVEL 13 PROCEDURE - GENERATE SELECTED REPORTS
COMMENT *****
procedure reports
label main13
$|v|=13
COMMENT ASK WHICH MIX WE'RE REPORTING ON
menu clear 15 4
menu draw box 2 28 4 48 15 4
menu print 3 29 15 4 SMSS REPORTS OPTION
menu print 6 24 15 4 Choose which mix to report on.
menu print 8 36 15 4 OPTIONS
menu print 10 24 15 4 1. MIX1
menu print 11 24 15 4 2. MIX2
menu print 12 24 15 4 3. MIX3
menu print 13 24 15 4 4. MIXX (Tentative mix results of last mixer run)
```

```
$firstline=10
$lastline=13
$linediff=1
$coim=23
call selopt
if $option=0 and $key=27 then return
if $option=0 and ($key=104 or $key=72)
   call help
   jump main13
endif
COMMENT SAVE SELECTED MIX NUMBER
$mix=$option
if $mix=1
   %9="1"
elseif $mix=2
   %9="2"
elseif $mix=3
   %9="3"
else
   %9="x"
endif
COMMENT NOW LET USER SELECT REPORT
label main131
$1v1=131
menu clear 15 4
menu draw box 2 28 4 48 15 4
menu print 3 29 15 4 SMSS REPORTS OPTION
menu print 5 36 15 4 OPTIONS
menu print 7 24 15 4 1. SCHOOL MIXING SUMMARY
menu print 8 24 15 4 2. SQUADRON MIXING SUMMARY
menu print 9 24 15 4 3. SEMINAR MIXING REPORT
menu print 10 24 15 4 4. COMPLETE MIXING REPORT (all the above)
menu print 11 24 15 4 5. SCHOOL ALPHA ROSTER
menu print 12 24 15 4 6. SQUADRON ALPHA ROSTER
menu print 13 24 15 4 7. SEMINAR ALPHA ROSTER
$firstline=7
$lastline=13
$linediff=1
$colm=23
call selopt
if $option=0 and $key=27 then jump main13
if $option=0 and ($key=104 or $key=72)
   call help
   jump main131
endif
COMMENT PRODUCE REPORT
call doreport
jump main131
```

CALLANCE DESCRIPTION OF CHARGES OF CONTRACTOR OF DESCRIPTION OF CHARGES OF CH

```
return
COMMENT ****************************
COMMENT PRODUCE REQUESTED REPORTS
COMMENT ON INPUT, SOPTION INDICATES REQUESTED REPORT
                          INDICATES REQUESTED AIX
COMMENT
                  $HIX
COMMENT ********
procedure doreport
COMMENT DETERMINE WHICH REPORT IS REQUESTED
   if $option=1
COMMENT SCHOOL SUMMARY
   call skoolsum
elseif $option=2
COMMENT SQUADRON SUMMARY-ASK WHICH SQUADRON
   menu print 7 52 15 4 Squadron? (1.2.3, or 4)
   menu print 8 52 15 4 382
   label ask2
   beep
   menu input 8 55 4 15 1 text1
   if text1=null then return
   if text1<"1" and text1<>"2" and text1<>"3" and text1<>"4" then jump ask2
   call squadsum
elseif *option=3
COMMENT SEMINAR STAT REPORT
COMMENT SEMINAR ALPH-ASK WHICH SEMINAR(S)
   menu print 8 53 15 4 Seminar(s)?
   menu print 14 27 15 4 Enter: "ALL" for all seminars
   menu print 15 34 15 4 "SQ1", "SQ2", "SQ3", or "SQ4" for all in a sqdn
   menu print 16 34 15 4 Seminar number for single seminar
   label ask3
   beep
   menu input 9 53 4 15 3 text1
COMMENT PICK APPROPRIATE SEMINARS
        if text1=="all"
           jump sortem
        elseif left(text1,2)=="sq"
COMMENT SELECTING ONE WHOLE SQUADRON
           text1=mid(text1,3,1)
           menu print 20 58 4 15 Selecting Seminars
           query predefined squadron index temp2
        elseif text1=null
           return
        else
COMMENT SINGLE SEMINAR-
COMMENT MAKE SURE IT'S IN RANGE
```

```
if val(texti)(i or val(texti) > 50 then jump ask3
COMMENT IF HE ENTERED SINGLE DIGIT, FIX IT
        if len(text1)=1 then text1="0":text1
        menu print 20 58 4 15 Selecting Seminar
        query predefined mix%9 index temp2
        endif
   order index temp2
   label sortem
   call semsum
elseif $option=4
COMMENT COMPLETE MIXING SUMMARY-ALL SEMINARS, SCHOOL, ALL SQUADRONS
   call semsum
COMMENT CLOSE INDEX FILE TEMP
   order sequential
   call skoolsum
   $sqcnt=1
   while $sqcnt <= 4
     text1=fixed($sqcnt,0)
     call squadsum
     order sequential
     $sqcnt=$sqcnt+1
   endwhile
elseif $option=5
COMMENT SCHOOL ALPHA REPORT
   order key [name]
COMMENT DETERMINE OUTPUT MEDIUM
   call whichout
   report print alpha %4 %5
elseif $option=6
COMMENT SQUADRON ALPHA-ASK WHICH SQUADRON
   menu print 11 49 15 4 Squadron?
   menu print 12 49 15 4 382
   label ask5
   beep
   menu input 12 52 4 15 1 text1
   if text1=null then return
   %1=text1
   if text1<>"1" and text1<>"2" and text1<>"3" and text1<>"4" then jump ask5
   order key [name]
   menu print 20 58 4 15 Selecting Squadron %1
COMMENT ISOLATE THAT SQUADRON
   query predefined squadron index temp
   order index temp
COMMENT DETERMINE WHICH OUTPUT MEDIUM
   call whichout
```

report print alpha %4 %5

elseif \$option=7 COMMENT SEMINAR ALPH-ASK WHICH SEMINAR(S) menu print 12 49 15 4 Seminar(s)? menu print 14 27 15 4 Enter: "ALL" for all seminars menu print 15 34 15 4 "SQ1", "SQ2", "SQ3", or "SQ4" for all in a sqdn menu print 16 34 15 4 Seminar number for single seminar label ask6 beep menu input 13 52 4 15 3 text1 if text1=null then return call getsem COMMENT TEST FOR ERROR RETURN if text1="0" then jump ask6 order index temp COMMENT DETERMINE WHICH OUTPUT MEDIUM call whichout report print mix%9 %4 %5 endif COMMENT MAKE SURE WE'RE LOOKING AT WHOLE FILE ON RETURN order sequential return COMMENT *************************** COMMENT PRODUCE SCHOOL MIXING STAT SUMMARY COMMENT *********************** procedure skoolsum COMMENT SORT BY SQUADRON menu print 20 61 4 15 Sorting by squadron sort predefined squadron index temp order index temp menu print 20 47 4 15 Computing school stats COMMENT ZERO ALL THE COUNTERS-4 SETS OF 23 \$frstunit=1 \$lastunit=4 call czero goto record rec-number 1 COMMENT RUN THRU FILE-UPDATE COUNTS OF ALL ATTRIBUTES. THERE WILL BE 4 COMMENT DIFFERENT SETS OF COUNTERS FOR 4 SQUADRONS label nextreci %1=[squadron] call count if record < records goto record next jump nextrec1 endif

```
COMMENT PRINT OUT THE REPORT WITH ALL ATTRIBUTE COUNTERS
   menu print 20 33 4 15 Printing School Stats- Make sure printer is on
   lprint
   lprint repeat(" ",28); "SCHOOL MIX STATISTICS"
   lprint repeat(" ",38);"MIX ";"%9";repeat(" ",25);date1(today)
   lprint
               ATTRIBUTE"; repeat(" ".18); "SQ1"; " SQ2"; " SQ3"; " SQ4"; " TOTAL"
   Iprint "
   lprint
   value1=1
COMMENT THERE ARE 23 DIFFERENT ATTRIBUTES
COMMENT AND THE FIELD DESCRIPTIONS ARE IN THE ENVIRONMENT FILE
   goto file environ screen environi
   while value1<= 23
   %1=value1
COMMENT PRINT ATTRIBUTE COUNT, LABEL , COUNT FOR EACH SQUADRON, & TOTAL COUNT
   lprint repeat(" ",2-len("%1")); "%1. ";[d%1]; repeat(" ",27-len([d%1])); *c%1_1;
   lprint repeat(" ",4-len(fixed($c%1 1,0)));$c%1_2;
   lprint repeat(" ",4-len(fixed($c%1_2,0)));$c%1_3;
   lprinc repeat(" ",4-len(fixed($c%1_3,0)));$c%1_4;
   lprint repeat(" ",4-len(fixed($c%1_4,0)));$c%1_1+$c%1_2+$c%1_3+$c%1_4
   value1=value1+1
   endwhile
COMMENT FORM FEED
   lprint chr(12)
COMMENT CLEAR AWAY THE COUNTERS
   call clear
COMMENT BACK TO STUDENT FILE
   goto file %Ostudents screen student1
return
COMMENT ******************************
COMMENT PRODUCE SQUADRON SUMMARY REPORT
COMMENT ON INPUT TEXT1 = SQUADRON NUMBER
COMMENT *****
procedure squadsum
   %3=text1
   menu print 20 58 4 15 Selecting Squadron %3
COMMENT ISOLATE THAT SQUADRON
   query predefined squadron index temp2
   order index temp2
COMMENT SORT BY SEMINAR
   menu print 20 61 4 15 Sorting by Seminar
   sort predefined semalf%9 index temp
COMMENT ZERO ALL THE COUNTERS-NEED TO KNOW WHICH SEMINARS ARE IN THIS
COMMENT SQUADRON. ENVIRONMENT FILE HAS THAT
   goto file environ screen environ1
   $frstunit=[fstsem%3]
   $lastunit=[lstsem%3]
```

```
menu print 20 61 4 15 Preparing Counters
   call czero
   goto file %Ostudents screen student1
   order index temp
   menu print 20 45 4 15 Computing squadron stats
   goto record rec-number 1
COMMENT RUN THRU FILE-UPDATE COUNTS OF ALL ATTRIBUTES. THERE WILL BE 4
COMMENT DIFFERENT SETS OF COUNTERS FOR 4 SQUADRONS
   label nextrec2
   %1=val([mix%9])
   call count
   if record < records
      goto record next
      jump nextrec2
   endif
COMMENT PRINT OUT THE REPORT WITH ALL ATTRIBUTE COUNTERS
   menu print 20 28 4 15 Printing Squadron %3 Stats- Make sure printer is on
   lprint
   lprint repeat(" ",27); "SQUADRON "; "%3"; " MIX STATISTICS"
   lprint repeat(" ",38);"MIX ";"%9";repeat(" ",25);date1(today)
   lprint
   lprint "
              ATTRIBUTE"; repeat(" ",18);
COMMENT PRINT ALL THE SEMINAR NUMBERS ACROSS TOP LINE
   value1=$frstunit
   while value1<= $lastunit
         lprint repeat("0",2-len(fixed(value1,0)));value1;" ";
         value1=value1+1
   endwhile
   lprint " TOTAL"
   Iprint
COMMENT THERE ARE 23 DIFFERENT ATTRIBUTES
COMMENT AND THE FIELD DESCRIPTIONS ARE IN THE ENVIRONMENT FILE
   goto file environ screen environi
   menu print 20 52 4 15 Printing Squadron %3 Stats
   while value1<=23
   %1=value1
COMMENT PRINT ATTRIBUTE NUMBER, LABEL , COUNT FOR EACH SEMINAR, & TOTAL COUNT
   lprint repeat(" ",2-len("%1")); "%1. ";[d%1]; repeat(" ",27-len([d%1]));
   value2=$frstunit
   $tot=0
      while value2<=$lastunit
         %2=value2
         lprint $c%1_%2; repeat(" ", 3-len(fixed($c%1_%2,0)));
         value2=value2+1
         $tot=$tot+$c%1 %2
      endwhile
   Iprint $tot
```

```
value1=value1+1
  endwhile
COMMENT FORM FEED
  lprint chr(12)
COMMENT CLEAR AWAY THE COUNTERS
  call clear
COMMENT BACK TO STUDENT FILE
  goto file %Ostudents screen student1
return
COMMENT PRODUCE SEMINAR SUMMARY REPORT
COMMENT *****************
procedure semsum
  menu print 20 58 4 15 Sorting by seminar
COMMENT SORT BY SEMINAR, RANK (KIND OF)-1ST IS MOST POTENTIAL SL. LAST IS LEAST
  sort predefined slorder%9 index temp
  order index temp
COMMENT DETERMINE WHICH OUTPUT MEDIA
  call whichcut
  report print semstat%9 %4 %5
return
```

COMMENT ***********COUNT************* COMMENT UPDATE ALL THE ATTRIBUTE COUNTS BASED ON THIS RECORD COMMENT ********************* procedure count COMMENT IGNORE DELETED RECORDS if deleted them return COMMENT EACH "\$C" COUNTER IS A COUNT OF THAT ATTRIBUTE COMMENT %1 INDICATES WHICH UNIT (SQUADRON OR SEMINAR) \$c1_%1=\$c1_%1+if [usaf]=="y" then 1 else 0 \$c2_%1=\$c2_%1+if [nomast]=="y" then 1 else 0 \$c3_%1=\$c3_%1+if [sorg]=="y" then 1 else 0 \$c4_%1=\$c4 %1+if [pilot]=="y" then 1 else 0 \$c5 %1=\$c5 %1+if [navigator]=="y" then 1 else 0 \$c6 %1=\$c6 %1+if [single]=="y" then 1 else 0 \$c7 %1=\$c7 %1+if [usafa]=="y" then 1 else 0 $c8_{1}=c8_{1}=c8_{1}=0$ \$c9 \%1=\$c9 \%1+if [othercomp]=="y" then 1 else 0 \$c10 %1=\$c10_%1+if [minority]=="y" then 1 else 0 \$c11 %1=\$c11 %1+if [female]=="y" then 1 else 0 \$c12_%1=\$c12_%1+if_[captain]=="y" then 1 else 0 \$c13_%1=\$c13_%1+if [nonline]=="y" then i else 0 \$c14 %1=\$c14 %1+if [stratopsk]=="y" then 1 else 0 \$c15_%1=\$c15_%1+if [tacopsk]=="y" then 1 else 0

```
$c16 %1=$c16 %1+if [ppbsk]=="y" then 1 else 0
$c17_%1=$c17_%1+if [acqlogsk]=="y" then 1 else 0
$c18_%1=$c18_%1+if [spacesk]=="y" then i else 0
$c19_%1=$c19_%1+if [tbd1]=="y" then 1 else 0
$c20_%1=$c20_%1+if [tbd2]=="y" then 1 else 0
$c21_%1=$c21_%1+if [tbd3]=="y" then i else 0
$c22_%1=$c22_%1+if itbd4]=="y" then i else 0
c23_{1}=c23_{1}+if [tbd5]=="y" then 1 else 0
return
COMMENT *************CZERO***
COMMENT ZERO ALL THE COUNTERS
COMMENT COUNTERS ARE $Cij WHERE i RANGES FROM 1 TO 23 AND
          j CAN BE 1 TO 4 FOR SQUADRONS IN THE SCHOOL SUMMARY
COMMENT
COMMENT
                OR ANY SEMINAR NUMBER IN THE SQUADRON SUMMARY
COMMENT ON INPUT, $FRSTUNIT & $LASTUNIT ARE 1 AND 4 FOR SCHOOL SUMMARY
COMMENT
            OR THE HIGHEST & LOWEST SEMINAR NUMBER FOR SQUADRON SUMMARY
COMMENT ***************************
procedure czero
value1=$frstunit
while value1 <= $lastunit
%1=value1
value2=1
COMMENT 23 COUNTERS FOR EACH UNIT
   while value2<=23
   %2=value2
   $c%2_%1=0
   value2=value2+1
   endwhile
value1=value1+1
endwhile
return
COMMENT **************************
COMMENT CLEAR ALL THE COUNTERS FROM MEMORY
procedure clear
value1=$frstunit
while value1 <= $lastunit
%1=value1
value2=1
COMMENT 23 COUNTERS FOR EACH UNIT
  while value2<=23
   %2=value2
   clear $c%2 %1
   value2=value2+1
   endwhile
```

```
value1=value1+1
endwhile
return
COMMENT ********GETSEM*******
COMMENT RUN APPROPRIATE QUERY BASED ON TEXT1 INPUT
COMMENT RETURN WITH TEMP INDEX FILE SET
COMMENT **************
procedure getsem
if text1=="all"
COMMENT SORT WHOLE FILE ON SEMINAR ORDER. REMEMBER %9 IS BASED ON $MIX
elseif left(text1,2)=="sq"
COMMENT SELECTING ONE WHOLE SQUADRON
   text1=mid(text1,3,1)
   menu print 20 59 4 15 Selecting Seminar(s)
   query predefined squadron index temp2
    order index temp2
COMMENT SORT BY SEMINAR/ALPHA
else
COMMENT SINGLE SEMINAR
COMMENT MAKE SURE IT'S IN RANGE
    if val(text1)<1 or val(text1) > 50
      text1="0"
      return
   endif
COMMENT IF HE ENTERED SINGLE DIGIT, FIX IT
   if len(text1)=1 then text1="0":text1
   menu print 20 56 4 15 Selecting Seminar
   query predefined mix%9 index temp2
   order index temp2
endif
   menu print 20 61 4 15 Sorting by seminar
   sort predefined semalf%9 index temp
return
COMMENT USER SELECTS PRINT OUTPUT OPTION: PRINTER, DISK, OR SCREEN
COMMENT ON RETURN, %4= "PRINTER", "DISK", OR "SCREEN"
COMMENT
                 %5= NULL, FILENAME OF DISK FILE, OR NULL
COMMENT ***********************************
procedure whichout
label main1311
$1v1=1311
COMMENT DISPLAY SELECTION SCREEN
menu clear 15 4
menu draw box 2 31 5 45 15 4
menu print 3 32 15 4 REPORT OUTPUT
```

```
menu print 4 34 15 4 SELECTION
menu print 6 19 15 4 Choose where you want report output sent
menu print 8 36 15 4 OPTIONS
menu print 10 24 15 4 1. PRINTER
menu print 11 24 15 4 2. DISK
menu print 12 24 15 4 3. SCREEN
menu print 14 24 15 4 Default (Esc) is PRINTER
$firstline=10
$lastline=12
$linediff=1
$colm=23
call selopt
if $option=0 and $key=27 then $option=1
if $option=0 and ($key=104 or $key=72)
   call holp
   jump main1311
endif
%6=null
COMMENT CALCULATE %4 AND %5
if $option=1
   %4="printer"
   %5≈null
elseif $option=2
   %4="disk"
COMMENT GET DISKFILE NAME
   menu print 10 37 15 4 Enter file (or path) name--No extension
   menu input 11 37 4 15 20 text1
   if text1=null then jump main1311
   %5=text1
   %6="file, " ("%5": ".prt"
else
   %4="screen"
   %5=null
menu print 20 30 4 15 Sending report to %4 %6
return
```

**** Project File ENVWRITE ****

COMMENT WRITE THE ASCII ENVIRONMENT RECORD COMMENT FIRST ERASE ENV. ASC IF IT ALREADY EXISTS goto file environ screen environ1 if file("env.asc")=1.0 then file erase env.asc COMMENT REBUILD ONE-RECORD ASCII ENVIRONMENT FILE COMMENT THIS ORDER SEEMS A LITTLE COMPLICATED BUT IT'S THE ORDER THAT MIXER COMMENT NEEDS THEM IN. IF THE STRUCTURE OF ENVIRON EVER CHANGES, THESE FIELD COMMENT NUMBERS WILL PROBABLY CHANGE, BUT THE RELATIVE ORDER MUST STAY THE COMMENT SAME. THAT ORDER IS MIX, MEDIA, NUM. BUDS, FSTSEM1, LSTSEM1, MISSEM11, COMMENT MISSEM12, MISSEM13, (SEMINAR DATA FOR SQDN 2,3,& 4), SEMCHANGE, BUDS, SPACESK, PPBSK, TACOPSK COMMENT STRATOPSK. PILOT, ANV. SINGLE USAFA, ARMY, OTHRCOMP, MINORITY, FEMALE, COMMENT CAPTAIN, NONLINE, SORG, SOSRULE, NOMAST, USAF, IORULE, TBD1, COMMENT TBD2, TBD3, TBD4, TBD5. NOTE ARIRULE NOT USED. write all [1;74;2:22;27;26;45;43;42;41;44;31:40;30;24;29;28;25;46:50] ascii env.asc

O SOCIOLO POSSOCIO POSSOCIO PERSOCIO PROGRAMO RESOCIO POSSOCIO POSSOCIO POSSOCIO POSSOCIO POSSOCIO POSSOCIO PO

COMMENT PROJECT FILE GOMIX
COMMENT WARVE STATE SESSION AND EXIT OFF TO DOS TO DO NIXING
menu clear 15 4
menu print 20 51 4 15 Exit Smart. Go off to mixer
quit

**** Project File IODEL ****

COMMENT PROJECT IODEL- DELETE ALL THE INTERNATIONAL OFFICERS COMMENT THEY'RE GONE AFTER 2ND MIX. THIS PROCESS MARKS THEM DELETED BUT DOES COMMENT NOT PURGE THEIR RECORDS FROM THE STUDENT FILE menu clear 15 4 menu print 3 24 15 4 SMSS - DELETE 10'S menu draw box 2 23 4 42 15 4 menu print 5 2 15 4 This process should be done prior to mixing for 3rd mix menu print 6 2 15 4 since the IO's will be gone then. menu print 8 2 15 4 ARE YOU SURE YOU WANT TO DELETE 10'S(y/n)? label iodel1 beep 1 menu input 8 45 4 15 1 \$answer if \$answer=="n" then end if \$answer<>"y" and \$answer<>"Y" then jump iodel1 COMMENT USE PREDEFINED QUERY TO DELETE IOS menu print 20 40 4 15 Deleting International Officer Records query predefined iodel neither end

**** Project File LOADEM ****

```
COMMENT *********LOADEM******
COMMENT INITIAL LOAD OF STUDENT DATA BASE & HELP SCREEN FILE
COMMENT %O MUST BE SET OUT OF GETMEDIA OR NEWMIX
COMMENT **************
menu print 20 58 4 15 Loading Student file
load %Ostudents screen studenti
if cerror=3001
   beep 3
   message Error opening students database -- give up
COMMENT TELL SMSS.BAT NOT TO DO MIXING
   unload all
   if file("env.asc")=1.0 then file erase env.asc
   quit
endif
activate %0students screen student2
menu print 20 54 4 15 Loading Help Screen file
activate help screen standard
```

**** Project File NEWMIX ****

```
COMMENT ************
COMMENT PROJECT NEWMIX-UPDATE STUDENT DB WITH RESULTS OF MIXING
COMMENT $media and %0 set on return IAW environment file
COMMENT ***************
COMMENT FIRST GET MEDIA CODE OUT OF ENVIRONMENT FILE TO DETERMINE HOW WE'RE
COMMENT OPERATING. THIS WAS SET BY USER AT INITIAL ENTRY
goto file environ screen environi
goto record rec-number 1
let $media=[media]
COMMENT FLOPPY?
if $media=1
   %0="b:\"
COMMENT HARD DISK?
elseif $media=2
   %0=null
COMMENT FLOPPY/VDISK?
elseif $media=3
   %0="d:\"
COMMENT ANYTHING ELSE MEANS A PROBLEM
PISP
   message ERROR in environment file media code
   stop
endif
COMMENT READ STUDUT. ASC (MIXER OUTPUT) INTO NEWMIX DATA BASE
COMMENT NEWMIX WILL BE THE TRANSACTION FILE TO UPDATE FIELDS IN STUDENTS
load %Onewmix screen standard
menu print 20 37 4 15 Reading mixer interface file (stuout.asc)
COMMENT MIXER PASSES NAME, STU. NO, SQUADRON, MIXX, RULE PRIORITY, SLX, ASLX, CC, SRO
COMMENT WE'LL IGNORE NAME.CC. AND SRO
read ascii stuout.asc fields [0; stu.no; squadron; mixx; priority; slx; aslx]
COMMENT PREPARE FOR TRANSACTION UPDATE. LOAD STUDENT FILE
execute loadem in-memory
order key [stu.no]
split horizontal 11 2
goto window 2
goto file %Onewmix screen standard
menu print 19 33 4 15 ***UPDATING STUDENT FILE WITH NEW MIX DATA***
COMMENT DETERMINE TIME TO RUN
if $media=1
   %1="33"
elseif $media=2
   %1=#9#
elseif $media=3
   %1="15"
endif
menu print 20 33 15 4 This will take about %1 minutes. Please wait.
transactions predefined newmix no-audit
```

**** Project File NEWMIX ****

COMMENT PREDEFINED TRANSACTION close unload file %Onewmix menu print 20 46 4 15 Purging to utilities purge %Onewmix COMMENT DELETE FILE STUDUT.ASC repaint file erase stuout.asc COMMENT PREDEFINED TRANSACTION SET UP TO DELETE RECORDS-NOW PURGE THEM menu print 20 46 4 15 Purging used transaction records COMMENT DELETE FILE STUDUT. ASC TO SHOW UPDATE HAS BEEN DONE

**** Project File RAMLOAD ****

```
COMMENT *********************
COMMENT LOAD STUDENT (NEWMIX) DATA BASES INTO VIRTUAL MEMORY STORAGE
COMMENT VIRTUAL MEMORY OPERATES MUCH FASTER THAN FLOPPY DISK
COMMENT SYSTEM MUST HAVE BEEN BOOTED WITH THE FOLLOWING COMMAND IN THE ROOT
COMMENT CONFIG.SYS FILE --- DEVICE = \BIN\VDISK.SYS 220
COMMENT **********
menu print 16 2 4 15 NOTE:
menu print 16 7 15 4 This option requires that VDISK be setup in the root
config.sys file
menu print 17 7 15 4 at startup time. If not, go back to DOS & do it.
menu print 18 7 15 4 is VDISK configured? (y/n)
label rloop
beep
menu input 18 34 4 15 1 text1
COMMENT IF USER BAILS OUT RETURN WITH TEXT1=N
if text1=="n" then end
if text1<>"y" and text1<>"Y" then jump rloop
COMMENT COPY ALL STUDENTS & NEWMIX FILES TO VDISK
menu print 20 47 4 15 Loading Student file to ramdisk
file copy b:\students.db to d:students.db
file copy b:\students.dbs to d:students.dbs
COMMENT INDEX FILES-IF STRUCTURE OF STUDENTS CHANGES, THESE MAY HAVE TO CHANGE
file copy b:\students.iO1 to d:students.iO1
file copy b:\students.i06 to d:students.i06
file copy b:\students.i21 to d:students.i21
file copy b:\newmix.db to d:newmix.db
file copy b:\newmix.dbs to d:newmix.dbs
```

**** Project File RAMSAVE *****


COMMENT *********************** COMMENT SAVE VDISK FILES BACK TO FLOPPY AFTER SMSS SESSION ENDS COMMENT ********************* menu print 20 46 4 15 Reclaiming vdisk files to floppy COMMENT FILE COPY DOESN'T OVERWRITE-SO FIRST DELETE DESTINATION FILES file erase b:students.* file erase b:newmix.db* COMMENT VOLATILE VDISK BACK TO PERMANENT FLOPPY file copy d:students.db to b:students.db file copy d:students.dbs to b:students.dbs COMMENT INDEX FILES-NOTE IF FILE STRUCTURE CHANGES-THESE MAY HAVE TO CHANGE file copy d:students.iO1 to b:students.iO1 file copy d:students.i06 to b:students.i06 file copy d:students.i21 to b:students.i21 file copy d:newmix.db to b:newmix.db file copy d:newmix.dbs to b:newmix.dbs COMMENT ERASE RAMDISK FILES SO DON'T GET "FILE EXISTS" MESSAGE NEXT TIME file erase d: *. * repaint

**** Project File STUNUMB ****

COMMENT PROJECT STUNUMB-CREATE STUDENT NUMBERS COMMENT THIS SHOULD BE A ONE TIME OPERATION DONE WHEN STUDENT FILE COMMENT IS SETTLED COMMENT SET UP SCREEN-ISSUE WARNING MESSAGE menu clear 15 4 menu print 3 24 15 4 SMSS - CREATE STUDENT NUMBERS menu draw box 2 23 4 53 15 4 menu print 5 2 15 4 This process should generally be done once at the start of menu print 6 2 15 4 the school year after all the records have been added to menu print 7 2 15 4 the student file. Once you've assigned student numbers. menu print 8 2 15 4 you shouldn't do this anymore. menu print 10 2 15 4 ARE YOU SURE YOU WANT TO ASSIGN NEW STUDENT NUMBERS (y/n)? label stuni beep 1 menu input 10 61 4 15 1 \$answer if \$answer=="n" then end if \$answer<>"y" and \$answer<>"Y" then jump stuni COMMENT PUT FILE IN ALPHA ORDER order key [name] COMMENT USE PREDEFINED QUERY TO UPDATE EACH [STU.NO] TO 10,15,20,...ETC menu print 20 31 4 15 Assigning student number to each student record query predefined stunum neither COMMENT REORGANIZE KEY FOR NEW VALUES menu print 20 44 4 15 Building student number key file key update end

**** Project File STUREAD ****

```
COMMENT PROJECT STUREAD-READ IN THE STUDENT DATA BASE FROM ASCII DISK
COMMENT ON INPUT, $option IS SET TO 1 OR 2 FROM LEVEL 111 OPTION SCREEN
call header
COMMENT READ IN ASCII FILE- FIRST GET FILENAME
menu print 7 2 15 4 ENTER NAME OF INPUT FILE (e.g. STUDENT.ASC)
menu print 8 2 15 4 (Esc to exit).
beep
menu input 7 46 4 15 12 text1
COMMENT LET HIM BAIL OUT HERE TOO
if text1=null then end
COMMENT OPTION 1 MEANS BUILD FROM SCRATCH-DELETE ALL RECORDS
if $option = 1 then call deletem
call header
%1=text1
message Load source diskette in drive A:--Any key when ready
menu print 20 41 4 15 Reading source file into Student file
COMMENT FIELD LIST MAY HAVE TO CHANGE DEPENDING ON AU/DP
COMMENT NEXT IS INTERIM FORMAT FROM BUCKNER'S DATABASE
READ ASCII A:\%1 FIELDS [1;6;2;9;8;12;19;26;3:5;7;11;18;10;20:22;27;23:25;13:17;
28:31:331
COMMENT UPDATE ALL THE KEYS
menu print 20 36 4 15 Organizing all key indexes
key update
COMMENT IF FLOPPY , MAKE SURE WE GET RUNTIME DISK BACK IN A:
if $media=1 or $media=3 then message Load SMSS execution disk back in A:--Any
key when ready
end
COMMENT ********HEADER********
COMMENT PAINTS THE SCREEN PROPERLY
COMMENT ***************
procedure header
menu clear 15 4
menu print 3 26 15 4 SMSS - BUILD STUDENT FILE
menu draw box 2 25 4 51 15 4
return
COMMENT ******DELETEM********
COMMENT CLEAR OUT EXISTING STUDENT DATA BASE BY DELETING ALL RECORDS
COMMENT *************
procedure deletem
menu print 5 2 15 4 YOU ARE ABOUT TO ERASE ALL CURRENT DATA BASE RECORDS
menu print 6 2 15 4 ARE YOU SURE YOU WANT TO DO THIS (y/n)?
label del1
beep 3
menu input 6 41 4 15 1 $answer
if $answer == "n" then end
if $answer <>"y" and $answer <>"Y" then jump del1
```





**** Project File STUREAD ****

COMMENT THAT'S ENOUGH WARNING-HE REALLY WANTS TO DO IT
COMMENT PREDEFINED QUERY "DELALL" DELETES ALL ACTIVE RECORDS-USE IT
menu print 20 33 4 15 Deleting all old records in Student file
query predefined delall neither
unload file %Ostudents
menu print 20 33 4 15 Purging all deleted records from Student file
utilities purge %Ostudents
load %Ostudents screen student1
return

**** Project File STUWRITE ****

Appendix Three

SMSS Mixer Program Program Listing

The mixer is a program, written in GW-BASIC, that does student mixing according to the rules passed in the environment record.

```
10000 REM ****
10010 REM **
               PROGRAM NAME: STUDENT MIX SOFTWARE SYSTEM (SMSS)
10020 REM **
10030 REM **
                            MIX ACSC STUDENTS
              FUNCTION:
10040 REM **
                                                 DATE: 16 FEB 1988
10050 REM **
              FILE NAME:
                            MIXER.BAS
10060 REM **
              COMPUTER:
                             ZENITH 158
                                                 LANGUAGE: BASIC
10070 REM **
               AUTHOR:
                             ART DECELLES
10080 REM **
10090 REM *****
10100 REM **
10110 REM **
              DESCRIPTION:
10120 REM **
10130 REM **
             THIS PROGRAM OPTIMALLY MIXES ACSC STUDENTS BASED ON STUDENT
10140 REM ** CHARACTERISTICS AND RULE PRIORITIES [NINE (HIGHEST) TO ZERO
                                                                             # *
10150 REM **
             (LOWEST)]. MIXING OCCURS IN THE FOLLOWING GENERAL SEQUENCE:
                                                                             * *
10160 REM **
                                                                             * *
10170 REM **
                   SEMINAR LEADERS AND THEIR ASSISTANTS (SL/ASL) ARE
                                                                             * *
10180 REM **
                   ASSIGNED IN THE FIRST PASS OF THE STUDENT DATA. ALSO,
                   PRE-ASSIGNED STUDENTS ARE "LOCKED-IN". INTERNATIONAL
10190 REM **
                                                                             * *
10200 REM **
                   OFFICERS AND SOS STUDENTS DON'T CHANGE SEMINARS IF THEY
10210 REM **
                   ARE ASSIGNED A PRIORITY OF "9".
10220 REM **
             2. ALL OTHER STUDENTS ARE RANDOMLY ASSIGNED TO SEMINARS
10230 REM **
10240 REM **
                   BASED ON THEIR CHARACTERISTICS, EACH CONSIDERED IN ORDER
10250 REM **
                   OF RULE PRIORITY ESTABLISHED BY THE MIX MASTER.
                                                                             * *
10260 REM **
10270 REM **
                 A. STUDENTS CANNOT BE ASSIGNED TO A PREVIOUS SEMINAR.
                                                                             # #
                 B. ASSIGNMENT IS MADE IF ALLOCATIONS PERMIT.
10280 REM **
                                                                             * *
10290 REM **
                   C. IF CONFLICT OCCURS MIXER ATTEMPTS TO MAKE A ONE FOR
10300 REM **
                      ONE EXCHANGE WITHIN ALLOCATION CONSTRAINTS.
                                                                             * *
                 D. IF STILL NOT POSSIBLE A FORCED ASSIGNMENT IS MADE:
10310 REM **
10320 REM **
                                                                             * *
10330 REM **
                       a. IF AN ALLOCATED SLOT IS AVAILABLE FOR THE RULE
10340 REM **
                           BEING PROCESSED.
10350 REM **
                       b. IF NOT, A ONE FOR ONE EXCHANGE IS ATTEMPTED WITH
10360 REM **
                           ASSIGNMENTS OF EQUAL PRIORITY.
10370 REM **
                       C. AS A LAST RESORT, ONE FOR ONE EXCHANGES ARE
                                                                             * *
                           ATTEMPTED FOR INCREMENTALLY HIGHER PRIORITIES.
10380 REM **
10390 REM **
10400 REM ******
10410 REM **
10420 REM **
             MAJOR VARIABLES:
10430 REM **
10440 REM **
             ALOT(27.4,11): ARRAY CONTAINING ALLOCATIONS WHICH REPRESENT
10450 REM **
                               THE TARGET BALANCED CHARACTERISTICS.
10460 REM **
             STAT(27,4,11): ARRAY TO GATHER STATISTICS ON ASSIGNMENTS.
10470 REM **
                                                                             * *
10480 REM **
```

```
10490 REM **
              ASSIGN(44,13,5): ARRAY CONTAINING A SUBSET OF STUDENT INFO
10500 REM **
                               AFTER AN ASSIGNMENT IN MADE.
10510 REM **
10520 REM **
              CHAR(27): ARRAY WHICH CONTAINS THE CHARACTERISTICS FOR THE
10530 REM **
                               STUDENT CURRENTLY BEING CONSIDERED.
10540 REM **
              SEMI(12): ARRAY MAINTIAINING CONSTRAINT INFORMATION FOR
10550 REM **
10560 REM **
                               ATTEMPTS TO ASSIGN STUDENT TO SEMINARS.
10570 REM **
10580 REM **
              RECNUM(575): ARRAY INDICATING WHICH RECORDS HAVE/HAVEN'T
10590 REM **
                               BEEN ASSIGNED PREVIOUSLY.
10600 REM **
10610 REM **
              MS(3): ARRAY INDICATING MISSING SEMINARS IN A SQUADRON.
10620 REM **
10630 REM **
              SQ$(4,7): ARRAY CONTAINING SCHOOL/SQUADRON PARAMETERS.
10640 REM **
10650 REM **
               SL(4): ARRAY USED TO TRACK SL ASSIGNMENTS.
10660 REM **
10670 REM **
              ASL(4): ARRAY USED TO TRACK ASL ASSIGNMENTS.
10680 REM **
10690 REM **
             STAT$(27): ARRAY CONTAINING RULE ALPHA DESCRIPTORS.
10700 REM **
              RULE$(27): ARRAY CONTAINING RULE PRIORITIES.
10710 REM **
10720 REM **
10730 REM ********
10740 REM **
10750 REM **
              STORAGE REQUIREMENTS:
10760 REM **
10770 REM
10780
              DIM SQ$(4,7), STAT(27,4,11), RULE$(27), ASSIGN(44,13,5), MS(3)
10790
               DIM TEMPIN$(36), STAT$(27), ALOT(27,4,11), SL(4), ASL(4)
10800
               DIM CHAR(27), SEMI(12), RECNUM(575)
10810 REM
10820 REM **
10830 REM *********
10840 REM **
10850 REM **
              INPUT/OUTPUT:
10860 REM **
10870 REM
              FIELD #2, 27 AS SNAME$, 4 AS STN$, 1 AS ASQ$, 2 AS MIX1$,
10880 REM
                   2 AS MIX2$, 2 AS MIX3$, 2 AS MIXX$, 1 AS USAF$,
10890 REM
                   1 AS NOED$, 1 AS HORG$, 1 AS PILOT$, 1 AS NAV$,
10900 REM
                   1 AS SING$, 1 AS AFA$, 1 AS ARMY$, 1 AS REST$,
10910 REM
                   1 AS RACE$, 1 AS SLX$, 1 AS ASLX$, 1 AS PRIOR$
10920 REM
10930 REM
             FIELD #3, 1 AS TOPS$, 1 AS SOPS, 1 AS PPBS$, 1 AS ACQLOG$.
10940 REM
                   1 AS SPAACE$, 1 AS TBD1$, 1 AS TBD2$, 1 AS TBD3$,
                                                                              * *
10950 REM
                   1 AS TBD4$, 1 AS TBD5$, 1 AS SL$, 1 AS ASL$, 1 AS SOS$.
10960 REM
                   1 AS ARI$, 1 AS SRO$, 1 AS CC$, 1 AS 10$, 1 AS FEM$,
10970 REM
```

```
10980 REM
                1 AS RNK$, 1 AS NOLINE$
10990 REM
11000 REM ********
11010 REM **
11020 REM **
             PROCEDURE:
11030 REM **
                                                                           * #
11040 REM
         SCREEN 0,1
11050
11060
         COLOR 2 0,1
11070
         OPEN "O", #1, "ERROR.SMS": PRINT #1, "SMSS MIXER PROGRAM ERROR":CLOSE
11080
         DELTA = +1
11090
         GOSUB 13070
                                              :REM ** RETRIEVE SCHOOL DATA **
         CLS: LN = 3
11100
        LOCATE 2,18: PRINT "TURN THE TRACE OUTPUT OFF AT TERMINAL? (Y/N) ";
11110
        INPUT "", CH$: LOCATE LN.18
11120
        1F CH# = "Y" OR CH# = "y" THEN TRONS = 0: TRONS# = "OFF": GOTO 11200
11130
        IF CH$ = "N" OR CH$ = "n" THEN TRONS = 1: TRONS$ = "ON": GOTO 11200
11140
         IF CH$ = "D" OR CH$ = "d" THEN TRONS = 2: TRONS$ = "ON": GOTO 11200
11150
11160
         LN = LN + 1
11170
         IF LN = 25 THEN GOTO 11100
         PRINT "
11180
                  INCORRECT CHOICE - TRY AGAIN? ":
11190
         GOTO 11120
         CLS: LOCATE 2,32: PRINT "MIX ":MIX;" RULES";
11200
11210
         LOCATE 4,21: PRINT "PROCESSING MIXER INPUT WITH TRACE "; TRONS$:PRINT
11220
        FOR I = 1 TO 27: INPUT #1, RULE$(I): NEXT I :REM ** INIT RULES **
11230
         CLOSE #1
11240
         G05UB 12850
                                      :REM ** INITIALIZE RULE DESCRIPTORS
         GOSUB 13770
11250
                                     :REM ** INITIALIZE STATISTICS
         IOMODE$ = "I": GOSUB 12210 : REM ** PROCESS INPUT DATA
11260
        IOMODE$ = "O": GOSUB 13980 :REM ** INITIALIZE RANDOM # GENERATOR **
11270
11280
        OPEN "O", #1, "MIXERLOG.DAT"
11290
         IF MIX = 1 THEN GOSUB 19900
                                                   :REM ** ALLOC SQ SLOTS **
11300
         GOSUB 14100
                                                   :REM ** ALLOC SEM SLOTS **
        CLS: LOCATE 2.30: PRINT "SMSS MIXING ROUTINE": PRINT
11310
11320
         PRIOR = 9
11330
         GOSUB 16230
                                                      :REM ** ASGN SL/ASL **
11340
         FOR PRIOR = 9 TO 1 STEP -1
             FOR INDEX = 3 \text{ TO } 27
11350
11360
                 IF VAL(RULE$(INDEX)) <> PRIOR THEN GOTO 11410
11370
                 IF PRIOR = 9 AND INDEX = 22 THEN GOTO 11410
11380
                 IF PRIOR = 9 AND INDEX = 19 THEN GOTO 11410
11390
                 IR = INDEX: RL = INDEX: RL$ = STAT$(IR)
11400
                 GOSUB 18700
             NEXT INDEX
11410
        NEXT PRIOR
11420
11430
        IR = 0: INDEX = 0: RL = 0: PRIOR = 0: RL$ = "ALL OTHER": STAT$(0)=RL$
11440
        GOSUB 18700
                                                      :REM ** PROCESS REST **
11450
        CLOSE #1: GOSUB 20170
                                                      :REM ** OUTPUT RSLTS **
11460
         OPEN "I", #1, "MIXERLOG.DAT"
                                                      :REM ** FINISHED
```

```
FOR 1 = 1 TO 999
11470
11480
              IF EOF(1) GOTO 11510
11490
              INPUT #1, TMP$: LPRINT TMP$
11500
          NEXT I
11510
          CLOSE: GOSUB 11610
                                                         :REM ** OUTPUT STATS **
11520
          CLOSE: KILL "ERROR.SMS"
11530
          END
11540 REM
11550 REM **
11560 REM **
11570 REM **
11580 REM **
               SUBROUTINE TO OUTPUT MIXER STATISTICS
11590 REM **
11600 REM
11610
          LPRINT: LPRINT: LPRINT: LPRINT
11620
          STAT$(0) = "SEMINAR ASSIGNMENTS"
11630
          FOR I = 0 TO 27
              IF I = 1 OR I = 2 THEN GOTO 11710
11640
11650
              LPRINT "* STATISTICS ON "; STAT$(!); " PR! = "; RULE$(!)
              FOR J = 1 TO 4
11660
11670
                  LPRINT "SQ:"; J; " => ";
                  FOR K = 1 TO 11: LPRINT STAT(I, J, K): NEXT K
11680
11690
                  LPRINT " "
              NEXT J: LPRINT " "
11700
          NEXT I
11710
11720
          LPRINT "* ASSIGNMENT ARRAY: "
11730
          FOR I = 1 TO 44
              IF I > 11 THEN FS = 12 ELSE FS = 1
11740
11750
              IF I > 22 THEN FS = 23
              IF I > 33 THEN FS = 34
11760
11770
              LPRINT "SEM:": I; " MIX1 STNTS=":
              FOR J = 1 TO 11: CHAR(J) = 0: NEXT J
11780
11790
              FOR J = 1 TO 13
11800
                  IF ASSIGN(I,J,1) = 0 GOTO 11820
11810
                  CHAR(ASSIGN(I,J,1)-FS+1) = CHAR(ASSIGN(I,J,1)-FS+1) + 1
11820
                  LPRINT ASSIGN(1, J, 1);
              NEXT J
11830
11840
              TEMP = 0
11850
              FOR J = 1 TO 11
                  IF TEMP < CHAR(J) THEN TEMP = CHAR(J)
11860
              NEXT J
11870
              LPRINT " MAX#"; TEMP
11880
              LPRINT "SEM:"; 1; " MIX2 STNTS=";
11890
              FOR J = 1 TO 11: CHAR(J) = 0: NEXT J
11900
              FOR J = 1 TO 13
11910
                  IF ASSIGN(I,J,2) = 0 GOTO 11940
11920
                  CHAR(ASSIGN(I,J,2)-FS+1) = CHAR(ASSIGN(I,J,2)-FS+1) + 1
11930
                  LPRINT ASSIGN(I,J,2);
11940
              NEXT J
11950
```

```
11960
              TEMP = 0
              FOR J = 1 TO 11
11970
11980
                  IF TEMP < CHAR(J) THEN TEMP = CHAR(J)
11990
              NEXT J
12000
              LPRINT " MAX#"; TEMP
12010
              LPRINT "SEM:"; 1; " RULE#= ";
12020
              FOR J = 1 TO 13
12030
                  LPRINT ASSIGN(I, J.5):
12040
              NEXT J
12050
              LPRINT " "
12060
              LPRINT "SEM:"; I: " RECORD#= ":
12070
              FOR J = 1 TO 13
                  LPRINT ASSIGN(1, J.O);
12080
12090
              NEXT J
12100
              LPRINT " "
12110
              LPRINT " "
12120
          NEXT I
          RETURN
12130
12140 REM
12150 REM **
12160 REM **
12170 REM **
12180 REM **
               SUBROUTINE TO PROCESS INPUT DATA
12190 REM **
12200 REM
12210
          OPEN "I", #1. "STU. ASC"
12220
          IF MEDIA$ <> "1" THEN GOTO 12260
12230
          OPEN "R", #2, "B:STDNT1.DAT"
          OPEN "R", #3, "B:STDNT2.DAT"
12240
12250
          GOTO 12280
          OPEN "R", #2, "STDNT1.DAT"
12260
12270
          OPEN "R", #3, "STDNT2.DAT"
          FIELD #2, 27 AS SNAME$,4 AS STN$,1 AS ASQ$,2 AS MIX1$,2 AS MIX2$,2 AS
12280
MIX3$,2 AS MIXX$,1 AS USAF$,1 AS NOED$,1 AS HORG$,1 AS PILOT$,1 AS NAV$,1 AS
SING$,1 AS AFA$,1 AS ARMY$,1 AS REST$,1 AS RACE$,1 AS SLX$,1 AS ASLX$,1 AS
PRIOR$
12290
          FIELD #3, 1 AS TOPS$,1 AS SOPS$,1 AS PPBS$,1 AS ACQLOG$.1 AS
SPAACE$.1 AS TBD1$,1 AS TBD2$,1 AS TBD3$,1 AS TBD4$,1 AS TBD5$,1 AS SL$,1 AS
ASL$,1 AS SOS$,1 AS ARI$,1 AS SRO$,1 AS CC$,1 AS IO$,1 AS FEM$,1 AS RNK$,1 AS
NOLINE$
12300
          SI = 0: KO = 1: PRINT: PRINT " READING ";
12310
          FOR KS = 1 TO 575
              IF KS/10 >= KO THEN PRINT ".";: KO = KO + 1
12320
              STDNT = SI
12330
12340
              FOR J = 1 TO 36
12350
                  IF EOF (1) THEN GOTO 12680
12360
                  INPUT #1, TEMPIN$(J)
12370
              NEXT J
              LSET SNAME$ = TEMPIN$(1):
12380
                                             LSET 10$
                                                           = TEMPIN$(21)
```

```
12390
              LSET ASQ$
                                             LSET USAF$
                            = TEMPIN$(2):
                                                           = TEMPIN$(22)
12400
              LSET MIX1$
                            = TEMPIN$(3):
                                             LSET NOED$
                                                           = TEMPIN$(23)
                            = TEMPIN$(4):
12410
              LSET MIX2$
                                             LSET HORG$
                                                           = TEMPIN$(24)
12420
              LSET MIX3$
                            = TEMPIN$(5):
                                             LSET PILOTS
                                                           = TEMPIN$ (25)
              LSET STN$
                            = TEMPIN$(6):
12430
                                             LSET NAV$
                                                           = TEMPIN$(26)
12440
              LSET SOS$
                            = TEMPIN$(7):
                                             LSET SING$
                                                           = TEMPIN(27)
12450
              LSET ARIS
                            = TEMPIN$(8):
                                             LSET AFA$
                                                           = TEMPIN$(28)
12460
              LSET CC$
                            = TEMPIN$(9):
                                             LSET ARMY$
                                                           = TEMPIN(29)
12470
              LSET SRO$
                            = TEMPIN$(10):
                                             LSET REST$
                                                           = TEMPIN*(30)
              LSET SL$
12480
                            = TEMPIN$(11):
                                             LSET RACE$
                                                           = TEMPIN$(31)
12490
              LSET ASL$
                            = TEMPIN$(12):
                                             LSET FEM$
                                                           = TEMPIN$(32)
12500
              LSET PPBS$
                            = TEMPIN$(13):
                                             LSET RNK$
                                                           = TEMPIN$(33)
12510
              LSET ACQLOG$ = TEMPIN$(14):
                                             LSET NOLINE$ = TEMPIN$(34)
              LSET SPAACE$ = TEMPIN$(15):
12520
                                             LSET SOPS$
                                                           = TEMPIN$(35)
12530
              LSET TBD1$
                            = TEMPIN$(16):
                                             LSET TOPS$
                                                           = TEMPIN$(36)
12540
              LSET TBD2$
                            = TEMPIN$(17):
                                             LSET SLX$
                                                           = "0"
12550
              LSET TBD3$
                            = TEMPIN$(18):
                                             LSET ASLX$
                                                           = "0"
12560
              LSET TBD4$
                                             LSET MIXX$
                            = TEMPIN$(19):
              LSET TBD5$
12570
                            = TEMPIN$(20):
                                             LSET PRIOR$
                                                           = "0"
12580
              IF (10$="Y" OR 10$="y") AND RULE$(22)="0" AND MIX=3 GOTO 12670
              JJ = 0: KK = 0: GOSUB 13270
12590
                                                   :REM ** RECORD SCHOOL STATS **
12600
              IF ASQ$ = " " GOTO 12650
              FOR J = 1 TO 4
12610
                                                   :REM ** POST SQUADRON STATS **
12620
                  IF VAL(ASQ$) <> VAL(SQ$(J,1)) GOTO 12640
                  JJ = J: KK = 0: GOSUB 13270: GOTO 12650
12630
12640
              NEXT J
12650
              SI = SI + 1
              PUT #2,SI: PUT #3,SI
12660
12670
          NEXT KS
12680
          STDNT = STAT(0,0,0) : CLS
          LOCATE 2,25: PRINT "PROCESSED"; KS-1; "STUDENTS INTO MIXER"
12690
12700
          LOCATE 3,20: PRINT STDNT; "STUDENTS KEPT FOR FURTHER PROCESSING"
12710
          PRINT
12720
          FOR 1 = 3 TO 27
12730
              IF STAT(1,0,0) = 0 THEN GOTO 12750
12740
              PRINT " THERE WERE "; STAT(1,0,0); " "; STAT$(1); " STUDENTS"
12750
          NEXT I
          PRINT " **** ALL OTHER CHARACTERISTICS WERE NOT REPRESENTED"
12760
12770
          CLOSE #1: RETURN
12780 REM
12790 REM **
12800 REM **
12810 REM **
               SUBROUTINE TO INITIALIZE RULE DESCRIPTIONS
12820 REM **
12830 REM **
12840 REM
                    = "SEMINAR CHANGE":
                                               STAT$(2)
                                                         = "BUDDY RULE"
12850
          STAT$(1)
                     = "SPACE SKILL":
                                                         = "PPBS SKILL"
                                               STAT$(4)
12860
          STAT$(3)
12870
          STAT$(5)
                    = "TAC OPS SKILL":
                                               STAT$(6)
                                                         = "STRAT OPS SKILL"
```

```
STAT$(7) = "ACQ/LOG SKILL":
                                               STAT$(8) = "PILOT"
12880
          STAT$(9) = "NAVIGATOR":
12890
                                               STAT$(10) = "SINGLE/UNACCOMP"
          STAT$(11) = "USAFA GRADUATE":
                                               STAT$(12) = "ARMY"
12900
          STAT$(13) = "RES/NG/USN/USMC/CIV": STAT$(14) = "MINORITY"
12910
          STAT$(15) = "FEMALE":
                                               STAT$(16) = "CAPTAIN"
12920
          STAT$(17) = "NON LINE":
12930
                                               STAT$(18) = "SR ORG EXPERIENCE"
12940
          STAT$(19) = "SOS":
                                               STAT$(20) = "NON MASTER DEGREE"
                                               STAT$(22) = "!0"
12950
          STAT*(21) = "USAF":
12960
          STAT$(23) = "UNLABELED":
                                               STAT$(24) = "UNLABELED"
12970
          STAT$(25) = "UNLABELED":
                                               STAT$(26) = "UNLABELED"
12980
          STAT$(27) = "UNLABELED"
12990
          RETURN
13000 REM
13010 REM **
13020 REM ***
13030 REM **
13040 REM **
                SUBROUTINE TO RETRIEVE SCHOOL DATA
13050 REM **
13060 REM
          OPEN "I", #1, "ENV. ASC"
13070
13080
          INPUT #1, MIX$, MEDIA$, PREV$
13090
          FOR I = 1 TO 4
13100
              ADJ = 0
              INPUT #1, SQ$(I,2), SQ$(I,3), SQ$(I,4), SQ$(I,5), SQ$(I,6)
13110
13120
              SQ$(I.1) = STR$(I)
13130
              IF VAL(SQ\$(1.4)) \iff 0 THEN ADJ = ADJ + 1
13140
              IF VAL(SQ\$(1,5)) \Leftrightarrow O THEN ADJ = ADJ + 1
13150
              IF VAL(SQ$(1,6)) \Leftrightarrow O THEN ADJ = ADJ + 1
13160
              SQ$(1,7) = STR$(VAL(SQ$(1,3)) - VAL(SQ$(1,2)) - ADJ + 1)
13170
          NEXT I
          MIX = VAL(MIX$)
13180
          RETURN
13190
13200 REM
13210 REM **
13220 REM ***
13230 REM **
13240 REM **
               SUBROUTINE TO UPDATE STATISTICS
13250 REM **
13260 REM
          IF IOMODE$ = "0" THEN GOTO 13290
13270
13280
          IF JJ = O THEN STAT(0,0,0) = STAT(0,0,0) + DELTA
          IF KK <> 0 THEN STAT(0, JJ, KK) = STAT(0, JJ, KK) + DELTA
13290
          IF JJ <> 0 THEN STAT(0, JJ, 0) = STAT(0, JJ, 0) + DELTA
13300
13310
          GOSUB 13440
13320
          FOR !! = 3 TO 27
13330
              IF CHAR(II) = 0 THEN GOTO 13350
13340
              STAT(II,JJ,KK) = STAT(II,JJ,KK) + DELTA
          NEXT II
13350
13360
          RETURN
```

```
13370 REM
13380 REM **
13390 REM ***************
13400 REM **
13410 REM **
              SUBROUTINE TO INITIALIZE CHARACTERISTICS ARRAY
13420 REM **
13430 REM
13440
          IF SPAACE$ = "Y" OR SPAACE$ = "y" THEN CHAR(3) = 1 ELSE CHAR(3)
13450
          IF PPBS$
                    = "Y" OR PPBS$
                                     = "y" THEN CHAR(4) = 1 ELSE CHAR(4)
13460
         IF TOPS$
                    = "Y" OR TOPS$
                                     = "y" THEN CHAR(5) = 1 ELSE CHAR(5) = 0
13470
         IF SOPS$
                    = "Y" OR SOPS$
                                     = "y" THEN CHAR(6) = 1 ELSE CHAR(6) = 0
         IF ACQLOG$ = "Y" OR ACQLOG$ = "y" THEN CHAR(7) = 1 ELSE CHAR(7) = 0
13480
         IF PILOT$ = "Y" OR PILOT$ = "y" THEN CHAR(8) = 1 ELSE CHAR(8) = 0
13490
         IF NAV$
                    = "Y" OR NAV$
                                     = "y" THEN CHAR(9) = 1 ELSE CHAR(9) = 0
13500
         IF SING$
13510
                    = "Y" OR SING$
                                     = "y" THEN CHAR(10) = 1 ELSE CHAR(10) = 0
13520
        IF AFA$
                    = "Y" OR AFA$
                                     = "y" THEN CHAR(11) = 1 ELSE CHAR(11) = 0
                    = "Y" OR ARMY$
                                     = "y" THEN CHAR(12) = 1 ELSE CHAR(12) = 0
13530
        IF ARMY$
13540
         IF REST$
                    = "Y" OR REST$
                                     = "y" THEN CHAR(13) = 1 ELSE CHAR(13) = 0
         IF RACE$
                                     = "y" THEN CHAR(14) = 1 ELSE CHAR(14) = 0
13550
                    = "Y" OR RACE$
        IF FEM$
                    = "Y" OR FEM$
                                     = "y" THEN CHAR(15) = 1 ELSE CHAR(15) = 0
13560
                  = "Y" UK FEM$
= "Y" OR RNK$
                                     = "y" THEN CHAR(16) = 1 ELSE CHAR(16) = 0
13570
        IF RNK$
13580
        IF NOLINE$ = "Y" OR NOLINE$ = "y" THEN CHAR(17) = 1 ELSE CHAR(17) = 0
         IF HORG$ = "Y" OR HORG$ = "y" THEN CHAR(18) = 1 ELSE CHAR(18) = 0
13590
                    = "Y" OR SOS$
13600
         IF SOS$
                                     = "y" THEN CHAR(19) = 1 ELSE CHAR(19) = 0
        IF NOED$
                    = "Y" OR NOED$
13610
                                     = "y" THEN CHAR(20) = 1 ELSE CHAR(20) = 0
                    = "Y" OR USAF$
                                     = "y" THEN CHAR(21) = 1 ELSE CHAR(21) = 0
13620
         IF USAF$
         IF IO$
13630
                    = "Y" OR IO$
                                     = "y" THEN CHAR(22) = 1 ELSE CHAR(22) = 0
         IF TBD1$
                    = "Y" OR TBD1$
                                     = "y" THEN CHAR(23) = 1 ELSE CHAR(23) = 0
13640
                    = "Y" OR TBD2$ = "y" THEN CHAR(24) = 1 ELSE CHAR(24) = 0
13650
         IF TBD2$
13660
         IF TBD3$
                   = "Y" OR TBD3$ = "y" THEN CHAR(25) = 1 ELSE CHAR(25) = 0
         IF TBD4$
                    = "Y" OR TBD4$ = "y" THEN CHAR(26) = 1 ELSE CHAR(26) = 0
13670
         IF TBD5$
                    = "Y" OR TBD5$
                                     = "y" THEN CHAR(27) = 1 ELSE CHAR(27) = 0
13680
13690
         RETURN
13700 REM
13710 REM **
13720 REM **
13730 REM **
              SUBROUTINE TO INITIALIZE/OUTPUT STATS & SEMINAR ASSIGNMENTS
13740 REM **
13750 REM **
13760 REM
         PRINT " INITIALIZING ";
13770
13780
         FOR I = 0 TO 27
             PRINT ".";
13790
13800
             FOR J = O TO 4
                 FOR K = 0 TO 11: STAT(I,J,K) = 0: NEXT K
13810
13820
             NEXT J
         NEXT I
13830
13840
         FOR J = 0 TO 13
             PRINT ",";
13850
```

```
FOR I = 0 TO 44
13860
                  FOR K = 0 TO 5: ASSIGN(I,J,K) = 0: NEXT K
13870
13880
13890
          NEXT J
          RETURN
13900
13910 REM
13920 REM **
13930 REM **
13940 REM **
13950 REM **
               SUBROUTINE TO INITIALIZE RANDOM NUMBER GENERATOR
13960 REM **
13970 REM
13980
          XT = TIME: XT = XT - (INT(XT/100)*100)
13990
          FOR I = 1 TO XT: X = RND: NEXT I
14000
          X = X * 10000: RANDOMIZE X
14010
          STDNT = STAT(0,0,0)
14020
          RETURN
14030 REM
14040 REM **
14050 REM ********************
14080 REM **
14070 REM **
               SUBROUTINE TO RANDOMLY ALLOCATE CHARACTERISTICS TO SEMINARS
14080 REM **
14090 REM
          PRINT: PRINT " ALLOCATING SLOTS TO SEMINARS ";
14100
14110
          FOR J = 1 TO 4
14120
              GOSUB 14870: KO = 1
              FOR I = 3 TO 27
14130
14140
                  IF 1/4 > KO THEN PRINT ".";: KO = KO + 1
14150
                  IF MIX = 1 THEN STAT(I, J, O) = ALOT(I, J, O)
14160
                  ALOT(1,0,0) = STAT(1,0,0)
14170
                  IF STAT(I,J,0) = 0 THEN GOTO 14390
14190
                  TA = STAT(I,J,O) / NS
                                                :REM ** TEMPORARY ALLOCATION **
14190
                  ALOT(I,J,O) = STAT(I,J,O)
14200
                  IF TA < 1 THEN TA = 0: GOTO 14270
14210
                  FOR K = 1 TO LS - FS + 1
14220
                      IF K = MS(1) - FS + 1 THEN GOTO 14260
14230
                      IF K = MS(2) - FS + 1 THEN GOTO 14260
                      IF K = MS(3) - FS + 1 THEN GOTO 14260
14240
14250
                      ALOT(I,J,K) = INT(TA)
                                                  :REM ** GIVE SEMINAR SHARE **
14260
                  NEXT K
14270
                  IF STAT(1, J, 0) - (NS * INT(TA)) = 0 THEN GOTO 14390
14280
                  ADJ = 0
14290
                  FOR K = 1 TO STAT(I,J,O)-(NS * INT(TA)) :REM ** GIVE REST **
14300
                      ADJ = ADJ + 1
14310
                      IF ADJ > 11 THEN ADJ = 1
14320
                      IF ADJ = MS(1) - FS + 1 THEN GOTO 14300
14330
                      1F ADJ = MS(2) - FS + 1 THEN GOTO 14300
14340
                      IF ADJ = MS(3) - FS + 1 THEN GOTO 14300
```

```
14350
                       ALOT(I,J,ADJ) = ALOT(I,J,ADJ) + 1
14360
                       ALOT(O, J, ADJ) = ALOT(O, J, ADJ) + 1
14370
                   NEXT K
                   IF MIX = 1 THEN STAT(I,J,O) = 0
14380
14390
              NEXT I
14400
              ALOT(0,J,0) = STAT(0,J,0)
              TA = 25: ADJ = 0
14410
14420
              FOR K = 1 TO NS
14430
                   ADJ = ADJ + 1
14440
                   IF ADJ = MS(1) - FS + 1 THEN GOTO 14430
                   IF ADJ = MS(2) - FS + 1 THEN GOTO 14430
14450
14460
                   IF ADJ = MS(3) - FS + 1 THEN GOTO 14430
14470
                   ALOT(O, J, ADJ) = INT(ALOT(O, J, O)/NS)
                   IF TA = 25 THEN TA = ALOT(0,J,0) - (ALOT(0,J,ADJ) * NS)
14480
14490
                   IF TA = 0 THEN GOTO 14520
14500
                   ALOT(O, J, ADJ) = ALOT(O, J, ADJ) + 1
14510
                  TA = TA - 1
14520
              NEXT K
14530
              STAT(0,J,0) = 0
14540
          NEXT J
14550
          PRINT
14560
          RETURN
14570 REM
14580 REM **
14590 REM **
14600 REM **
14610 REM **
               SUBROUTINE TO RANDOMLY ASSIGN STUDENTS TO TEMPORARY SEMINARS
14620 REM **
14630 REM
14640
          RS = RND
14650
          FOR LL = 1 TO LS - FS + 1
14660
              IF RS > LL/(LS - FS + 1) GOTO 14750
14670
              TSEM = FS + LL - 1: PS = LL
              FOR R = 1 TO 3
14680
14690
                   IF TSEM = MS(R) THEN GOTO 14720
14700
              NEXT R
14710
              GOTO 14760
              LL = LL + 1
14720
              IF LL > 11 THEN LL = 1
14730
              GOTO 14670
14740
14750
          NEXT LL
14760
          IF MIX = 1 THEN KK = 0 ELSE KK = PS
14770
          IF MIX = 1 THEN JJ = PS ELSE JJ = J
          IF TRONS > 1 THEN PRINT "* DEBUG: J=";J;" JJ=";JJ;" KK=";KK;" PS=";PS
14780
14790
          RETURN
14800 REM
14810 REM **
14820 REM **
```

14830 REM **

```
14840 REM ** SUBROUTINE TO GET SEMINAR DATA FOR SQUADRON
14850 REM **
14860 REM
                                              :REM ** FIRST SEMINAR IN SQ
        FS = VAL(SQ*(J,2))
14870
                                              :REM ** LAST SEMINAR IN SQ
14880
        LS = VAL(SQ*(J,3))
                                              :REM ** MISSING SEMINAR IN SQ **
14890
         MS(1) = VAL(SQ*(J,4))
14900
        MS(2) = VAL(SQ$(J,5))
                                             :REM ** MISSING SEMINAR IN SQ **
        MS(3) = VAL(SQ*(J,6))
14910
                                             :REM ** MISSING SEMINAR IN SQ **
        NS = VAL(SQ*(J,7))
                                              :REM ** # SEMINARS IN SQ
14920
14930
          TS = STAT(0,J,0)
                                              :REM ** TOTAL STUDENTS IN SQ
14940
          RETURN
14950 REM
14960 REM **
14970 REM ****
14980 REM **
               SUBROUTINE TO DETERMINE CURRENT SQUADRON ASSIGNMENT
14990 REM **
15000 REM **
15010 REM
15020
          FOR J = 0 TO 4
15030
          IF VAL(ASQ\$) = VAL(SQ\$(J,1)) THEN GOSUB 14870: GOTO 15060
15040
          NEXT J
15050
         J = 0
          JJ = J
15060
          IF TRONS > 1 THEN PRINT "* DEBUG: FINDING CORRECT SQUADRON - J=": J
15070
15080
          RETURN
15090 REM
15100 REM **
15110 REM ****
15120 REM **
               SUBROUTINE TO FIND OFFSET FOR PRE-ASSIGNED STUDENTS
15130 REM **
15140 REM **
15150 REM
15160
          TSEM = 0
15170
        IF MIX = 1 THEN TSEM = VAL(MIX1$)
         IF MIX = 2 THEN TSEM = VAL(MIX2$)
15180
          IF MIX = 3 THEN TSEM = VAL(MIX3$)
15190
15200
          GOSUB 15290
15210
          RETURN
15220 REM
15230 REM **
15240 REM ****
15250 REM **
               SUBROUTINE TO CHECK AGAINST MISSING SEMINARS
15260 REM **
15270 REM **
15280 REM
15290
          IF TSEM = 0 THEN GOTO 15370
15300
         KK = TSEM - FS + 1
15310
         IF KK >= 0 THEN GOTO 15340
15320
         PRINT "*** ERROR *** SQUADRON "; ASQ$;" AND SEMINAR "; TSEM; " MISMATCH"
```

```
15330
          PRINT "
                    WILL REASSIGN TO NEW SEMINAR ": GOSUB 14560
          IF TSEM = MS(1) AND TSEM <> 0 THEN GOSUB 14640: GOTO 15370
15340
          IF TSEM = MS(2) AND TSEM <> 0 THEN GOSUB 14640: GOTO 15370
15350
15360
          IF TSEM = MS(3) AND TSEM (> 0 THEN GOSUB 14640
15370
          IF TRONS > 1 THEN PRINT "* DEBUG: TSEM=";TSEM;" FINDING CURRENT SMNR"
15380
          RETURN
15390 REM
15400 REM **
15410 REM **
15420 REM **
15430 REM **
               SUBROUTINE TO CHECK ON PREVIOUSLY ASSIGNED STUDENTS
15440 REM **
15450 REM
15460
          IF SWAPFLG$ = "Y" GOTO 15480
          IF SEMI(KK) = 100 GOTO 15680
15470
15480
          MX1FLG = 0: MX2FLG = 0: MX3FLG$ = "N": SASN$ = "Y"
          CN = C: MIX1CNT = O: MIX2CNT = O
15490
          IF SWITCH = 0 THEN SEMI(KK) = 100
15500
15510
          IF TSEM = VAL(MIX1$) AND MIX <> 1 THEN GOTO 15680
15520
          IF TSEM = VAL(MIX2$) AND MIX = 3 THEN GOTO 15680
15530
          FOR AB = 1 TO ASSIGN(TSEM, 0, 0)
15540
              IF MIX <> 1 AND ASSIGN(TSEM, AB, 1) = VAL(MIX1$) THEN MX1FLG = 1
15550
              IF MIX = 3 AND ASSIGN(TSEM, AB, 2) = VAL(MIX2$) THEN MX2FLG = 1
15560
              IF MX1FLG = 0 AND MX2FLG = 0 THEN GOTO 15620
              IF MX1FLG = 1 AND MX2FLG = 1 THEN MX3FLG$ = "Y": GOTO 15680
15570
              IF SLFLAG$ = "Y" AND AB = 1 THEN GOTO 15680
15590
              IF MX1FLG = 1 THEN MIX1CNT = MIX1CNT + 1
15590
              IF MX2FLG = 1 THEN MIX2CNT = MIX2CNT + 1
15600
15610
              CN = CN + 1: MX1FLG = 0: MX2FLG = 0
15620
          NEXT AB
          IF SLFLAG$ = "Y" GOTO 15690
15630
15640
          IF CN >= MAXSTDNTS THEN GOTO 15670
15650
          IF SWITCH = 0 THEN SEMI(KK) = 0: SEMI(12) = 0
15660
          GOTO 15690
          IF SWITCH = 0 THEN SEMI(KK) = CN + 300
15670
          SASN$ = "N"
15680
15690
          IF TRONS > 1 THEN PRINT "* DEBUG: PREV=":SASN*;SLFLAG*:MX3FLG*:CN
15700
15710 REM
15720 REM **
15730 REM **
15740 REM **
15750 REM **
               SUBROUTINE TO CHECK ALLOCATION RESTRICTIONS
15760 REM **
15770 REM
          IF SWAPFLG$ = "Y" GOTO 15810
15780
          IF SEMI(KK) > 300 THEN SASN$ = "N": GOTO 16000
15790
          IF SEMI(KK) = 100 THEN SASN$ = "N": GOTO 16000
15800
15810
          SASN$ = "Y"
```

```
GOSUB 13440
15820
15830
          FOR II = 0 TO 27
              IF (II = 1 OR II = 2) THEN GOTO 15990
15840
15850
              IF II = 0 GOTO 15870
15860
              IF CHAR(II) = 0 THEN GOTO 15990
15870
              IF STAT(II, JJ, KK) < ALOT(II, JJ, KK) THEN GOTO 15990
15880
              FOR LL = 1 TO 11
15890
                   IF ALOT(II, JJ, LL) <= ALOT(II, JJ, KK) THEN GOTO 15950
                   IF STAT(11, JJ, LL) >= ALOT(11, JJ, LL) THEN GOTO 15950
15900
15910
                  TEMP = ALOT(II, JJ, KK)
15920
                   ALOT(II.JJ.KK) = ALOT(II.JJ.LL)
15930
                   ALOT(II,JJ,LL) = TEMP
15940
                  GOTO 15990
15950
              NEXT LL
15960
              IF SWITCH = 0 THEN SEMI(KK) = II + 200
              IF SWITCH = 0 AND II = 0 THEN SEMI(KK) = 100
15970
              SASN$ = "N": GOTO 16000
15980
15990
          NEXT II
16000
          RETURN
16010 REM
16020 REM **
16030 REM **
16040 REM **
               SUBROUTINE TO ASSIGN TO NEW MIX
16050 REM **
16060 REM **
16070 REM
16080
          IF TSEM < 10 THEN Z = 1 ELSE Z = 2
          TSEM$ = MID$(STR$(TSEM), 2, Z)
16090
          IF TSEM < 10 THEN TSEM$ = "O"+MID$(TSEM$.1.1)
16100
          RSET MIXX$ = TSEM$
16110
16120
          RSET PRIOR$ = STR$(PRIOR)
          IF MIX = 1 THEN LSET ASQ$ = SQ$(PS,1)
16130
          SASN$ = "Y"
16140
16150
          RETURN
16160 REM
16170 REM **
16180 REM ***
16190 REM **
16200 REM **
               SUBROUTINE TO ASSIGN SL & ASL TO EACH SEMINAR
16210 REM **
16220 REM
16230
          PRINT: PRINT " ASSIGNING SL & ASL ( PRIORITY = 9 )": PRINT
16240
          SLFLAG$ = "Y": ARFLAG$ = "N"
16250
          SLASLF = 0: MAXSTDNTS = 1
          FOR J = 1 TO 4
16260
16270
              GOSUB 14870: SL(J) = NS: ASL(J) = NS
16280
          NEXT J
          FOR J = 1 TO 44
16290
16300
              ASSIGN(J,0,0) = 2
```

```
16310
          NEXT J
16320
          FOR SSI = 1 TO STDNT
16330
              SI = SSI
16340
              GET #2.51: GET #3.51
              IF TRONS > 1 THEN PRINT "* DEBUG: RCRD="; SI; SNAME$
16350
16360
              IF MIX = 1 GOTO 16410
16370
              IF VAL(RULE$(22)) = 9 AND (10$ = "Y" OR 10$ = "y") GOTO 16400
              IF VAL(RULE$(19)) = 9 AND (SOS$ = "Y" OR SOS$ = "y") GOTO 16400
16380
16390
              GOTO 16410
16400
              LSET MIX3$ = MIX1$
              GOSUB 15020
16410
                                                :REM ** FIND CORRECT SQUADRON **
16420
              GOSUB 14870
                                                :REM ** FIND SEMINAR DATA
              GOSUB 15160
16430
                                                :REM ** FIND OFFSET
              LIS = 0
16440
16450
              IF TSEM > 0 THEN LIS = 1: KK = TSEM - FS + 1
                                                              :REM ** LOCK-IN **
16460
              IOH$ = "
16470
              IF IO$ = "Y" THEN IOH$ = " INTERNATIONAL OFFICER
              IF IO$ = "y" THEN IOH$ = " INTERNATIONAL OFFICER
16480
              IF SOS$ = "Y" THEN IOH$ = " SOS INSTRUCTOR
16490
              IF SOS$ = "y" THEN IOH$ = " SOS INSTRUCTOR
16500
16510
              IF SLASLF = 1 GOTO 17080
                                                               :REM ** DONE
              IF IO$ = "Y" OR IO$ = "y" THEN GOTO 17080
16520
16530
              IF SL$ = "Y" OR SL$ = "y" THEN GOTO 17080
              IF CC$ = "Y" OR CC$ = "y" THEN GOTO 17080
16540
              IF SRO$ = "Y" OR SRO$ = "y" THEN GOTO 17080
16550
              IF MIX < 3 AND (SOS$ = "Y" OR SOS$ = "y") THEN GOTO 17080
16560
              IF MIX = 1 AND (USAF$ <> "Y" AND USAF$ <> "y") THEN GOTO 16800
16570
              IF MIX = 1 AND (NOLINE$ = "Y" OR NOLINE$ = "y") THEN GOTO 16800
16580
              IF TRONS > 1 THEN PRINT "* DEBUG: SL/ASL - LIS="; LIS; SNAME$
16590
16600
              SSL = 0
              FOR I = 0 TO 12: SEMI(I) = 299: NEXT I
16610
              IF MS(1) \Leftrightarrow 0 THEN SEMI(MS(1) - FS + 1) = 100
16620
              IF MS(2) \Leftrightarrow 0 THEN SEMI(MS(2) - FS + 1) = 100
16630
              IF MS(3) \Leftrightarrow 0 THEN SEMI(MS(3) - FS + 1) = 100
16640
16650
              IF LIS = 0 THEN GOSUB 14640
                                                      :REM ** RANDOMLY ASSIGN **
              IF TRONS > 1 THEN PRINT "* DEBUG: TSEM="; TSEM; JJ; KK; SSL; FS; LIS
16660
              IF SEMI(KK) = 100 AND LIS = 0 THEN GOTO 16650
16670
              IF SSL = 1 GOTO 16810
16680
              IF SL(JJ) = 0 GOTO 16800
16690
              IF ASSIGN(TSEM, 1, 0) > 0 GOTO 16750
16700
                                                    :REM ** CHECK CLASSMATES
              SWITCH = 2: GOSUB 15460
16710
              IF SASN$ = "N" GOTO 16750
16720
                                                    :REM ** CHECK CONSTRAINTS **
16730
              SWITCH = 2: GOSUB 15780
                                                   :REM ** ASSIGN AS THE SL **
              IF SASN$ = "Y" GOTO 16960
16740
              IF LIS = 1 THEN GOTO 16800
                                                    :REM ** TRY TO USE AS ASL **
16750
              SEMI(KK) = 100
16760
              FOR I = 1 TO 11
16770
                  IF SEMI(1) = 299 GOTO 16650 : REM ** TRY ANOTHER SEMINAR **
16780
16790
              NEXT I
```

```
16800
              SSL = 1: GOTO 16610
              IF ASL$ = "Y" OR ASL$ = "y" THEN GOTO 16830
16810
                                                    :REM ** DONE WITH ASL'S?
              IF ASL(JJ) <> 0 GOTO 16840
16820
              IF LIS = 1 GOTO 17080 ELSE GOTO 17120
16830
              IF ASSIGN(TSEM. 2.0) > 0 GOTO 16900
16840
              IF ASSIGN(TSEM, 1.0) = 0 GOTO 16900
16850
              SWITCH = 2: GOSUB 15460
                                                    :REM ** CHECK CLASSMATES
16860
              IF SASN$ = "N" GOTO 16900
16870
                                                    :REM ** CHECK CONSTRAINTS **
              SWITCH = 2: GOSUB 15780
16880
              IF SASN$ = "Y" GOTO 16960
                                                     :REM ** ASSIGN AS THE ASL **
16890
              IF LIS = 1 GOTO 17080
16900
16910
              SEMI(KK) = 100
              FOR I = 1 TO 11
16920
                   IF SEMI(I) = 299 GOTO 16650 :REM ** TRY ANOTHER SEMINAR **
16930
16940
              NEXT I
16950
              GOTO 17120
              IF SSL = 0 THEN ASG$ = "SL" ELSE ASG$ = "ASL"
16960
              IF TRONS = 0 THEN GOTO 17000
16970
              PRINT " ASSIGNING "; SNAME$; " # ="; SI; " AS ";
16980
16990
              PRINT ASG$;" FOR SEMINAR "; TSEM;"
                                                        :REM ** UPDATE RECORDS **
17000
              GOSUB 16080: GOSUB 17220
              IF SSL = 0 THEN SL(JJ) = SL(JJ) - 1 ELSE ASL(JJ) = ASL(JJ) - 1
17010
17020
              FOR I = 1 TO 4
17030
                   IF SL(1) <> 0 GOTO 17070
17040
                   IF ASL(1) <> 0 GOTO 17070
17050
              NEXT 1
17060
              SLASLF = 1
                                                 :REM ** GET THE NEXT STUDENT **
17070
              GOTO 17120
17080
              IF TSEM = 0 \text{ GOTO } 17120
                                                 :REM ** CHECK FOR LOCK-INS
              IF TRONS > 0 THEN PRINT " *LOCK IN* "; SNAME$; " TO "; TSEM; IOH$
17090
17100
              PRINT #1, "*LOCK IN* "; SNAME$; " TO "; TSEM; IOH$
17110
              GOSUB 15020: GOSUB 14870: GOSUB 16080: GOSUB 17390
17120
          NEXT SSI
17130
          SLFLAG$ = "N": ARFLAF$ = "N"
                                           :REM ** ALL SL'S & ASL'S ASSIGNED **
17140
          RETURN
17150 REM
17160 REM **
17170 REM
17180 REM **
17190 REM **
               SUBROUTINE TO UPDATE STUDENT RECORDS
17200 REM **
17210 REM
17220
          RETEMP = ASSIGN(VAL(MIXX$),0.0)
17230
          IF SSL = 1 GOTO 17270
17240
          LSET SLX$ = "Y"
                                                           :REM ** UPDATE SL **
17250
          ASSIGN(VAL(MIXX\$),0,0) = 0
17260
          GOTO 17290
          LSET ASLX$ = "Y"
17270
                                                          :REM ** UPDATE ASL **
17280
          ASSIGN(VAL(MIXX\$),0,0) = 1
```

```
17290
          GOSUB 17390
17300
          ASSIGN(VAL(MIXX\$), 0, 0) = RETEMP
17310
          RETURN
17320 REM
17330 REM **
17340 REM *
17350 REM **
               SUBROUTINE TO WRITE OUT STUDENT RECORDS
17360 REM **
17370 REM **
17380 REM
17390
          RSET PRIOR$ = STR$(PRIOR)
17400
          ASSIGN(VAL(MIXX\$),0,0) = ASSIGN(VAL(MIXX\$),0,0) + 1
17410
          ASSIGN(VAL(MIXX\$), ASSIGN(VAL(MIXX\$), 0, 0), 0) = SI
          IF MIX=2 THEN ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$),0,0),1)=VAL(MIX1$)
17420
17430
          IF MIX=3 THEN ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$), 0, 0), 1)=VAL(MIX1$)
17440
          IF MIX=3 THEN ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$), 0, 0), 2) = VAL(MIX2$)
17450
          IF MIX=1 THEN ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$), 0,0),1)=VAL(MIXX$)
          IF MIX=2 THEN ASSIGN(VAL(MIXX*), ASSIGN(VAL(MIXX*), 0, 0), 2)=VAL(MIXX*)
17460
          IF MIX=3 THEN ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$), 0,0),3)=VAL(MIXX$)
17470
          ASSIGN(VAL(MIXX\$), ASSIGN(VAL(MIXX\$), 0, 0), 4) = PRIOR
17480
          ASSIGN(VAL(MIXX\$), ASSIGN(VAL(MIXX\$), 0, 0), 5) = 1R
17490
17500
          RECNUM(SI) = PRIOR + 50
          IF PRVFLG$ = "Y" THEN PREV$ = STR$(MAXSTDNTS): PRVFLG$ = "N"
17510
17520
          FSFLG$ = "N"
17530
          PUT #2,SI: PUT #3,SI
17540
          DELTA = + 1: GOSUB 13270
          IF TRONS < 2 GOTO 17620
17550
                  "* DEBUG: ";STR$(SI);", ";SNAME$;MIXX$;", PRIOR=";PRIOR$;
17560
          PRINT
17570
                   ", ";SLX$;ASLX$;", ";STR$(ASSIGN(VAL(MIXX$),0,0));", ";
          PRINT
17580
          PRINT
                   ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$),0,0),1);
17590
          PRINT
                   ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$),0,0),2);
                   ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$),0,0),3);
17600
          PRINT
                   ASSIGN(VAL(MIXX$), ASSIGN(VAL(MIXX$),0,0),4)
17610
          PRINT
17620
          RETURN
17630 REM
17640 REM **
17650 REM **
17660 REM **
17670 REM **
               SUBROUTINE TO LOCATE ASSIGNED SKILLS TO SWITCH
17680 REM **
17690 REM
          SWTCH = 0
17700
          FOR SLT = 1 TO 11
17710
               IF TRONS > 1 THEN PRINT "* DEBUG: SLT="; SLT; SWTCH
17720
               IF TRONS > 1 THEN LPRINT "* DEBUG: SLT="; SLT; SWTCH
17730
               IF STAT(IR, JJ, SLT) > ALOT(IR, JJ, SLT) THEN GOTO 18580
17740
               IF SEMI(SLT) < 200 OR SEMI(SLT) > 300 THEN GOTO 18590
17750
               TEMP1 = SEMI(SLT) - 200
17760
               TSEM = SLT + FS - 1
17770
```

```
SWITCH = 2: GOSUB 15460: SWITCH = 0
17780
              IF MX3FLG$ = "Y" GOTO 18580
17790
              FOR PTR = ASSIGN(TSEM.O.O) TO 3 STEP -1
17800
                  IF TRONS > 1 THEN PRINT "* DEBUG: PTR=": PTR; SEMI(SLT)
17810
                  IF TRONS > 1 THEN LPRINT "* DEBUG: PTR="; PTR; SEMI(SLT)
17820
                  IF ASSIGN(TSEM, PTR, 4) > PRIOR + OMEGA THEN GOTO 18580
17830
                  SI = ASSIGN(TSEM, PTR, 0)
17840
                  GET #2,SI: GET #3,SI
17850
17860
                  GOSUB 13440
17870
                  IF OMEGA <> 0 GOTO 17900
17880
                  IF FSFLG$ = "Y" AND IR <> 0 AND CHAR(IR) <> 1 GOTO 18570
17890
                  IF FSFLG$ = "N" AND CHAR(TEMP1) <> 1 GOTO 18570
17900
                  DELTA = -1: KK = SLT: GOSUB 13270
                  GET #2.SK: GET #3.SK
17910
17920
                  GOSUB 13440
17930
                  IF SWTCH = 0 G0T0 17970
                  FOR YY = 3 TO 27
17940
                      IF VAL(RULE\$(YY)) = 0 THEN CHAR(YY) = 0
17950
                  NEXT YY
17960
                  SWITCH = 2: KK = SLT
17970
                  GOSUB 15780: SWITCH = 0: TEMP$ = SNAME$: TMP$ = STN$
17980
                  GET #2.51: GET #3.51
17990
                  GOSUB 13440
18000
18010
                  DELTA = +1: KK = SLT: GOSUB 13270
                  IF FSFLG$ = "Y" GOTO 18040
18020
                  IF SASN$ = "N" GOTO 18570
18030
                  IF SWTCH = 0 GOTC 18080
18040
                  FOR YY = 3 TO 27
18050
                      IF VAL(RULE\$(YY)) = 0 THEN CHAR(YY) = 0
18060
18070
                  NEXT YY
                  SWAPFLG$ = "Y"
18080
                  FOR SMNR = FS TO LS
18090
18100
                      IF TRONS > 1 THEN PRINT "* DEBUG: SMNR="; SMNR
                      IF TRONS > 1 THEN LPRINT "* DEBUG: SMNR="; SMNR; FSFLG$; FS
18110
                      IF SMNR = TSEM GOTO 18550
18120
                      IF SMNR = MS(1) GOTO 18550
18130
18140
                      IF SMNR = MS(2) GOTO 18550
18150
                      IF SMNR = MS(3) GOTO 18550
18160
                      IF (MIX = 2 OR MIX = 3) AND SMNR = VAL(MIX1$) GOTO 18550
                      IF MIX = 3 AND SMNR = VAL(MIX2$) THEN GOTO 18550
18170
                      XX = SMNR - FS + 1
18180
18190
                      SWITCH = 2: KK = XX
18200
                      GOSUB 15780: SWITCH = 0
                      IF TRONS > 1 THEN LPRINT "* DEBUG: ALOC=";SASN$;KK;SNAME$
18210
18220
                      IF FSFLG$ = "Y" GOTO 18250
18230
                      IF SASN$ = "N" GOTO 18550
                      TSEM = SMNR
18240
                      SWITCH = 2: GOSUB 15460: SWITCH = 0: TSEM = SLT + FS - 1
19250
                      IF TRONS > 1 THEN LPRINT "* DEBUG: PRV=";SASN$;MX3FLG$;CN
18260
```

```
18270
                      IF MX3FLG$ = "Y" GOTO 18550
                      IF SASN$ = "N" THEN MXFLG$ = "Y": GOTO 18550
18280
18290
                      IF TRONS = 0 \text{ GOTO } 18320
                      PRINT " *** EXCHANGING ***
18300
                      PRINT "
18310
                                               WITH ----- "; SNAME$
                      IF LOGFLG$ <> "Y" THEN GOTO 18350
18320
18330
                      PRINT #1, "*** EXCHANGING *** (STU # "; TMP$; ") "; TEMP$
                      PRINT #1, "..... WITH (STU # ";STN$;") "; SNAME$
18340
18350
                      FOR YY = PTR TO 13
18360
                           TEMPA = ASSIGN(TSEM.PTR.5)
18370
                           FOR R = 0 TO 5
18380
                               IF YY = 13 THEN ASSIGN(TSEM, 13, R) = 0: GOTO 18400
18390
                               ASSIGN(TSEM, YY, R) = ASSIGN(TSEM, YY+1, R)
18400
                               IF R=5 AND ASSIGN(TSEM, YY, 0) = 0 THEN GOTO 18430
                          NEXT R
18410
                      NEXT YY
18420
18430
                      ASSIGN(TSEM, 0, 0) = YY - 1
18440
                      TSEM = SMNR: IR = TEMPA
                      IF LOGFLG$ <> "Y" THEN GOTO 18470
18450
                      PRINT #1, "ASSIGNING "; SNAME$; "# ="; SI; " TO SEMINAR "; TSEM
18460
18470
                      IF TRONS = 0 THEN GOTO 18490
18480
                      PRINT " ASSIGNING "; SNAME$;" # ="; SI; " TO SEMINAR "; TSEM
                      GOSUB 16080: GOSUB 17390
18490
18500
                      IR = INDEX
                                                                :REM ** REMOVE **
18510
                      DELTA = -1: KK = SLT: GOSUB 13270
18520
                      TSEM = SLT + FS - 1
18530
                      SWAPFLG$ = "N"
                      GOTO 18610
18540
18550
                  NEXT SMNR
                  SWAPFLG$ = "N"
18560
              NEXT PTR
18570
18580
              SEMI(SLT) = 100
          NEXT SLT
18590
          SEMI(12) = 2
18600
          SWTCH = 0
18610
          RETURN
18620
18630 REM
18640 REM **
18650 REM
18660 REM **
               SUBROUTINE TO PROCESS REMAINING STUDENTS
18670 REM **
18680 REM **
18690 REM
          NP = STAT(IR,0,0)
18700
18710
          PRINT
          PRINT " ASSIGNING REMAINING "; RL$; " STUDENTS ";
18720
          PRINT " ( PRIORITY = "; PRIOR; ")"
18730
         PRINT
18740
          NP = STAT(IR,0,0)
18750
```

```
IF NP = 0 THEN GOTO 19820
18760
          ARFLAG$ = "N":SLFLAG$ = "N":MXFLG$ = "N":PRVFLG$ = "N":FSFLG$ = "N"
18770
          FOR SSI = 1 TO STONT
18780
18790
              SI = SSI
              IF RECNUM(SI) <> 0 THEN GOTO 19810
18800
18810
              GET #2.51: GET #3.51
              LOGFLG$ = "N": OMEGA = 0
18820
18830
              IF IR = 0 THEN GOTO 18860
18840
              GOSUB 13440
18850
              IF CHAR(IR) = 0 THEN GOTO 19810
              GOSUB 15020
                                                   :REM ** FIND SQUADRON DATA **
18860
18870
              GOSUB 14870
                                                   :REM ** FIND SEMINAR DATA
                                                   :REM ** FIND OFFSET
13880
              GOSUB 15160
18890
              FOR I = 0 TO 12: SEMI(I) = 0: NEXT !
18900
              IF MS(1) \Leftrightarrow 0 THEN SEMI(MS(1) - FS + 1) = 100
              IF MS(2) \Leftrightarrow 0 THEN SEMI(MS(2) - FS + 1) = 100
18910
18920
              1F MS(3) \iff 0 THEN SEMI(MS(3) - FS + 1) = 100
                                                :REM ** RANDOMLY ASSIGN
              GOSUB 14640
18930
              IF TRONS > 1 THEN PRINT "* DEBUG: TSEM="; TSEM; JJ; KK
18940
18950
              SWITCH = 0: GOSUB 15460
                                                :REM ** CHECK PREV CLASSMATES **
18960
              IF SASN$ = "N" THEN GOTO 18990
              SWITCH = 0: GOSUB 15780
                                                :REM ** CHECK ON CONSTRAINTS **
18970
18980
              IF SASN$ = "Y" THEN GOTO 19740
18990
              SEMI(0) = 0: SEMI(12) = 0
19000
              FOR 1 = 1 TO 11
                  IF SEM!(I) = 0 THEN GOTO 18930
19010
                                                            :REM ** TRY AGAIN **
                  IF SEMI(1) > 300 THEN SEMI(0) = 1: GOTO 19040
19020
19030
                  IF SEM!(1) > 200 THEN SEMI(12) = 1
              NEXT I
19040
              IF TRONS < 2 GOTO 19090
19050
              PRINT "* DEBUG: SEMI=":
19060
              FOR ! = 0 TO 12: PRINT SEMI(1);: NEXT |
19070
              PRINT SI; SK: PRINT
19080
              IF SEMI(12) = 1 THEN GOTO 19680
19090
              IF SEMI(0) = 1 GOTO 19140
19100
19110
              IF PRVFLG$ = "N" GOTO 19130
19120
              PREV$ = STR$(MAXSTDNTS): PRVFLG$ = "N": GOTO 19340
19130
              IF MXFLG$ = "Y" THEN GOTO 19200 ELSE GOTO 19330
19140
              SEMI(0) = 0
              FOR I = 1 TO 11
19150
15160ء
                  IF SEMI(I) = 100 GOTO 19190
19170
                  IF MAXSTDNTS (> SEMI(I) - 300 GOTO 19190
19180
                  SEMI(I) = 0
19190
              NEXT I
19200
              MAXSTDNTS = MAXSTDNTS + 1
19210
              IF MXFLG$ = "Y" THEN MXFLG$ = "N": GOTO 18890
19220
              IF MAXSTDNTS <= VAL(PREV$) GOTO 18890
              :F MAXSTDNTS > 9 THEN MAXSTDNTS = VAL(PREV*): GOTO 18990
19230
19240
              PRVFLG$ = "Y": LOGFLG$ = "Y"
```

```
19250
             PRINT #1, "*** WARNING *** UNABLE TO ASSIGN ( #": SI:") ":SNAME$
19260
             PRINT #1. "
                                         TO SEMINAR WITH LESS THAN";
             PRINT #1, MAXSTDNTS - 1:"PREVIOUS CLASSMATES"
19270
19280
             IF TRONS = 0 THEN GOTO 18890
19290
                      *** WARNING *** UNABLE TO ASSIGN ( #"; SI;") "; SNAME$
             PRINT "
19300
             PRINT
                                        TO SEMINAR WITH LESS THAN";
19310
             PRINT MAXSTDNTS - 1; "PREVIOUS CLASSMATES"
19320
             GOTO 18890
19330
             IF LOGFLG$ = "Y" THEN GOTO 19390
19340
             IF TRONS = 0 THEN GOTO 19360
19350
             PRINT " *** FORCING ASSIGNMENT FOR "; SNAME$; "(STU # "; STN$; ")"
19360
             PRINT #1, "** FORCING ASSIGNMENT FOR "; SNAME$
             PRINT #1, ". (STU # "; STN$; ") - RULE FOR "; STAT$(IR)
19370
             LOGFLG$ = "Y"
19380
19390
             SWTCH = 0: KK = 0
19400
             TEMP = 15: L'_{-} = 0
             FOR PTR = 1 TO 11
19410
19420
                 IF SEMI(PTR) = SWTCH GOTO 19470
                 IF MIX <> 1 AND VAL(MIX1$) = PTR + FS - 1 THEN GOTO 19470
19430
19440
                 IF MIX = 3 AND VAL(MIX2\$) = PTR + FS - 1 THEN GOTO 19470
19450
                 IF STAT(O,JJ,PTR) >= ALOT(O,JJ,PTR) GOTO 19470
                 IF TEMP > STAT(0, JJ, PTR) THEN TEMP = STAT(0, JJ, PTR): LL = PTR
19460
19470
             NEXT PTR
19480
             KK = LL: TSEM = KK + FS - 1
19490
             IF TRONS > 1 THEN PRINT"* DEBUG: TSEM":TSEM:KK:SWTCH:FSFLG$:OMEGA
19500
             IF FSFLG$ = "N" GOTO 19600
19510
             IF KK <> 0 THEN GOTO 19670
19520
             IF OMEGA + PRIOR < 5 THEN OMEGA = OMEGA + 1: GOTO 18890
             PRINT #1, "----"
19530
19540
             PRINT #1, "*** CAN'T ASSIGN *** "; SNAME$; " ( # "; STN$; " )"
             PRINT #1. "----"
19550
19560
             PRINT " -----
19570
             PRINT "
                      *** CAN'T ASSIGN *** "; SNAME$; " ( # "; STN$; " )"
19580
             PRINT "
19590
             GOTO 19810
             IF SWTCH > 1 THEN FSFLG$ = "Y": SWTCH = 0: GOTO 18860
19600
             IF TEMP = 15 THEN SWTCH = SWTCH + 1: GOTO 19410
19610
19620
             IF STAT(IR.JJ,KK)>=ALOT(IR.JJ.KK) THEN SEMI(KK)=SWTCH: GOTO 19400
             SEMI(KK) = SWTCH: GOSUB 15460
19630
             IF MX3FLG$ = "Y" THEN SEMI(KK) = SWTCH: GOTO 19400
19640
19650
             IF SWTCH > 0 G0T0 19670
             IF SASN$ = "N" GOTO 19400
13660
19670
             SWTCH = 0: GOTO 19740
19680
             SK = SI: SWTCH = 0
19690
             GOSUB 17700
                                                    :REM ** TRY EXCHANGING **
19700
             SI = SK
             GET #2,SI: GET #3,SI
19710
             GOSUB 13440
19720
19730
             IF SEMI(12) = 2 THEN GOTO 18990
```

```
IF LOGFLG$ <> "Y" THEN GOTO 19770
1974C
19750
              PRINT #1, "ASSIGNING "; SNAME$;" # ="; S1;" TO SEMINAR ";
19760
              PRINT #1. TSEM: "
              IF TRONS = 0 THEN GOTO 19800
19770
19780
              PRINT " ASSIGNING "; SNAME$; " # ="; SI; " TO SEMINAR ";
              PRINT TSEM: "
19790
19800
              GOSUB 13440: GOSUB 16080: GOSUB 17390 : REM ** UPDATE RECORDS **
19810
          NEXT SSI
          RETURN
19820
19830 REM
19840 REM **
19850 REM **
19860 REM **
               SUBROUTINE TO RANDOMLY ALLOCATE CHARACTERISTICS TO SQUADRONS
19870 REM **
19880 REM **
19890 REM
19900
          PRINT " ALLOCATING SLOTS TO SQUADRONS ":
          GOSUB 14870
19910
19920
          ADJ = 0
19930
          FOR ! = 3 TO 27
19940
              PRINT ".":
              IF STAT(1.0.0) = 0 THEN GOTO 20070
19950
              TA = STAT(1,0,0) / 4
19960
                                                 :REM ** TEMPORARY ALLOCATION **
19970
              IF TA < 1 THEN TA = 0: GOTO 20010
19980
              FOR J = 1 TO 4
19990
                  ALOT(I,J,O) = INT(TA)
                                           :REM ** GIVE SQUADRON FAIR SHARE **
              NEXT J
20000
20010
              1F STAT(1,0,0) - (4 * INT(TA)) = 0 THEN GOTO 20070
20020
              FOR L = 1 TO STAT(I,0,0) - (4 * INT(TA))
                                                            :REM ** GIVE REST **
20030
                  ALOT(I,ADJ,O) = ALOT(I,ADJ,O) + 1
                  ADJ = ADJ + 1
20040
                  IF ADJ > 4 THEN ADJ = 1
20050
20060
              NEXT L
          NEXT !
20070
          PRINT
20080
20090
          RETURN
20100 REM
20110 REM **
20120 REM
20130 REM **
20140 REM **
               SUBROUTINE TO OUTPUT RESULTS TO SMART IN ASCII
20150 REM **
20160 REM
20170
          CLS: LOCATE 2,25: PRINT "MIXER OUTPUTTING TO SMSS": PRINT: PRINT
20180
          STDNT = STAT(0,0,0)
20190
          OPEN "O", #1, "STUOUT.ASC"
          k0 = 1: PRINT " OUTPUTTING ":
20200
20210
          FOR SSI = 1 TO STONT
20220
              IF SSI/10 >= KO THEN PRINT ".":: KO = KO + 1
```

```
20230
               SI = SSI
20240
               GET #2,SI: GET #3,SI
20250
               OTREC$ = CHR$(34)+SNAME$+CHR$(34)+","
20260
               OTREC$ = OTREC$+CHR$(34)+STN$+CHR$(34)+"."
               OTREC$ = OTREC$+CHR$(34)+ASQ$+CHR$(34)+","
20270
               OTREC$ = OTREC$+CHR$(34)+MIXX$+CHR<math>$(34)+","
20280
20290
               OTREC$ = OTREC$+CHR$(34)+PRIOR$+CHR$(34)+"."
20300
               OTREC$ = OTREC$+CHR$(34)+SLX$+CHR<math>$(34)+"."
               OTREC$ = OTREC$+CHR$(34)+ASLX$+CHR<math>$(34)+m,
20310
20320
               PRINT #1,0TREC$
          NEXT SSI
20330
          PRINT #1, CHR$ (26)
20340
20350
          CLOSE: RETURN
20360 REM
20370 REM **
20380 REM
```

Appendix Four

SMSS.BAT Program Listing

SMSS.BAT is an MS-DOS batch file. When the user enters "smss" to start the system, this file of MS-DOS commands is called. Its major function is to pass control between SMART and the mixer program.

SMSS.BAT

echo off echo Calling SMART--Standby Please SMSS.BAT--this is the DOS batch file used to call SMSS and control rem rem entry and exit between SMART and the BASIC program, MIXER rem rem After operator enters "smss" from dos, entry is here rem First call the SMART datamanager and project file smss smart d -psmss :smloop Return from SMART either because the user hit Esc at the main menu or because the user has chosen to call the mixer. Existence of file env.asc will be used to test for which. if not exist env.asc goto smexit echo call mixer mixer rem do test for error exit if exist error.sms goto smerr echo Calling SMART -- Standby smart d -psmss rem return could be from exit or mixer call. go back and check goto smloop :smerr echo error exit from mixer :smexit echo exit from smss

TE DA 88